Description of document:	Bureau of Reclamation (USBR) records regarding efficiency and optimization projects at Reclamation facilities, 2016
Requested date:	March 2016
Released date:	22-March-2016
Posted date:	12-December-2016
Source of document:	Bureau of Reclamation DFOIA Officer PO Box 25007, 84-21300 Denver CO 80225-0007 Fax: (303) 445-6575 or (888) 808-5104

From: "Bishop, Clark"
Date: Mar 22, 2016 3:33:07 PM
Subject: Reclamation Optimization
Cc: Max Spiker, Michael Pulskamp

I received your request through my manager, Max Spiker regarding efficiency and optimization projects at Reclamation facilities. In response, I've attached a zip folder containing four files:

Optimization Slides: Slides provide background on Reclamation's standardized hydropower optimization system (hydrOS) and deployment schedule.

USBR MWH HMI Report: Report assesses capacity gains at Reclamation facilities (e.g. generator uprates). Assessment provides Reclamation and our power customers a tool to identify and act on opportunities for capacity gains at our facilities.

FY2016 Q1 Renewable Update: Identifies federal and non-federal renewable energy projects currently online or in development at Reclamation projects. Update also provides information on ongoing turbine replacement and generator rewind projects at Reclamation power facilities.

Generation Gains: Spreadsheet identifies turbine replacement projects and generator uprates completed since 1999 - as well as expected generation benefits resulting from those projects.

I believe these files will provide the information you requested.If you have any questions, please feel free to contact me or my colleagues, Michael Pulskamp or Max Spiker (cc'd).

Thank you.

Clark Bishop
Bureau of Reclamation
Power Resources
Email: cbishop@usbr.gov
Office: 303-445-2908

RECLAMATION

Managing Water in the West



U.S. Department of the Interior
Bureau of Reclamation

Optimization Systems

- **Optimization: continuous computer modeling to determined the optimal operation to achieve desired power production using the least amount of water.**
- **Increases Efficiency**
  - **Uses Less Water at Same Power Output Level**
  - **Or Increase Generation Levels – Use Same Amount of Water**
- **When All Reclamation Plants are Optimized**
  - **1% - 3% Efficiency Gains (410,000 MWh – 1,230,000 MWh)**
  - **$10.3M - $30.8M Annually (at $25 per MWh)**

RECLAMATION

Past Optimization Efforts

- Grand Coulee showed a 2.2% efficiency increase from optimization work (2003-2006)
- Hoover showed a 1.85% efficiency increase from optimization work (2011)
- Yellowtail showed a 1.68% efficiency increase from partial optimization work (2011)

Standardized Optimization System

- First installation of standardized system at Black Canyon Control Center (8/2013)
  - 142,711 MWh – 428,133 MWh
- Once all Reclamation plants are optimized
  - 19 MW – 57 MW of generating capacity
  - 410,000 MWh – 1,230,000 MWh



- Glen Canyon Control Center (ongoing)
- Elephant Butte (ongoing)
- Casper Control Center (ongoing)
- Parker/Davis
- Grand Coulee
- Central Valley Operations

RECLAMATION

RECLAMATION

Managing Water in the West



U.S. Department of the Interior
Bureau of Reclamation

RECLAMATION

Managing Water in the West

Hydropower Modernization Initiative

Assessment of Potential Capacity Increases at Existing Hydropower Plants

U.S. Department of the Interior
Bureau of Reclamation
Sacramento, California

MWH

BUILDING A BETTER WORLD

FINAL - October 2010

Mission Statements

The mission of the Department of the Interior is to protect and provide access to our Nation's natural and cultural heritage and honor our trust responsibilities to Indian Tribes and our commitments to island communities.

The mission of the Bureau of Reclamation is to manage, develop, and protect water and related resources in an environmentally and economically sound manner in the interest of the American public.

Assessment of Potential Capacity Increases at Existing Hydropower Plants

Hydropower Modernization Initiative

Prepared for

United States Department of the Interior
Bureau of Reclamation

Prepared by

MWH

BUILDING A BETTER WORLD

U.S. Department of the Interior
Bureau of Reclamation
Denver, Colorado

FINAL - October **2010**

This page left blank intentionally.

MWH

BUILDING A BETTER WORLD

October 26, 2010

U.S. Bureau of Reclamation
Denver Federal Center
Bldg. 67 (86-61600)
P.O. Box 25007
Denver, CO 80225-0007

Attn: Mr. Michael Pulskamp

Subject: Final Report on Assessment of Capacity Increases at Existing Hydroelectric Plants

Ref: USACE Contract No. W9127N-10-D-0004, MWH Americas, Inc., Task Order 0002

Dear Michael,

Enclosed is our final report assessing capacity gains at existing United States Bureau of Reclamation (Reclamation) hydroelectric plants. This work was performed under Task 2 of our IDIQ contract with the US Army Corps of Engineers (USACE) for the Hydropower Modernization Initiative, Bureau of Reclamation.

The report presents the results from creating energy simulation models at Reclamation hydropower plants, and developing a comprehensive valuation of benefits from potential capacity increases at all plants. The primary authors of the report were John Haapala and Jill Gray.

MWH appreciates the opportunity to work with Reclamation on this interesting assignment. We hope this document provides useful results regarding potential capacity additions and will help direct future investigation efforts toward the plants that have the most potential. We enjoyed our collaboration with both Reclamation and USACE on this study and look forward to additional opportunities to be of service

Thank you.

John Haapala (for)

Nancy Walker
Project Manager
MWH Americas, Inc.

encl: Final Report

2353 - 130th Avenue NE
Suite 200
520 Corporate Center
Bellevue, Washington 98005 United States

TEL +1 425 896 6900
FAX +1 425 602 4020
www.mwhglobal.com

This page left blank intentionally.

Disclaimer

The findings, interpretations of data, recommendations, specifications or professional opinions presented in this report are based upon available information at the time the report was prepared. Studies described in this report were conducted in accordance with generally accepted professional engineering and geological practice, and in accordance with the requirements of the Client. There is no other warranty, either expressed or implied.

The findings of this report are based on the readily available data and information obtained from public and private sources. MWH relied on this information provided by others and did not verify the applicability, accuracy or completeness of the data. Additional studies (at greater cost) may or may not disclose information that may significantly modify the findings of this report. MWH accepts no liability for completeness or accuracy of the information presented and/or provided to us, or for any conclusions and decisions that may be made by the Client or others regarding the subject site or project.

The cost estimates developed for the report are prepared in accordance with the cost estimate classes defined by the Association for the Advancement of Cost Engineering. MWH has no control over costs of labor, materials, competitive bidding environments and procedures, unidentified field conditions, financial and/or market conditions, or other factors likely to affect the cost estimates contained herein, all of which are, and will unavoidably remain, in a state of change, especially in light of the high volatility of the market attributable to market events beyond the control of the parties. These estimates are a "snapshot in time" and the reliability of these cost estimates will inherently degrade over time. MWH cannot and does not make any warranty, promise, guarantee, or representation, either express or implied, that proposals, bids, project construction costs, or cost of operation or maintenance will not vary substantially from MWH's good faith Class 5 cost estimate.

This report was prepared solely for the benefit of the Client. No other entity or person shall use or rely upon this report or any of MWH's work product unless expressly authorized by MWH. Any use of or reliance upon MWH's work product by any party, other than the Client, shall be solely at the risk of such party.

This page left blank intentionally.

Executive Summary

There has recently been a considerable resurgence of interest in hydropower in the USA. The current interest in hydropower has been primarily directed at developing incremental hydropower where an existing dam, or an existing dam and powerhouse can be utilized. Incremental hydropower can be developed through efficiency increases in existing units and/or by the addition of capacity to utilize flow for generation that would be otherwise spilled at existing dams. One of the driving forces behind the increased interest in electricity generation from hydropower plants is that greenhouse gas (GHG) emissions from hydropower are virtually zero when compared to thermal generation from fossil fuels. Additional clean hydropower generation would offset or reduce GHG emissions from fossil fuel-fired generation.

Reclamation has 58 existing hydroelectric plants with a total installed capacity of about 15,000,000 kilowatts (kW) (15,000 megawatts [MW]). This report assesses the potential for capacity increases at the 58 existing hydroelectric plants that could potentially generate additional power. Also included in the report is an estimated quantification of incremental energy increases from efficiency gains that would result from replacement of older turbine runners with new runners of modern design. A final task involves the estimation of potential GHG offsets that could be credited to the incremental energy increases or the avoidance of outages at the existing plants.

Due to the large number of plants involved, these studies were performed at the planning-level (reconnaissance-level)) for purposes of screening between plants. Additional more detailed feasibility-level studies of individual plants would be needed to make final investment decisions at those specific plants that show promise for capacity additions in this study.

Because the “best” capacity addition from an economic standpoint was not known in advance, five capacity additions of different sizes were tested for each plant. The capacity additions tested at each plant were 10%, 20%, 30%, 40%, and 50% of the existing combined nameplate capacities (the installed capacity). For each of the alternative capacity additions, a benefit to cost ratio (BCR) and a net present value (NPV) were determined. The preferred capacity addition would have either the maximum benefit to cost ratio (if it was greater than 1.00) or the maximum net present value (if positive).

The determination of benefits from a capacity addition requires the estimation of the average incremental energy generation, which is developed with a hydroelectric energy simulation model. An energy model was developed that could simulate up to 30 years of daily energy generation at each of the 58 existing plants. Plant specific input data to the energy model was supplied by Reclamation that included reservoir outflows and elevations, and many

characteristics of the existing hydroelectric plants. Results generally showed reasonable agreement between the simulated and recorded generation, which satisfactorily validates the model.

In addition to the energy generation in megawatt-hours (MWh), the value of energy ($/MWh) and capacity ($/kW-yr) must be known to determine the total benefits of a capacity addition. The value of energy was developed on a regional basis for each of the plants based on information obtained from the Energy Information Administration, Department of Energy. The value of energy was separated into on-peak and off-peak hours. The value of capacity was also developed based on information obtained from the Energy Information Administration, Department of Energy and is a variable function of the relative amount of energy associated with each capacity addition, so the more incremental energy, the higher the capacity value.

An estimate of the costs associated with each plant capacity addition was necessary to evaluate the benefit to cost ratios and net present values. The cost estimates included construction, mitigation, and operation and maintenance costs. The cost estimating methodology was taken from a 2007 Federal report (U.S. Department of the Interior, et al, 2007), known as the 1834 study, on potential hydroelectric development at existing Federal facilities. Notably, the 1834 study excluded the 58 existing Reclamation plants that are studied herein because it was thought at that time that with few exceptions, the existing plants were either originally constructed or had already been uprated so that they were then currently sized to the available flow.

Results of this study show that only 10 of the 58 plants have potential capacity additions of any size with positive NPVs, which corresponds to a BCR greater than 1.00 and is an indicator of economic feasibility. The 10 plants that show initial promise for capacity additions (Table ES-1) are mostly among the smallest of the 58 plants. Selecting the capacity addition at each of the 10 plants that has the highest benefit to cost ratio would result in a total capacity addition of about 67 MW. The additional 67 MW capacity would represent less than one-half of one percent of the existing total nameplate capacity of the 58 plants. If maximum NPV was the criterion for selecting the capacity addition (Table ES-2), the economic capacity addition would rise to about 143 MW, still less than one percent of the existing total nameplate capacity. The Palisades hydropower plant has the highest net present value.

Table ES-1. Capacity Opportunities – Ranked by Benefit to Cost Ratio

Rank [1]	Plant	Region	Existing Installed Capacity (MW)	Maximum BCR Percent Increase	Maximum NPV Percent Increase	Maximum BCR Capacity Increase (MW)	Maximum BCR	Maximum NPV ($M)
1	Shoshone	Great Plains	3.0	50%	50%	1.5	3.50	$12.2
2	Black Canyon	Pacific Northwest	10	50%	50%	5.1	2.52	$19.6
3	Boise Diversion	Pacific Northwest	3.5	40%	50%	1.4	2.48	$7.8
4	Palisades	Pacific Northwest	177	20%	50%	35	2.28	$123
5	Canyon Ferry	Great Plains	50	10%	40%	5.0	1.53	$13.4
6	Guernsey	Great Plains	6.4	50%	50%	3.2	1.52	$4.6
7	Nimbus	Mid-Pacific	13.5	20%	50%	2.7	1.39	$5.8
8	Minidoka	Pacific Northwest	28	10%	20%	2.8	1.21	$2.6
9	Deer Creek	Upper Colorado	5.0	10%	20%	0.5	1.04	$0.1
10	Crystal	Upper Colorado	31.5	30%	30%	9.5	1.00	$0.1

Notes

[1] Plants are ranked based on the capacity addition increment with the highest BCR for each plant .

BCR - Benefit to Cost Ratio

NPV - Net Present Value

Table ES-2. Capacity Opportunities – Ranked by Net Present Value

Rank [1]	Plant	Region	Existing Installed Capacity (MW)	Maximum BCR Percent Increase	Maximum NPV Percent Increase	Maximum NPV Capacity Increase (MW)	Maximum BCR	Maximum NPV ($M)
1	Palisades	Pacific Northwest	177	20%	50%	88	2.28	$123
2	Black Canyon	Pacific Northwest	10	50%	50%	5.1	2.52	$19.6
3	Canyon Ferry	Great Plains	50	10%	40%	20	1.53	$13.4
4	Shoshone	Great Plains	3.0	50%	50%	1.5	3.50	$12.2
5	Boise Diversion	Pacific Northwest	3.5	40%	50%	1.7	2.48	$7.8
6	Nimbus	Mid-Pacific	14	20%	50%	6.8	1.39	$5.8
7	Guernsey	Great Plains	6.4	50%	50%	3.2	1.52	$4.6
8	Minidoka	Pacific Northwest	27.7	10%	20%	5.5	1.21	$2.6
9	Deer Creek	Upper Colorado	5.0	10%	20%	1.0	1.04	$0.1
10	Crystal	Upper Colorado	32	30%	30%	9.5	1.00	$0.1

Notes

[1] Plants are ranked based on the capacity addition increment with the highest NPV for each plant .

BCR - Benefit to Cost Ratio

NPV - Net Present Value

It can be concluded that 10 of the 58 plants show some promise for capacity additions that could be investigated in more detail in future studies. But it must also be concluded that if the capacity additions were implemented in the sizes indicated by this planning-level study, the resulting additions would increase the total capacity of the 58 existing Reclamation plants by less than 1%. This conclusion generally supports the assertion in the 2007 Federal study that the existing Reclamation hydroelectric plants are with few exceptions currently economically sized to the available flow.

Additional results presented in detail in subsequent chapters of this report show substantial potential for generation increases from efficiency gains that would result in substantial offsets of greenhouse gasses (GHGs) from fossil fuel-fired

generation. Table ES-3 shows the ten plants with the largest opportunities for annual generation increases due to efficiency improvements at the existing units, provided the potential efficiency improvements are at least 3%. One plant in the Pacific Northwest Region, Hungry Horse, and a few plants in the Mid-Pacific Region top the list. A total of 36 plants could potentially increase their annual generation by more than 3%.

Table ES-3. Largest Efficiency Gain Opportunities – Plants with >3% Potential Increases

Rank [1]	Plant	Region	Installed Capacity	Annual Average Existing Generation	Incremental Generation from Efficiency Improvements	
			(MW)	(MWh/yr)	(MWh/yr)	(%)
1	Hungry Horse	Pacific Northwest	428	930,345	49,272	5.3
2	Spring Creek	Mid-Pacific	180	590,037	36,681	6.2
3	Trinity	Mid-Pacific	140	517,251	31,209	6.0
4	New Melones	Mid-Pacific	382	470,677	29,916	6.4
5	Keswick	Mid-Pacific	117	461,014	25,762	5.6
6	Canyon Ferry	Great Plains	50	380,509	25,391	6.7
7	Palisades	Pacific Northwest	177	706,936	22,716	3.2
8	San Luis [2]	Mid-Pacific	424	304,679	20,490	6.7
9	Morrow Point	Upper Colorado	173	363,625	19,421	5.3
10	Flatiron [3]	Great Plains	94.5	241,042	14,436	6.0

Notes

[1] Plants are ranked based on the percent of additional generation from efficiency improvements over their existing annual (simulated) generation.

[2] Installed capacity of 424 MW for San Luis includes the Federal and CA shares. The Federal share is 202 MW.

[3] Installed capacity at Flatiron is 94.5 MW. Only Units 1 and 2 (81.3 MW) were included in the modeling.

In addition to generation increases, three potential ways of achieving GHG offsets were determined. Table ES-4 shows the total GHG offset opportunities for each of the five regions. GHG offsets from efficiency improvements and from capacity increases are based on the capacity addition increment from each plant that yielded the highest BCR. GHG offsets from avoided outages is a concept that was developed as part of the asset investment planning process. Results for individual plants are also presented in Chapter 9, Summary of Results.

Table ES-4. Potential GHG Reduction Opportunities by Region

Region	GHG Offsets from Incremental Generation from Efficiency Improvements		GHG Offsets from Incremental Generation from Hydraulic Capacity Increases [1]		GHG Offsets from Avoided Energy Losses [2]	
	(MWh/yr)	metric tons CO2e/yr	(MWh/yr)	metric tons CO2e/yr	(MWh/yr)	metric tons CO2e/yr
Mid-Pacific	186,818	84,961	187,735	69,129	527,348	243,476
Upper Colorado	81,627	63,134	116,853	67,246	473,221	373,756
Lower Colorado	141,191	79,612	30,833	15,993	77,649	43,783
Pacific Northwest	193,491	106,405	142,011	63,803	398,253	215,777
Great Plains	144,159	77,825	105,692	45,683	584,088	302,024

Notes

[1] Incremental GHG offsets are based on the summation of the hydraulic capacity increase increment for each plant with the highest BCR.

[2] GHG offsets from avoided energy losses are based on a generic split between on-peak and off-peak hours depending on whether the plant is operated as a peaking, base load or intermediate plant.

GHG - Greenhouse Gas

Costs and economic benefits were not assigned to the efficiency gains or greenhouse gas offsets in this study. A cost/benefit analysis was not performed for potential efficiency gains because this more detailed level of analysis is performed in the Asset Investment Planning Tool that is included in a separate task under the current overall contract. GHG offsets were not assigned dollar values because there is currently a great deal of uncertainty regarding their future valuation.

This page left blank intentionally.

Contents

Tables

Figures

Appendices

Abbreviations and Acronyms

%	percent
$/kW	dollars per kilowatt
$/kW-yr	dollars per kilowatt per year
$/MWh	dollars per megawatt hour
AIP	Asset Investment Planning
BCR or B/C	benefit to cost ratio
cfs	cubic feet per second
CH_4	methane
CO_2	carbon dioxide
CO_2e	carbon dioxide equivalents
CO_2e/yr	carbon dioxide equivalents per year
DO	dissolved oxygen
EIA	Energy Information Administration
EMM	Electricity Market Module
FERC	Federal Energy Regulatory Commission
GHG	greenhouse gas
GWh	gigawatt hour
HMI	Hydropower Modernization Initiative
INEEL	Idaho National Engineering and Environmental Laboratory
kW	kilowatt
lb/MWh	pounds per megawatt-hour
MB	megabyte
MW	megawatt
MWh	megawatt hour
N_2O	nitrous oxide
NERC	North American Electric Reliability Corporation
NPV	net present value
O&M	operations and maintenance
PLEESM	Planning Level Energy and Economics Study Model
Reclamation	United States Department of the Interior, Bureau of Reclamation
TPUD	Trinity Public Utilities District
U.S.	United States
USACE	U.S. Army Corps of Engineers

This page left blank intentionally.

Chapter 1
Introduction

The United States Department of the Interior, Bureau of Reclamation (Reclamation) has been tasked by the Secretary of Interior and the Commissioner of Reclamation to determine the potential for generator uprating and turbine efficiency gains at all Reclamation hydropower projects. In conversations with the U.S. Army Corps of Engineers (USACE), it came to the attention of the Power Resources Office that there was an ongoing effort to not only quantify this potential at USACE projects, but to assess the investment needs of 54 USACE projects and to develop a tool to provide ongoing analysis. The USACE has contracted with MWH Americas to conduct this study.

Reclamation has partnered with the USACE Hydropower Modernization Initiative (HMI) effort to assess the investment needs of all Reclamation hydropower projects, and as a part of this effort, to quantify the uprating and efficiency gains that can be made at these facilities. The work covers 58 Reclamation hydropower projects in five Regions. This study was authorized as a part of USACE Contract No. W9127N-10-D-0004 with MWH Americas, Task Order No. 2, Hydropower Modernization Initiative, Bureau of Reclamation.

Scope

The scope of work for this study is contained in the following tasks outlined as a part of Task No. 2, Hydropower Modernization Initiative, Bureau of Reclamation:

Task 5: Implement Analytical Model to Assess Capacity and Efficiency Gain Opportunities. This resource assessment should quantify Reclamation's potential capacity and efficiency gains through equipment upgrades within existing environmental, water delivery, and other regulatory constraints for (initially) 58 Reclamation power plants. All opportunities must include a benefit/cost ratio and must be ranked according to greatest benefit. The results of this modeling will be reported independently (Reference Task 7) and incorporated into the Investment Plans.

Task 6: Develop Environmental and Climate Change Benefits. The Contractor shall develop environmental criteria including quantitative and qualitative criteria related to climate change, greenhouse gas (GHG) reduction, and other site specific environmental benefits and/or impacts to habitat, water quality or recreational activities. Climate change benefits are to be based on energy production estimates of each project. The environmental and climate change

benefits estimates shall be integrated into the Analytic Model development task (Reference Task 5).

Task 7: Prepare a Final Report on Capacity and Efficiency Gain Opportunities. The Contractor shall prepare a final report which describes the methodologies used, the data quality measures taken, the analytical models developed, the capacity/efficiency gains that can be made at Reclamation facilities, the benefit/cost ratio of those opportunities, and the environmental and climate change benefits.

Objectives

The objectives of the potential capacity and efficiency gains study can be briefly summarized as follows:

- Assess the potential for capacity additions at each of 58 Reclamation plants with existing hydropower;
- Estimate costs for the capacity additions;
- Present capacity addition results in terms of benefit to cost ratios (BCR) and net present values (NPV);
- Provide quantitative results for potential GHG reductions;
- Estimate energy gains through efficiency increases;
- Summarize the methodology and results in a report.

Because the optimum capacity addition at each plant was not known in advance, results for a range of capacity additions were developed at each plant. A number of major steps were required to arrive at the final BCR and NPV results, which included:

- Determine the energy associated with each increment of capacity addition at each plant;
- Develop energy values ($/MWh) and capacity values ($/kW-yr) by region over the economic period of analysis;
- Develop construction, mitigation, and operation and maintenance (O&M) costs for each increment of capacity addition;
- Develop an economic methodology and parameters that will provide the final BCR and NPV results;
- Quantify GHG reduction opportunities from capacity increases, efficiency gains, outage reductions;
- Develop a data quality rating for each plant as a measure of the quality and completeness of the data input to the energy model;

Each of these major steps and the final results are presented in the following chapters of the report.

Limitations

Due to the large number of plants involved, these studies were performed at the planning-level (screening or reconnaissance-level), not at the feasibility-level. Future studies could refine the results for individual plants that showed promise for capacity additions. This study is suitable for evaluating, screening and prioritizing across the group of 58 Reclamation plants. Future studies of specific plants would be required to evaluate the final feasibility of specific capacity additions and/or efficiency improvements at specific plants.

No site visits to the existing hydroelectric plants were made within the scope of this study. Site specific investigations of the physical or operational potential to add capacity were not conducted for this study, but could be the focus of future more detailed studies at selected plants. Physical and operational limitations could preclude capacity additions at some plants.

Ongoing plans and plant rehabilitation activities at various facilities at Reclamation have not been included in this report. This report is based on the currently available completed capacities at the existing plants.

Cost estimates were based on parametric equations, which is an appropriate method for a planning-level study.

The few pumped-storage units at the existing plants were simulated as conventional hydro units. Full consideration of the hourly operation and special economics of pumped storage units would essentially require a separate study that is beyond the scope of this study.

This page left blank intentionally.

Chapter 2
Summary of Reclamation Existing Hydroelectric Facilities

Existing Hydroelectric Facilities

This chapter provides background information on the existing Reclamation hydroelectric plants included in this study. Much of the information in this chapter was either supplied by Reclamation personnel or obtained from the Reclamation web site. The Reclamation facilities and operations are divided into five regions, as shown on Figure 2-1.

Figure 2-1. Reclamation Regions

Of the 58 Reclamation facilities with existing hydropower plants included in this report, 21 are in the Great Plains Region, 3 are in the Lower Colorado Region, 12 are in the Mid-Pacific Region, 10 are in the Pacific Northwest Region, and 12 are in the Upper Colorado Region. The 58 hydropower plants have a total of 194 units that have a combined total of 14,966,186 kW (14,966 MW) of capacity.

Of the 58 existing hydropower plants, Grand Coulee alone has about 45% of the total generating capacity. Grand Coulee includes 27 conventional hydro units

and 6 pump-generating units. About 68% of the total Reclamation generating capacity is contained in three plants, which are Hoover, Glen Canyon, and Grand Coulee. The location of the existing plants is shown on Figure 2-2.Table 2-1 presents a summary of data for the 58 existing Reclamation hydropower plants.

Figure 2-2. Reclamation Existing Hydroelectric Plant Locations

Table 2-1. Reclamation Existing Hydroelectric Plants

Plant Number	USBR Region Name	Project Name	Site Name	Location	In Service Date	Number of Units	Total Nameplate Capacity (kW)
1	Great Plains	Kendrick	Alcova	Alcova, WY	Jul-55	2	41,400
2	Great Plains	Colorado-Big Thompson	Big Thompson	Loveland, CO	Apr-59	1	4,500
3	Great Plains	Pick-Sloan Mo. Basin	Boysen	Thermopolis, WY	Aug-52	2	15,000
4	Great Plains	Pick-Sloan Mo. Basin	Buffalo Bill	Cody, WY	Jul-92	3	18,000
5	Great Plains	Pick-Sloan Mo. Basin	Canyon Ferry	Helena, MT	Dec-53	3	50,000
6	Great Plains	Colorado-Big Thompson	Estes	Estes Park, CO	Sep-50	3	45,000
7	Great Plains	Colorado-Big Thompson	Flatiron	Loveland, CO	Jan-54	3	94,500
8	Great Plains	Pick-Sloan Mo. Basin	Fremont Canyon	Alcova, WY	Dec-60	2	66,800
9	Great Plains	Pick-Sloan Mo. Basin	Glendo	Glendo, WY	Dec-58	2	38,000
10	Great Plains	Colorado-Big Thompson	Green Mountain	Kremmling, CO	May-43	2	26,000
11	Great Plains	North Platte	Guernsey	Guernsey, WY	Jul-10	2	6,400
12	Great Plains	Shoshone	Heart Mountain	Cody, WY	Dec-48	1	5,000
13	Great Plains	Pick-Sloan Mo. Basin	Kortes	Sinclair, WY	Jun-50	3	36,000
14	Great Plains	Colorado-Big Thompson	Marys Lake	Estes Park, CO	May-51	1	8,100
15	Great Plains	Fryingpan-Arkansas	Mt. Elbert	Twin Lakes, CO	Jun-81	2	200,000
16	Great Plains	Pick-Sloan Mo. Basin	Pilot Butte	Morton, WY	Jan-10	2	1,600
17	Great Plains	Colorado-Big Thompson	Pole Hill	Loveland, CO	Jan-54	1	38,238
18	Great Plains	Kendrick	Seminoe	Sinclair, WY	Aug-39	3	51,750
19	Great Plains	Pick-Sloan Mo. Basin	Shoshone	Cody, WY	Jun-92	1	3,000
20	Great Plains	Pick-Sloan Mo. Basin	Spirit Mountain	Cody, WY	Oct-94	1	4,500
21	Great Plains	Pick-Sloan Mo. Basin	Yellowtail	Hardin, MT	Aug-66	4	250,000
22	Lower Colorado	Parker-Davis	Davis	Bullhead City, AZ	Jan-51	5	255,000
23	Lower Colorado	Boulder Canyon	Hoover	Boulder City, NV	Sep-36	19	2,078,800
24	Lower Colorado	Parker-Davis	Parker	Parker Dam, AZ	Dec-42	4	120,000
25	Mid-Pacific	Central Valley	Folsom	Folsom, CA	May-55	3	207,000
26	Mid-Pacific	Central Valley	Judge Francis Carr	French Gulch, CA	May-63	2	154,400
27	Mid-Pacific	Central Valley	Keswick	Redding, CA	Oct-49	3	117,000
28	Mid-Pacific	Central Valley	Lewiston	Lewiston, CA	Feb-64	1	350
29	Mid-Pacific	Central Valley	New Melones	Jamestown, CA	Jun-79	2	382,000
30	Mid-Pacific	Central Valley	Nimbus	Folsom, CA	May-55	2	13,500
31	Mid-Pacific	Central Valley	O'Neill	Los Banos, CA	Nov-67	6	25,200
32	Mid-Pacific	Central Valley	San Luis (1)	Los Banos, CA	Mar-68	8	202,000
33	Mid-Pacific	Central Valley	Shasta	Redding, CA	Jun-44	7	714,000
34	Mid-Pacific	Central Valley	Spring Creek	Redding, CA	Jan-64	2	180,000
35	Mid-Pacific	Washoe	Stampede	Truckee, CA	Jan-88	2	3,650
36	Mid-Pacific	Central Valley	Trinity	Redding, CA	Feb-64	2	140,000
37	Pacific Northwest	Boise	Anderson Ranch	Mountain Home, ID	Dec-50	2	40,000
38	Pacific Northwest	Boise	Black Canyon	Emmet, ID	Dec-10	2	10,200
39	Pacific Northwest	Boise	Boise River Diversion	Boise, ID	May-10	3	3,450
40	Pacific Northwest	Yakima	Chandler	Benton City, WA	Feb-56	2	12,000
41	Pacific Northwest	Columbia Basin	Grand Coulee	Grand Coulee, WA	Mar-41	33	6,809,000
42	Pacific Northwest	Rogue River Basin	Green Springs	Ashland, OR	May-60	1	17,290
43	Pacific Northwest	Hungry Horse	Hungry Horse	Columbia Falls, MT	Oct-52	4	428,000
44	Pacific Northwest	Minidoka	Minidoka	Rupert, ID	May-10	4	27,700
45	Pacific Northwest	Palisades	Palisades	Palisades, ID	Feb-57	4	176,564
46	Pacific Northwest	Yakima	Roza	Yakima, WA	Aug-58	1	12,937
47	Upper Colorado	Colorado River Storage	Blue Mesa	Gunnison, CO	Sep-67	2	86,400
48	Upper Colorado	Colorado River Storage	Crystal	Montrose, CO	Jun-78	1	31,500
49	Upper Colorado	Provo River	Deer Creek	Heber, UT	Feb-58	2	4,950
50	Upper Colorado	Rio Grande	Elephant Butte	Truth or Consequences, NM	Nov-40	3	27,945
51	Upper Colorado	Colorado River Storage	Flaming Gorge	Dutch John UT	Nov-63	3	151,950
52	Upper Colorado	Seedskadee	Fontenelle	La Barge, WY	May-68	1	10,000
53	Upper Colorado	Colorado River Storage	Glen Canyon	Page, AZ	Sep-64	8	1,320,000
54	Upper Colorado	Collbran	Lower Molina	Molina, CO	Dec-62	1	4,860
55	Upper Colorado	Dolores	McPhee	Cortez, CO	Dec-92	1	1,283
56	Upper Colorado	Colorado River Storage	Morrow Point	Montrose, CO	Dec-70	2	173,334
57	Upper Colorado	Dolores	Towaoc	Cortez, CO	May-93	1	11,495
58	Upper Colorado	Collbran	Upper Molina	Molina, CO	Dec-62	1	8,640
Totals						**194**	**14,966,186**

Note (1): For San Luis, 202,000 kW represents the Federal share of the 424,000 kW installed capacity. The plant is operated by the State of California.

Reclamation Uprating Program

Following the 1973 oil embargo, a review was made of Reclamation's powerplants to determine if they could be uprated to a higher capacity and to produce more energy. Uprating existing hydroelectric powerplants to fully utilize the available water resource for additional energy and peaking capacity was recognized as one of the better long range additions that could be made to help solve the energy problem. In 1978, the Bureau of Reclamation and the Department of the Interior established, as one of their major program goals, the investigating and implementing of all viable opportunities to improve existing plants by modernizing and uprating the generating equipment. Since 1978, Reclamation initiated a power uprating program to increase the capacity of Reclamation facilities as funding and unit availability allowed. In addition, there have been a number of generator rewinds where no appreciable uprate potential existed but winding condition was poor.

Uprating hydroelectric generator and turbine units at existing power plants are one of the most immediate, cost effective, and environmentally acceptable means for developing additional electrical power. As a result of the uprating program, the generating capacity of over one-third of Reclamation's hydroelectric generators has been increased, with almost a 50 percent average increase in generating capacity of each unit.

An uprate normally involves an increase in rating of more than 15 percent, which in turn necessitates a review of the capability and limits of all of the power equipment, from the penstock through the turbine, generator, bus, switchgear, transformer, and transmission system. These systems can then either be retained, modified or replaced in order to develop and accommodate the selected uprate level.

A good indicator for considering uprating a generator is when the turbine capability substantially exceeds the generator capability at normal operating heads. Most Reclamation turbines are designed to provide rated output (or nameplate capacity) at rated head. Since the rated head was chosen far enough below the maximum operating head to ensure the generator overload capacity could be utilized, reservoirs often operate at heads much higher than rated and the turbine is usually capable of more mechanical output than the generator can convert to electrical energy. In these and other situations, increased rating and efficiency can be obtained by runner replacement. For pre-1960 turbines, it is frequently possible to obtain output increases as high as 30 percent and efficiency increases of 1.5 percent in comparison to new original equipment by replacing existing runners with runners of modern design. A summary of the unit uprates performed by Reclamation to date is presented in Table 2-2. Uprate projects that are currently in-progress are not included in Table 2-2.

Between the original sizing of the hydroelectric plants and the uprating program, Reclamation regional staff has previously indicated that they believe there is little or no surplus water at existing Reclamation hydroelectric plants to warrant additional units. In the recent study, *Potential Hydroelectric Development at Existing Federal Facilities* (U.S. Department of the Interior, et al, 2007) that is commonly known as the 1834 Study, it was stated that with few exceptions, the existing Reclamation generation facilities have been sized to their available hydrology, many over 30 years ago. There was such confidence in this statement that all of the existing Reclamation hydroelectric facilities were completely excluded from the 1834 study, a planning-level study of potential hydroelectric development at existing Federal facilities.

The current studies described in this report began and were performed with no pre-conceived conclusions on the potential for, or viability of, capacity additions at the existing Reclamation hydroelectric plants.

Table 2-2. Reclamation Unit Uprates

Plant	Units	Each Unit Old Rating (kW)	Each Unit New (kW)	Percent Increase	Added kW Plant	Year Uprate Completed
Anderson Ranch	2	13,500	20,000	48.1%	13,000	1983
Black Canyon	2	4,000	5,100	27.5%	2,200	1995
Blue Mesa	2	30,000	43,200	44.0%	26,400	1995
Boise River Diversion	3	500	1,150	130.0%	1,950	2005
Crystal	1	28,000	35,000	25.0%	7,000	2004
Flaming Gorge	3	36,000	50,495	40.3%	43,485	1992
Flatiron	2	31,500	43,020	36.6%	23,040	1983
Fremont Canyon	2	24,000	33,400	39.2%	18,800	1989
Glen Canyon	2	118,750	165,000	38.9%	92,500	1987
Glen Canyon	3	118,750	165,000	38.9%	138,750	2006
Glen Canyon	3	118,750	165,000	38.9%	138,750	2009
Glendo	2	12,000	19,000	58.3%	14,000	1983
Hoover	2	82,500	127,000	53.9%	89,000	1989
Hoover	12	82,500	130,000	57.6%	570,000	1992
Hoover	1	95,000	130,000	36.8%	35,000	1992
Hoover	1	40,000	61,500	53.8%	21,500	1992
Hoover	1	50,000	68,500	37.0%	18,500	1992
Hungry Horse	4	71,250	107,000	50.2%	143,000	1993
Judge Francis Carr	2	70,722	77,200	9.2%	12,956	2010
Keswick	3	25,000	39,000	56.0%	42,000	1991
Minidoka	1	2,400	3,000	25.0%	600	1996
Morrow Point	2	60,000	86,667	44.4%	53,334	1993
Palisades	2	28,500	44,141	54.9%	31,282	1994
Palisades	2	30,875	44,141	43.0%	26,532	1995
Shasta	2	75,000	142,000	89.3%	134,000	2008
Shasta	3	75,000	142,000	89.3%	201,000	2005
Trinity	2	50,000	70,000	40.0%	40,000	1984
Totals	**67**	**3,875,094**	**5,813,673**	**48.4%**	**1,938,579**	

Generator rewinds can increase the nameplate capacity of the units. Many of the older Reclamation generators were purchased with a continuous overload capability of 15 percent above rated output (“nameplate rating”), which was the effective standard for rating generators at that time. When “rewinding" a generator, the new winding is purchased with a base rating equal to or greater than 115 percent of the original generator nameplate rating, using the appropriate allowable temperature rise consistent with the insulation class of the new winding. If the new winding is capable of operation at levels higher than 115% of the original nameplate rating, the machine would typically still be limited to operation at its new base rating level, unless the mechanical and

structural characteristics of the generator were confirmed to be capable of higher loads. Ratings of the bus, unit breakers, transformer, etc. are examined for capability to accommodate the new generator rated capacity, and detailed studies and selected replacements are performed as required to accommodate the new output capacity.

Table 2-3 presents a summary of the unit rewinds to date of Reclamation generators where the new base rating of the generators was 115% of their original nameplate rating. Note that, in these cases, only the *nameplate* rating changed; the actual generating capacity did *not* increase.

Table 2-3. Reclamation Unit Rewinds

Plant	Units	Year	kW Added
Alcova	2	2001-2002	5,400
Davis	5	1974-2003	30,000
Elephant Butte	3	1990-2002	3,645
Flatiron	2	1978-96	1,660
Folsom	3	1962-72	36,720
Grand Coulee	18	1968-2004	306,000
Green Mountain	2	1982	2,400
Green Springs	1	2005	1,290
Guernsey	2	1993	1,600
Pole Hill	1	1987	4,988
Seminoe	3	1978-80	19,350
Spring Creek	2	1981-82	30,000
Total	**44**		**443,053**

So, from the above tables, 67 units have had increased nameplate capacity and increased actual generating capacity, and an additional 44 units have had increased nameplate capacity without any increase in actual generating capacity. A total of 111 of the 194 units (57%) have had an uprate or a rewind.

This page left blank intentionally.

Chapter 3
Energy Model

An energy model is the fundamental tool used to determine the increased energy output, and therefore the benefit, that is available from a capacity addition. An energy model can also be called a power study model or an operation model. This chapter details the energy model used to simulate the 58 existing Reclamation hydroelectric plants and the capacity additions.

Objectives of PLEESM

The energy model used in this study is called the Planning Level Energy and Economics Study Model (PLEESM). PLEESM is a new model designed specifically for the objective of performing planning-level simulation of the energy production of a large number of hydroelectric plants in a relatively short amount of time. The model has also been directed at the task of investigating several alternative capacity additions at each plant in a single run. The determination of benefit/cost ratios and net present values is done within PLEESM for each capacity addition alternative. PLEESM was also designed to provide results for input to the Asset Investment Planning (AIP) tool. As a planning level model, PLEESM was intended to find the more promising of many alternatives. It was not intended to simulate energy production in the ultimate detail that would need to be incorporated into feasibility or final design studies.

Methodology

PLEESM is a sequential streamflow simulation model that operates on a daily time increment. PLEESM is an Excel© spreadsheet based model that was designed to simulate the daily energy generation at multiple hydroelectric plants for a period of up to 30 years. A key simplification of the PLEESM model is that total reservoir outflow is an input to the model, whereas reservoir inflow is input to some other power study models and outflow is determined by the model. Using reservoir outflow as model input is made possible in this study because all of the reservoirs have existed for many years. Using historic reservoir outflows as input data also implies that future reservoir operation will be essentially the same as historical/existing reservoir operation.

PLEESM includes provision for the modeling of up to eight separate existing turbine-generator units that may have varying capacities. PLEESM allocates flow to units in order, such that the hydraulic capacity of Unit 1 is completely utilized on a given day before any flow is allocated to Unit 2, with a similar

pattern repeated through Unit 8. Herein this utilization pattern is termed logical units, and it contrasts with the roughly equal utilization that would typically occur with actual physical units. The logical unit concept is incorporated into the model for two reasons: (1) the same procedure clearly determines the flow allocated to capacity additions of different sizes; and (2) if one, two, or three units were on outage, the amount of generation lost can be directly determined for input to the AIP tool. For the two plants that had more than eight existing units, Grand Coulee and Hoover, units were aggregated into eight logical units. As discussed below in Simulation Accuracy, this assumption/ simplification still yielded good correlation with actual historical generation.

The PLEESM model consists of a single calculation engine with specific plant data read-in from other spreadsheets. The plant to be simulated is specified from a drop-down list. Although the model operates on a daily time increment, provision for the characterization of hourly or peaking operation is included by the specification of the percentage of generation that occurs on-peak and off-peak. Unless more specific information was supplied for a plant, peaking plants were assumed to generate 85% of their total energy on-peak, base load plants had 46% of their energy on-peak, and combined operation plants had 65% of the total energy on-peak, with all remaining energy being off-peak. It is noted that pumped-storage units are simulated as conventional hydroelectric units, without consideration of the pumping cycle. The detailed hourly operation cycles and the economic justification for pumped-storage units are different from conventional units and beyond the scope of this study.

Because the optimum potential capacity addition was not known in advance, five different capacity additions were tested to provide a range of values from which a curve of benefit to cost ratios and net present values could be plotted. The potential capacity additions were taken as 10%, 20%, 30%, 40%, and 50% of the existing nameplate plant capacity. Prior to modeling of the plants, it was thought that the maximum benefit to cost ratio would occur at 50% capacity addition or less. In addition to the up to eight existing units, the capacity increases were developed in the model as five additional virtual units. Because the method of capacity addition is unspecified in this study, the five additional virtual units should not be taken as corresponding to the addition of five actual units.

PLEESM also incorporates the economic cost and benefit calculations that are described in subsequent chapters of this report. The detailed results included in Appendix A were copied directly out of PLEESM. Due to the detailed energy and economics calculations for a total of 13 logical units, the model is a rather large spreadsheet that is about 35 MB in size.

Model Input

Model input data for the simulation of hydroelectric generation is divided into two general types, time-series data and plant parameter data. Both of these types of data were supplied for each of the 58 plants by Reclamation. Where some of the data was unavailable for certain plants, reasonable assumptions or calculation procedures were used to estimate the necessary data.

Time-series data input to the model included:

- Total outflow (all hydraulic pathways)
- Turbine flow
- Head, or reservoir elevation, and tailwater
  - Gross head input directly
  - Reservoir elevation and tailwater used to calculate gross head (time-series or rating curve)
- Existing historic generation; used for model verification

Plant parameter data included the following:

- Hydraulic capacity of each unit
- Required non-power releases (irrigation, fish, etc.)
- Unit efficiencies, existing and modified
- Head losses
- Percent of time the plant generation is on-peak and off-peak

Model Output

Model output was organized into tables and plots on the various model tabs. Model output includes:

- Long-term average energy – original and upgraded units
- Monthly and annual on-peak and off-peak energy
- Energy potentially lost in outages of various duration for up to three units out
- Month to start outage to minimize the financial impact from the generation lost
- Energy gained with capacity increases
- Plots and summary tables

- Sheet with tabulated parameters for import to the AIP tool
- Economics

Figures 3-1 through 3-4 are examples of plots for Keswick that are automatically developed within PLEESM for each plant. Figure 3-1 is a plot of flow duration through each unit and for five potential capacity additions. Keswick has three existing units (Units 1-3) and Figure 3-1 shows that the great majority of the available flow can by utilized by the existing units. The five smaller color bands (virtual Units 9-13) are the flow that could be utilized by the five potential increments of additional capacity. Figure 3-2 shows the monthly distribution of flow through each of the existing units and potential capacity addition increments. Figures 3-3 and 3-4 show typically good agreement between simulated and actual generation for monthly and daily generation, respectively. Figure 3-4 displays daily generation developed from monthly data by making all daily data input equal to the monthly average.



Figure 3-1. Flow Thru Existing Keswick Units and Potential Capacity Additions



Figure 3-2. Keswick Average Monthly Energy Distribution



Figure 3-3. Keswick Simulated and Actual Monthly Generation



Figure 3-4. Simulated and Actual Keswick Daily Generation

Interface with AIP Tool

PLEESM was designed to provide results for input to the AIP tool. The AIP tool incorporates risk management principles to guide hydroelectric equipment investments to maximize the return on investment for a given level of service. Parameters determined in PLEESM and transferred to the AIP tool include:

- Existing and upgraded unit on-peak and off-peak average monthly energy in logical unit order
- Upgraded unit on-peak and off-peak average monthly energy corresponding to a selected capacity increase
- For outages having durations of one to twelve months, the month when the outage should be scheduled to start to minimize financial losses is determined.

Simulation Accuracy

Simulation accuracy is a measure of the agreement between the simulated and recorded generation. Reasonable agreement between simulated and actual generation validates the data input and the modeling procedure. With few

exceptions, the simulation accuracy was generally good. Simulated generation was usually higher than actual generation for at least three reasons. First, simulation of the existing units assumed the efficiencies would correspond to new, original condition. This was due to the required interface with the AIP tool which performs the unit degradation with age. Second, uprates have occurred over time such that simulated generation based on the current capacity will show greater generation than actual data based on the pre-uprate recorded generation. And finally third, historic outages were not directly simulated. The simulation accuracy is summarized in Table 3-1.

Table 3-1. Summary of Simulation Accuracy

% Difference between Simulated and Actual Generation	Number of Plants	% of Total	Cumulative % of Total
± 0 - 5%	21	37%	37%
± 5 - 10%	19	33%	70%
± 10 - 15%	8	14%	84%
± 15 - 20%	4	7%	91%
± 20 - 25%	4	7%	98%
± 25 - 30%	1	2%	100%
± > 30%	0	0%	-

An example of how uprates affect the simulation accuracy is shown on Figure 3-5 for Palisades, which was uprated in 1994-95. For the months with the highest generation prior to 1995, the existing generation was substantially less than the simulated generation. This is because the model includes the current uprated capacity for the entire period of the simulation. For 1995 and later, the simulation is excellent, even though the simulation accuracy shows a 12% difference between simulated and actual generation.



Figure 3-5. Palisades Simulated and Actual Monthly Generation

A second example is Minidoka, which had an uprate in 1996. The effects of the uprate are clearly shown in the years prior to, and after 1996. Minidoka also exhibits an apparent outage in 1996. In the more recent years, the simulation becomes excellent. Despite a simulation statistic that shows a difference between simulated and actual of almost 30%, the energy model simulation of the current configuration is as good as can be expected.



Figure 3-6. Minidoka Simulated and Actual Monthly Generation

This page left blank intentionally.

Chapter 4
Economics

This chapter provides the economic parameters, methodology, and example calculation details of the costs and benefits associated with the capacity additions for each plant. The economic analysis defines the capacity addition amounts that would be most beneficial from a purely economic viewpoint. This is usually determined by selecting the alternative having the maximum NPV, or the highest BCR. The BCR and NPV values can also be used as a means to rank the most beneficial capacity additions among the 58 plants.

Definitions

The following definitions define terms as they are used in this study:

- Benefit to Cost Ratio (BCR or B/C) – The present value of total benefits divided by the present value of total costs
- Discount Rate – Time value of money used to convert or aggregate costs and benefits occurring at various times to a common point in time.
- Net Present Value (NPV) – The present value of the total benefits minus the present value of the total costs.
- Nominal Values (nominal dollars, nominal discount rate) – Includes the effects of expected or historic inflation. Costs expressed in nominal dollars are in terms of the cost in the year spent. Benefits expressed in nominal dollars are in terms of the benefit in the year realized.
- Present Value – The present value provides a means to determine and compare total costs or benefits over time. A series of annual values in nominal dollars should not be totaled in an economic analysis as the dollar values are not equivalent. The discount rate is used to adjust dollar values over time to current dollar values.
- Real (or Constant Dollar) Values – Values adjusted to eliminate the effects of expected or historic inflation.
- Levelized capital cost – Represents the present value of the total capital cost and fixed O&M costs of building and operating a generating plant over its financial life, amortized to equal annual payments.

The economic analysis for this study uses nominal values.

Economic Parameters

The economic analysis was performed using several basic economic parameters and assumptions as summarized below:

- Period of economic analysis – 50 years; 2015 through 2064
- On-line date for all alternatives – 2015
- Discount rate – 4.375%. Applicable to Federal water resources planning and reflects Federal ownership (Federal Register, 2010).
- Inflation rate – 1.8%. Based on the differential between a long-term (30-year) real interest rate of 2.7% (OMB 2009) and the nominal interest rate of 4.5%, an inflation rate of 1.8% is implied.
- Energy value escalation – includes a variable annual real escalation plus 1.8% per year for inflation.
- Capacity escalation – Capacity values are constant in nominal dollars as they are assumed to represent levelized capital costs
- O&M escalation rate – 2.3% (consisting of 1.8% inflation plus 0.5% real escalation)
- Annual costs and benefits – expressed in nominal dollars
- Present value year – 2010
- Interest rate – not applicable as the construction and mitigation costs are included as a single capital cost and are not amortized

Because ownership and funding for the capacity additions is expected to be Federal, a 4.375% discount rate is applicable (OMB 2009). If private ownership and financing were involved, the discount rate would be higher and use of a different interest rate for amortization may be necessary. Depending on the ownership and financing source, the applicable discount rate could range from 4.375% to about 12%. For example, a typical discount rate used by a large investor owned utility could be about 8.0%. Because of the sensitivity of the results to the selected discount rate, examples of varying the discount rate are shown in Example Economic Results Description.

Costs and Benefits

Costs and benefits include several components that are discussed in more detail in subsequent chapters. Cost components include:

- Initial construction cost
- Mitigation costs
- Fixed and variable annual O&M costs

Benefits include annual values for:

- On-peak energy (MWh) times the annual value of on-peak energy ($/MWh)
- Off-peak energy (MWh) times the annual value of off-peak energy ($/MWh)
- Capacity ($/kW-year), which is a variable depending on the incremental capacity factor of the added capacity times the added capacity (kW)

Example Economic Results Description

Because the optimal capacity addition for any plant is not known in advance, economic results were determined for capacity additions in five increments of 10%, 20%, 30%, 40%, and 50% of the existing installed capacity. It was thought that the most beneficial capacity additions would in most cases be less than 50% of the existing installed capacity. Plotting curves of the economic results for the various capacity additions can enhance comprehension of the results.

Examples of the detailed economic results, which are provided for each of the 58 plants in Appendix A, are presented in the following figures for a hypothetical plant with an existing installed capacity of 100 MW. To show the sensitivity of the results to the range of potential discount rates, Figures 4-1, 4-2, and 4-3 have identical input except for discount rates of 4.375%, 8.0% and 12.0%. The hypothetical plant used for the figures is capable of generating substantial additional energy as shown by the total incremental capacity factor. Capacity factor is a ratio (or percent) that represents the actual generation divided by the generation that could be obtained if the incremental capacity was run at full output for the entire year. For example, 40 MW of capacity could potentially generate 350,400 MWh (40 MW times 8,760 hours in a year). If the actual annual average generation was 87,600 MWh, the capacity factor would be 25% (87,600/350,400 – times 100 to convert to a percentage).

Numerical values plotted on the following figures are tabulated above the figures. The construction and mitigation total cost represents the initial capital investment. The construction and mitigation cost is also shown in the table above the figures in terms of $/kW as a reference value. The maximum BCR ratio and the maximum net present value typically do not occur at the same capacity addition value as shown in the example.

The results show that while the maximum BCR always occurs for a 20% capacity addition, the maximum benefit to cost ratio drops from 2.85 with a discount rate of 4.375%, to 2.02 with a discount rate of 8%, to 1.50 with a discount rate of 12.0%. The maximum net present value (in millions of dollars)

drops even more dramatically from $97.4 at a 40% capacity addition with a 4.375% discount rate, to $34.2 at a 30% capacity addition with an 8.0% discount rate, to $11.8 at a 30% capacity addition with a 12.0% discount rate. The range of these results should be of interest to private developers that may consider capacity additions.

Percent Capacity Increase	Capacity Increase (MW)	Average Incremental Energy (MWh/yr)	Total Incremental Capacity Factor	Construction & Mitigation Total Cost ($M)	Construction & Mitigation Total Cost ($/kW)	PV of Total Costs ($M)	PV of Energy Benefits ($M)	PV of Capacity Benefits ($M)	PV of Total Benefits ($M)	NPV of Total Benefits ($M)	B/C Ratio
10%	10.0	35,040	40%	$15.5	$1,551	$22.0	$38.6	$21.9	$60.5	$38.4	2.74
20%	20.0	61,320	35%	$27.4	$1,369	$38.4	$67.5	$41.8	$109.4	$71.0	2.85
30%	30.0	78,840	30%	$38.2	$1,274	$53.2	$86.8	$59.9	$146.7	$93.6	2.76
40%	40.0	87,600	25%	$48.5	$1,211	$67.0	$96.5	$67.9	$164.4	$97.4	2.45
50%	50.0	87,600	20%	$58.3	$1,165	$80.2	$96.5	$69.9	$166.4	$86.2	2.07



Figure 4-1. Example Economic Details Results - 4.375% Discount Rate

Percent Capacity Increase	Capacity Increase (MW)	Average Incremental Energy (MWh/yr)	Total Incremental Capacity Factor	Construction & Mitigation Total Cost ($M)	Construction & Mitigation Total Cost ($/kW)	PV of Total Costs ($M)	PV of Energy Benefits ($M)	PV of Capacity Benefits ($M)	PV of Total Benefits ($M)	NPV of Total Benefits ($M)	B/C Ratio
10%	10.0	35,040	40%	$15.5	$1,551	$14.7	$17.2	$11.4	$28.6	$13.9	1.95
20%	20.0	61,320	35%	$27.4	$1,369	$25.6	$30.1	$21.8	$51.8	$26.2	2.02
30%	30.0	78,840	30%	$38.2	$1,274	$35.6	$38.7	$31.1	$69.8	$34.2	1.96
40%	40.0	87,600	25%	$48.5	$1,211	$44.9	$43.0	$35.3	$78.3	$33.3	1.74
50%	50.0	87,600	20%	$58.3	$1,165	$53.9	$43.0	$36.3	$79.3	$25.5	1.47



Figure 4-2. Example Economic Details Results - 8% Discount Rate

Percent Capacity Increase	Capacity Increase (MW)	Average Incremental Energy (MWh/yr)	Total Incremental Capacity Factor	Construction & Mitigation Total Cost ($M)	Construction & Mitigation Total Cost ($/kW)	PV of Total Costs ($M)	PV of Energy Benefits ($M)	PV of Capacity Benefits ($M)	PV of Total Benefits ($M)	NPV of Total Benefits ($M)	B/C Ratio
10%	10.0	35,040	40%	$15.5	$1,551	$10.7	$8.9	$6.6	$15.4	$4.7	1.44
20%	20.0	61,320	35%	$27.4	$1,369	$18.8	$15.5	$12.5	$28.1	$9.3	1.50
30%	30.0	78,840	30%	$38.2	$1,274	$26.1	$20.0	$18.0	$37.9	$11.8	1.45
40%	40.0	87,600	25%	$48.5	$1,211	$33.0	$22.2	$20.3	$42.5	$9.6	1.29
50%	50.0	87,600	20%	$58.3	$1,165	$39.5	$22.2	$20.9	$43.1	$3.6	1.09



Figure 4-3. Example Economic Details Results - 12% Discount Rate

Note that Tables 4-1 through 4-3 were for a hypothetical plant with an existing installed capacity of 100 MW.

Chapter 5
Energy and Capacity Benefits

The benefits from capacity additions at the 58 plants are based on the costs of an equivalent increment of an alternative thermal plant that would be offset by the additional hydropower. Benefits are developed in more detail in the following chapters, but in a simplified and approximate manner, benefits can be expressed in the following alternative terms:

Benefits = capacity + on-peak and off-peak energy

= fixed costs + variable costs

= capital costs + operating costs

= (construction costs + fixed O&M) + (fuel costs + variable O&M)

Energy Benefits

The Energy Information Administration has developed a system to provide 25 year forecasts and analyses of energy-related activities, including electricity prices as a component of the *Annual Energy Outlook* (EIA 2010a). The Electricity Market Module (EMM) represents the capacity planning, generation, transmission, and pricing of electricity. Energy values ($/MWh) for this study were developed for the appropriate EMM region. Average annual energy values were then distributed to monthly values on a regional basis to account for the seasonal timing of the additional capacity generation (EIA 2010c). EMM regions were defined by the Energy Information Administration (EIA 2010a) as shown on Figure 5-1. All of the 58 Reclamation plants in this study are in regions 11, 12, or 13.

1 East Central Area Reliability Coordination Agreement (ECAR)
2 Electric Reliability Council of Texas (ERCOT)
3 Mid-Atlantic Area Council (MAAC)
4 Mid-American Interconnected Network (MAN)
5 Mid-Continent Area Power Pool (MAPP)
6 New York (NY)
7 New England (NE)
8 Florida Reliability Coordinating Council (FL)
9 Southeastern Electric Reliability Council (SERC)
10 Southwest Power Pool (SPP)
11 Northwest Power Pool (NPP)
12 Rocky Mountain Power Area, Arizona, New Mexico, and Southern Nevada (RA)
13 California (CA)

Figure 5-1. Electricity Market Module Regions

Benefits were separated into on-peak and off-peak energy values and capacity values. To provide market prices for energy and capacity, values were developed based on information available from the Department of Energy, Energy Information Administration (EIA), *Annual Energy Outlook* (EIA, 2010). The specific data used to develop the energy and capacity values is contained in a spreadsheet available on the Internet at the following location:

http://www.eia.doe.gov/oiaf/aeo/supplement/sup_elec.xls

The relevant base information is contained in Tables 82, 83, and 84 of the above referenced spreadsheet for Electric Power Projections for Regions 11, 12, and 13. The energy values used in this study do not appear directly in the EIA tables, but are calculated from information in the table.

After a review of a number of possibilities, it was determined that energy values based on the average of two methods would be most appropriate. In the first method, on-peak energy values are based on the value of gas-fired generation, while off-peak generation values are based on the value of coal-fired generation. The general formulas used in the energy value calculations are as follows:

Energy value = fuel costs + variable operating costs

Variable operating costs = 20% of fuel costs

On-peak energy fuel = gas

Off-peak energy fuel = coal

Generation in the following formula is based on the particular fuel type.

$$Energy\ value\ \left(\frac{\$}{MWh}\right) = \frac{Fuel\ price\ \left(\frac{\$}{Btu}\right) * Fuel\ consumption\ (Btu) * 1.2}{Generation\ (MWh)}$$

In the second method, regional information obtained from Federal Energy Regulatory Commission (FERC) Form 714 (Annual Electric Balancing Authority Area and Planning Authority Area Report) is used to determine the on-peak and off-peak energy values. On FERC Form 714, the system "lambda" is reported for each hour of the year, where "lambda" represents the marginal cost of electricity for the given hour. From these values, the ratio of the marginal cost of energy during on-peak and off-peak hours can be determined as a ratio to the 24-hour average marginal cost of energy. The average cost of thermal generation for the EMM region as determined from the EIA data is then adjusted by these ratios. The on-peak and off-peak energy values used for each region are taken as the average of the two methods. On-peak is the 16-hour period generally from 6 am to 10pm (more specifically, the 16 hour period with the highest values); other hours are off peak.

Figure 5-2 shows the results for real and nominal values of on-peak and off-peak energy analysis for the Northwest Power Pool area (Region 11 on Figure 5-1). Up to 2035, real escalation was as determined from the EIA data, and an annual inflation rate of 1.8% was added. For years 2045 and beyond, a real escalation rate of 0.5% was assumed, which was less than the average real escalation rate up to 2035. In the period from 2036 to 2044, annual real escalation rates were estimated that would smoothly transition from the higher real escalation rates prior to 2035 to the lower real escalation rates beginning in 2045. An annual inflation rate of 1.8% was added for all years. For 2045 and beyond, the effective energy value annual escalation rate is 2.3%.

The projections beyond 2035 are based on the calculated compounded growth rate for the last 10 years of the DOE projected horizon, 2025 to 2035. This growth rate is generally applied to extrapolate values to 2064. However, in some cases, the rate is high, resulting in unreasonable out-year values. A limiting growth rate of 0.5% was specified. If the calculated 2025 to 2035 growth rate is less than the limiting growth rate, the calculated growth rate is applied from 2036 and beyond. If the calculated 2025 to 2035 growth rate is greater than the limiting growth rate, the calculated rate is reduced linearly each year from 2036 to 2045, and the limiting growth rate is used thereafter.



Figure 5-2. Real and Nominal Energy Values for the Northwest Power Pool

In a similar manner, Figure 5-3 shows the results for real and nominal values of on-peak and off-peak energy analysis for the Rocky Mountain Power Area (Region 12 on Figure 5-1), and Figure 5-4 shows the energy values for California (Region 13 on Figure 5-1).



Figure 5-3. Real and Nominal Energy Values for the Rocky Mountain Power Area



Figure 5-4. Real and Nominal Energy Values for California

Capacity Benefits

The capacity value represents the per kilowatt annualized capital cost and other fixed costs associated with the alternative thermal plant. Capacity values have the units of dollars per kilowatt per year ($/kW-yr). In some studies, benefits are developed solely from "all-in" energy values in which capacity benefits are included as a component of the energy value. In many other studies (this one included), benefits are developed from separate annual capacity and energy values. It was known in advance that many of the Reclamation plants would develop little or no additional energy as a result of the potential capacity additions. If there was zero additional energy associated with a capacity increase, the "all-in" energy values would result in zero benefits for the capacity increase. At a minimum, because the existing Reclamation plants have upstream regulating reservoirs, the added capacity would have some potential to occasionally move some energy from off-peak hours to higher-valued on-peak hours. Additionally, added hydropower capacity may have increasing value in the future for integration of renewable energy, such as wind power. Including separate capacity and energy values in the structure of the economic analysis provides for the explicit variable inclusion of capacity valuation, and for the future capability to adjust the value of added capacity for cases with little or no added energy.

The capacity values were developed from a note associated with the *Annual Energy Outlook* 2010 (EIA 2010b). A $/kW-yr capacity value can be derived by using EIA projections of capacity additions and EIA estimates of capital costs. Because the EIA data is based on U.S. average levelized values, the capacity values were constant for all regions in all years. The EIA estimates a conventional combined cycle generation resource entering service in 2016 and operating at a capacity factor of 87 percent carries a annual fixed cost of about 200 $/kW/yr, and a conventional combustion turbine entering service in 2016 operating at a capacity factor of 30% carries an annual cost of 120 $/kW/yr. At 0% capacity factor, the capacity value was estimated to be about 10% of the 30% capacity factor value, or 12 $/kW-yr. The resulting incremental capacity values as a function of capacity factor is shown on Figure 5-5.



Figure 5-5. Capacity Value as a Function of Incremental Capacity Factor

It should be noted that the useful life of most thermal alternatives is 30 years, rather than the 50 to 100-year life assumed for hydro plants. It is assumed that, should the alternative thermal plant be constructed, it would be replaced by an identical plant at appropriate intervals through the hydro project's life (30, 60, and 90 years). As long as the thermal plant cost increases over this period are limited to those resulting from general inflation, the amortized present value of the fixed costs for the series of identical thermal plants over 100 years (adjusted to remove the effects of general inflation) will be identical to the amortized present value of the initial thermal plant amortized over its 30-year life. As a result, capacity values are normally computed simply on the basis of the initial thermal plant's 30-year life. It is very likely that the replacement plants will not be identical to the initial plant, but it is difficult to predict 30 years in advance if the replacement plant will be more or less expensive (in today's dollars) than the initial plant. Because of the uncertainty about future inflation and because the present value of the future replacement plants is relatively small, basing capacity values on the initial thermal plant's service life is considered to be reasonable (USACE 1985). Therefore, the capacity values shown on Figure 5-3 were assumed to remain constant over the 50-year economic life.

To be allocated economic benefits, the capacity should be dependable capacity. While procedures for determining dependable capacity can vary by region, dependable capacity essentially means that the capacity will be available with a high reliability when needed, at least for short periods of time. Because most of

the Reclamation plants have storage reservoirs associated with them, it has been assumed in this planning-level study that the capacity would be available on demand. To the extent that site specific operating limitations restrict the ability to use the additional capacity when needed, the capacity benefits could be reduced. More detailed future feasibility studies could refine the estimate of dependable capacity.

Chapter 6
Capacity Addition Cost Estimates

A cost estimating methodology was needed that would be applicable to potential capacity additions at all 58 existing hydropower sites and which could be developed quickly for five capacity additions at each plant. The Idaho National Engineering and Environmental Laboratory (INEEL) has developed such a methodology under contract to the U.S. Department of Energy (INEEL 2003). A collection of sources of historical hydroelectric plant data was used by INEEL to create cost estimating equations. Costs are not based on site specific conditions at the individual plants, which would be the subject of future studies.

Because it was determined that the various costs correlated with plant capacity, cost estimating equations were developed as a function of installed capacity. The cost estimating equations developed for existing dams with existing hydropower plants were used in this study. These cost estimating equations were also used in a more recent study of potential hydroelectric development at existing Federal facilities (U.S. Department of the Interior, et al, 2007) that is commonly known as the 1834 Study.

The following are the formulas for each cost category, where MW is the additional installed capacity in megawatts (expressed in 2002 dollars):

- Construction cost = $1{,}400{,}000*MW^{0.81}$
- Fish and wildlife mitigation cost = $83{,}000*MW^{0.96}$
- Recreation mitigation cost = $63{,}000*MW^{0.97}$
- Historical and archaeological mitigation cost = $63{,}000*MW^{0.72}$
- Water quality monitoring cost = $70{,}000*MW^{0.44}$
- Fixed annual O&M = $24{,}000*MW^{0.75}$
- Variable annual O&M = $24{,}000*MW^{0.80}$

It is noted that in the 1834 Study, the coefficient for the annual O&M costs is apparently incorrectly shown as 240,000.

Construction costs were adjusted from 2002 dollars to the anticipated online date using the Reclamation construction cost index for powerplants up to 2010 (Reclamation 2010) and the U.S. Army Corps of Engineers civil works construction cost index system (USACE 2010) from 2010 to the assumed online date in 2015. Mitigation costs were escalated to 2015 using the general annual inflation rate of 1.8%. Operation and maintenance costs were escalated at 2.3% per year.

Figure 6-1 provides a graphical summary of the construction and mitigation costs for capacity additions up to 100 MW. Construction and mitigation costs were totaled to form an initial development cost, which was then divided by the installed capacity to form the commonly used index of initial capacity cost in dollars per kilowatt. As shown on Figure 6-1, 10 MW of capacity addition costs about $1,550/kW, while the cost of 100 MW of capacity addition would be reduced to about $1,040/kW.



Figure 6-1. Construction, Mitigation, and Capacity Costs as a Function of Added MW

Chapter 7
Environmental and Climate Change Benefits

This chapter provides quantitative and qualitative information related to the environmental and climate change benefits of hydroelectric capacity additions. Environmental and climate change benefits from hydroelectric plants primarily result from the replacement (offset) of fossil fuel generation and its associated GHG emissions, with emission-free hydroelectric generation. Additional environmental benefits can be associated with turbine and runner replacement, which can result in uprating or capacity addition at a hydroelectric plant. In addition to GHG offsets, potential environmental benefits from capacity addition or turbine replacement projects include:

- Offsets of criteria pollutant emissions and other air toxics emissions.
- Elimination of grease contamination to the river by installing greaseless wicket gate bushings when the turbine runners are replaced.
- Improve water quality by increasing dissolved oxygen (DO) levels with the installation of aerating-type turbine runners.

Though environmental benefits have intrinsic value, monetary valuation of these benefits is complicated and currently there is no established, stable, generally accepted market value. In contrast, the quantification of GHG reductions has well established procedures and is therefore used in this project to demonstrate and rank environmental benefits.

Hydropower and Greenhouse Gasses

In the United States (U.S.), carbon dioxide accounts for 85 percent (%) of GHG emissions, with about 34% of the carbon dioxide emissions originating from electricity generation, which is more than from any other single source. Energy-related GHG emissions, mainly from fossil fuel combustion are projected to rise by over 50% by 2030 (IPCC 2007b). This makes reductions of GHG from electricity generation an imperative.

In 2004, hydroelectric systems provided 16% of global electricity and 90% of global renewable energy (IPCC 2007b). In the United States, hydropower accounted for nearly 9% of the U.S. total electric generating capacity (EPRI 2007) and about 7% of the annual electric energy output (EIA 2008). Existing conventional hydropower generation represents 75% of the U.S. renewable energy generation, averaging about 270,000 GWh per year (EPRI 2007). In the United States in 2006, hydropower capacity was about 96,000 MW, split between about 75,000 MW of conventional capacity and 21,000 MW of

pumped storage capacity. The 75,000 MW of conventional hydropower capacity was split almost equally between federal projects (~37,500 MW) and non-federal projects that are subject to FERC jurisdiction over licensing and regulatory structure (Hall and Reeves 2006). This means that federal hydropower projects provide a significant opportunity for GHG reductions.

Between 1980 and 2006, average annual hydroelectric energy generation in the United States remained almost constant, while thermal electric energy generation increased by about 70% (EIA 2008). Therefore, with consideration given to GHG offsets available from green hydropower production, incremental hydropower generation increases should be implemented when justified, and existing hydropower capacity should be maintained and rehabilitated as needed.

Opportunities for Climate Change Benefits

GHG reductions that will result from hydroelectric capacity additions or investments are accounted for in three different ways in this study:

- Capacity additions result in increased hydroelectric energy output by increasing the hydraulic capacity of the turbines and generating with flow that would be otherwise spilled and not flow through a turbine.

- Turbine runner replacement will result in improvement of the runner condition (elimination of deterioration and surface irregularities) that improves efficiency and increases energy generation. Turbine runner replacement may also result in a modern runner shape that is inherently more efficient (1.5%) than the older runner was in new condition.

- Planned turbine replacements will reduce the risk of longer unplanned outage durations and therefore result in reduced generation losses. Depending on the system or type of equipment, outage durations can vary significantly. A one year incremental outage of one unit at each plant was used as an index value to account for the reduced generation losses and GHG offsets that could potentially result from planned turbine replacements.

GHG Reduction Quantification

Environmental benefits in the form of GHG emission reductions will be achieved though incremental energy increases due to improved efficiency, increased hydraulic capacity, and reduced outages. Hydropower generation increases resulting from these equipment improvements were determined for each plant on an annual average basis. The annual average incremental generation increase at the plant was used to calculate annual average GHG reductions.

GHG reductions are quantified in terms of metric tons of carbon dioxide (CO_2) or carbon dioxide equivalents (CO_2e). In this evaluation of hydropower capacity addition projects, CO_2e incorporates the global warming potential of methane (CH_4) and nitrous oxide (N_2O), the other two primary GHG emissions that result from burning fossil fuels. Table 7-1 shows the relative 100-year global warming potential values (per lb CO_2) for CO_2, CH_4 and N_2O that are based on the Intergovernmental Panel on Climate Change's Second Assessment Report (IPCC, 2007a).

Table 7-1. 100-Year Global Warming Potential Values

	Greenhouse Gas		
	Carbon Dioxide (CO_2)	Methane (CH_4)	Nitrous Oxide (N_2O)
IPCC Second Assesment Report Values	1	21	310

GHG reductions were estimated using GHG emission rates based on the regional electricity generation resource mix and the 100-year global warming potential values for CO_2, CH_4 and N_2O to determine the total CO_2e offsets. The values were taken from the U.S. Environmental Protection Agency's (USEPA) Office of Atmospheric Programs' eGRID2007 (Version 1.1) database (USEPA 2008). eGrid (Emissions & Generation Resource Integrated Database) is an inventory of environmental attributes of electric power systems in the U.S., and was compiled based on information from USEPA, the Energy Information Administration, FERC, and the North American Electric Reliability Corporation (NERC) (USEPA, 2008). The regional GHG emission rates for each plant were determined based on the eGrid subregion, shown in Figure 7-1.



Figure 7-1. eGrid Subregions

Annual GHG output emission rates, based on the existing generation mix in each geographic area, are shown on Table 7-2 in pounds per megawatt-hour (lb/MWh) for CO_2, CH_4 and N_2O, for the regions encompassing the locations of the 58 plants. The annual output emission rates are used to calculate GHG reductions from baseload, or off-peak, generation, and the non-baseload emission rates are used to calculate GHG reductions from non-baseload, or on-peak, generation.

Table 7-2. Year 2005 GHG Annual Output Emission Rates

eGRID subregion acronym	eGRID Subregion Name	Annual output emission rates			Annual non-baseload output emission rates		
		Carbon dioxide (lb/MWh)	Methane (lb/MWh)	Nitrous oxide (lb/MWh)	Carbon dioxide (lb/MWh)	Methane (lb/MWh)	Nitrous oxide (lb/MWh)
AZNM	WECC Southwest	1311.05	0.0175	0.0179	1201.44	0.0208	0.0085
CAMX	WECC California	724.12	0.0302	0.0081	1083.02	0.0392	0.0056
NWPP	WECC Northwest	902.24	0.0191	0.0149	1333.64	0.0493	0.0187
RMPA	WECC Rockies	1883.08	0.0229	0.0288	1617.71	0.0224	0.0201

GHG reductions are quantified in terms of metric tons of CO_2e offset. The GHG offsets are based on the megawatt-hours of incremental generation that result from hydroelectric capacity increases, efficiency increases, or reduced outages. Efficiency increases from turbine runner replacement were based on

the expected degradation of the turbine runners as a function of age plus increase due to modern design if the runners were older than 15 years. Because outage durations vary depending on the system or equipment affected, GHG offsets from outages are given as an index value based on an assumed one year incremental outage of one unit at each plant.

Greenhouse Gas Equivalents

The quantification of GHG offsets in metric tons of a gas and carbon dioxide equivalents are new terms for most people. Another way GHG reductions can be presented is in terms of CO_2e equivalents, which describe these abstract concepts in everyday terms. While it may be difficult to picture how much a metric ton of gas is, it is easier to understand that one metric ton of CO_2e is equivalent to the CO_2 emissions from consuming 114 gallons of gasoline (USEPA 2009). In comparison to generation from fossil fuel sources, 100,000 MWh of hydropower generation would offset:

- 71,816 metric tons of carbon dioxide equivalent (CO_2e)
- 13,732 passenger vehicles taken off the road/year
- 8,078,332 gallons of gasoline consumed
- 167,015 barrels of oil consumed
- 8,716 homes electricity use for 1 year
- 6,112 homes total energy use for 1 year
- 0.02 coal fired power plant for 1 year

This page left blank intentionally.

Chapter 8
Plant Data Ratings

As requested by Reclamation, a plant data rating was developed to provide a measure of the quality and completeness of the data input to the energy model. Data quality ratings were input and displayed in the energy model, but were not used to modify the results. Ratings are unrelated to plant condition or operation.

Input data was given a score on a four point scale based on the descriptions provided below:

Rating 1 – The data was essentially complete with no significant omissions. Daily total outflow and head data, in the form of daily headwater elevations and daily tailwater elevations or a tailwater rating curve, were provided for at least 10 years. Where some parameter data was missing, relatively reliable fallback data sources were provided by Reclamation. Actual generation, either daily or monthly, was provided for the same period as the flow data.

Rating 2 – The data was mostly complete with some significant omissions. Significant omissions include data sets for plants with less than 10 years of daily total outflow and head data; at a low head plants, data sets that included daily reservoir elevations without a tailwater rating curve, and either a constant tailwater or an estimated tailwater rating curve had to be used; data sets that did not include required releases that are unavailable for generation increases, etc. Some actual generation, either daily or monthly, was provided.

Rating 3 – The data had major shortcomings. Major shortcomings include data sets for plants that had only monthly total outflow and head data; plants that only provided generation outflow; plants with less than 5 years of daily total outflow and head data, etc. Several parameters may have been missing for which no reliable fallback data sources were available. No generation data were provided.

Rating 4 – The data was insufficient to perform the energy model analysis. An example would be a plant where no flow data or no head data of any type was provided by Reclamation.

Table 8-1 provides a summary of the plant data ratings.

Table 8-1. Plant Data Ratings Summary

Region	Number of Plants with each Rating			
	1	2	3	4
Great Plains	8	5	8	0
Lower Colorado	3	0	0	0
Mid-Pacific	9	1	1	0
Pacific Northwest	5	2	3	0
Upper Colorado	0	8	4	0
Total Plants	25	16	16	0

Table 8-2 provides the data ratings for the individual plants.

Table 8-2. Individual Plant Data Ratings

Plant	Region	Data Quality Rating
Alcova	Great Plains	1
Anderson Ranch	Pacific Northwest	1
Big Thompson	Great Plains	2
Black Canyon	Pacific Northwest	1
Blue Mesa	Upper Colorado	2
Boise Diversion	Pacific Northwest	3
Boysen	Great Plains	1
Buffalo Bill	Great Plains	3
Canyon Ferry	Great Plains	1
Chandler	Pacific Northwest	3
Crystal	Upper Colorado	2
Davis	Lower Colorado	1
Deer Creek	Upper Colorado	2
Elephant Butte	Upper Colorado	3
Estes	Great Plains	3
Flaming Gorge	Upper Colorado	2
Flatiron	Great Plains	3
Folsom	Mid-Pacific	1
Fontenelle	Upper Colorado	2
Fremont Canyon	Great Plains	3
Glen Canyon	Upper Colorado	2
Glendo	Great Plains	1
Grand Coulee	Pacific Northwest	1
Green Mountain	Great Plains	2
Green Springs	Pacific Northwest	2
Guernsey	Great Plains	1
Heart Mountain	Great Plains	3
Hoover	Lower Colorado	1
Hungry Horse	Pacific Northwest	2
Judge Francis Carr	Mid-Pacific	3
Keswick	Mid-Pacific	1
Kortes	Great Plains	1
Lower Molina	Upper Colorado	3
Marys Lake	Great Plains	2
McPhee	Upper Colorado	2
Minidoka	Pacific Northwest	1
Morrow Point	Upper Colorado	2
Mount Elbert	Great Plains	3
New Melones	Mid-Pacific	1
Nimbus	Mid-Pacific	1
O'Neill	Mid-Pacific	1
Palisades	Pacific Northwest	1
Parker	Lower Colorado	1
Pilot Butte	Great Plains	2
Pole Hill	Great Plains	2
Roza	Pacific Northwest	3
San Luis	Mid-Pacific	1
Seminoe	Great Plains	1
Shasta	Mid-Pacific	1
Shoshone	Great Plains	3
Spirit Mountain	Great Plains	3
Spring Creek	Mid-Pacific	1
Stampede	Mid-Pacific	2
Towaoc	Upper Colorado	3
Trinity	Mid-Pacific	1
Upper Molina	Upper Colorado	3
Yellowtail	Great Plains	1

This page left blank intentionally.

Chapter 9
Summary of Results

The results from the energy model include the economic calculations, the incremental generation from the existing units due to capacity increases or efficiency gains, and the avoided generation loss from outages. These results are used to determine the GHG offsets. The results for the capacity addition opportunities, additional generation and GHG offsets are shown by region for each of the plants and the top potential capacity increase opportunities are discussed in this chapter.

Capacity Additions

A brief review of the steps in the determination of capacity addition results is summarized as follows:

- Based on the plant nameplate capacity, determine the 10%, 20%, 30%, 40%, and 50% capacity additions in MW
- From the capacity additions in MW, determine the corresponding hydraulic capacity increases in cubic feet per second (cfs)
- For each of the hydraulic capacity increases, determine the incremental energy with PLEESM (Chapter 3 of this report)
- Determine the energy benefits from the energy values ($/MWh) as presented in Chapter 5 and the average monthly incremental energy (MWh)
- From the incremental energy increases, determine the capacity factor
- Determine the incremental capacity value ($/kW-yr) from the capacity factor and Figure 5-5
- Determine the capacity benefits from the incremental capacity value ($/kW-yr)and the capacity additions (kW)
- Develop the total costs as presented in Chapter 6 of this report
- Using the economic parameters and methodology presented in Chapter 4, determine the present values of the total costs and the total benefits (energy plus capacity)
- Determine the NPV, which is the present value of benefits minus present value of costs; and the BCR, which is the present value of benefits minus the present value of costs.

- From the five capacity addition increments, select the capacity addition with the maximum BCR and the one with the maximum NPV, which can result in the selection of two different capacity increments.

It must be emphasized that selecting a capacity addition with the maximum NPV or BCR is not necessarily an indication of economic viability. Only capacity additions with benefit to cost ratios greater than 1.00 and positive net present values provide indications of economic feasibility.

For plants that have zero or negligible incremental energy associated with the capacity additions, the BCR values will maximize at the largest (50%) capacity addition because the cost per installed kilowatt decreases with size (Fig. 6-1) and the capacity benefit per installed kilowatt is constant when the capacity factor is zero (Fig. 5-5). For example, Grand Coulee has its maximum BCR of 0.27 at the 50% capacity increase of 3,247.5 MW, which should not be interpreted to mean that the recommended capacity addition is over 3,000 MW. The bottom line message for Grand Coulee (and other plants with similar results) would be that no capacity addition shows economic feasibility based on the methodologies employed in this report.

The capacity addition results are shown by region in Tables 9-1 through 9-5 for each of the five Reclamation regions and are summarized below. The plants are ranked in each region based on the maximum BCR from the five capacity addition increments included in the analysis. For each plant, the existing installed capacity, maximum BCR and NPV, the capacity increase increment associated with the maximum BCR and NPV are shown in the table. The capacity increase and the incremental capacity factor associated with the maximum BCR are also shown.

Mid-Pacific Region

Of the 11 plants in the Mid-Pacific region, the only plant with have both BCRs equal to or greater than one and positive NPVs is Nimbus (Table 9-1). The maximum BCR for Nimbus of 1.39 occurs at a capacity increase of 20% over the existing installed capacity, which corresponds to a 2.7 MW capacity increase. The incremental capacity factor for a 2.7 MW capacity increase at Nimbus is 26% indicating that the potential incremental generation is about a quarter of the generation that could be obtained if the additional capacity was run continuously at full output. Since the remaining plants in the Mid-Pacific region have BCRs less than 1.0 and negative NPVs, capacity additions at these plants would not be economically beneficial.

A Lease of Power Privilege Agreement for the Lewiston Hydroelectric Project (Agreement) was signed in June 2009 between Reclamation and the Trinity Public Utilities District (TPUD). The Agreement calls for complete replacement of the existing 350 kW hydroelectric unit with a new unit capable of generating up to 2,000 kW. The TPUD generation share from the new unit would be all generation in excess of that for the 350 kW unit if it operated at a

90.1% capacity factor. Because the Lewiston capacity addition will be (or has been) determined by TPUD within the limits of the Agreement, it would not be productive to include Lewiston in the current studies. Therefore, no results are presented for Lewiston.

Table 9-1. Capacity Addition Results - Mid-Pacific Region

Rank [1]	Plant	Existing Installed Capacity (MW)	Maximum BCR Percent Increase	Maximum NPV Percent Increase	Capacity Increase (MW)	Incremental Generation from Capacity Addition [2] (MWh/yr)	Incremental Capacity Factor	Maximum BCR	Maximum NPV ($M)
1	Nimbus	13.5	20%	50%	2.7	6,104	26%	1.39	$5.8
2	Folsom	207	30%	20%	62	32,607	6.0%	0.97	-$2.3
3	Shasta	714	30%	10%	214	73,426	3.9%	0.86	-$23.8
4	Stampede	3.65	30%	10%	1.1	1,669	17%	0.85	-$0.3
5	Keswick	117	40%	10%	47	26,278	6.4%	0.66	-$10.1
6	Trinity	140	20%	10%	28	17,625	7.2%	0.57	-$13.7
7	Judge Francis Carr	154	10%	10%	15	4,476	3.3%	0.45	-$17.0
8	Spring Creek	180	20%	10%	36	12,180	3.9%	0.21	-$28.0
9	San Luis [3]	424	50%	10%	212	5,289	0.3%	0.16	-$61.7
10	New Melones	382	50%	10%	191	7,830	0.5%	0.16	-$56.9
11	O'Neill	25	10%	10%	2.5	251	1.1%	0.12	-$6.5

Notes

[1] Plants are ranked based on the capacity addition increment with the highest BCR for each plant .

[2] Incremental generation shown is for the capacity addition with the highest BCR.

[3] Installed capacity of 424 MW for San Luis includes the Federal and CA shares. The Federal share is 202 MW.

BCR - Benefit to Cost Ratio

NPV - Net Present Value

Upper Colorado Region

Of the 12 plants in the Upper Colorado region, two plants, Deer Creek and Crystal, both have BCRs equal to or greater than one and positive NPVs (Table 9-2). The maximum BCR for Deer Creek of 1.04 occurs at a capacity increase of 10% over the existing installed capacity, which corresponds to a 495 kW capacity increase. The incremental capacity factor for the 495 kW capacity increase at Deer Creek is 24%. The maximum BCR for Crystal of 1.00 occurs at a capacity increase of 30% over the existing installed capacity which corresponds to a 9.5 MW capacity increase. The incremental capacity factor for the 9.5 MW capacity increase at Crystal is 13%. The remaining plants in the Upper Colorado region have BCRs less than or equal to one and negative NPVs, or no NPV in the case of McPhee; thus, capacity additions at these plants would not be economically beneficial.

Table 9-2. Capacity Addition Results - Upper Colorado Region

Rank [1]	Plant	Existing Installed Capacity (MW)	Maximum BCR Percent Increase	Maximum NPV Percent Increase	Capacity Increase (MW)	Incremental Generation from Capacity Addition [2] (MWh/yr)	Incremental Capacity Factor	Maximum BCR	Maximum NPV ($M)
1	Deer Creek	5.0	10%	20%	0.5	1,023	24%	1.04	$0.1
2	Crystal	32	30%	30%	9.5	10,950	13%	1.00	$0.1
3	McPhee	1.3	10%	10%	0.1	413	37%	1.00	$0.0
4	Fontenelle	10	50%	10%	5.0	4,774	11%	0.57	-$1.9
5	Glen Canyon	1,320	30%	10%	396	71,082	2.0%	0.51	-$103
6	Towaoc	11	10%	10%	1.1	1,120	11%	0.41	-$2.3
7	Flaming Gorge	152	50%	10%	76	13,495	2.0%	0.35	-$20.2
8	Blue Mesa	86	40%	10%	35	3,219	1.1%	0.23	-$15.4
9	Morrow Point	173	50%	10%	87	10,279	1.4%	0.20	-$28.4
10	Elephant Butte	28	10%	10%	2.8	357	1.5%	0.15	-$6.8
11	Lower Molina	4.9	50%	10%	2.4	133	0.6%	0.10	-$1.8
12	Upper Molina	8.6	50%	10%	4.3	8	0%	0.08	-$3.0

Notes
[1] Plants are ranked based on the capacity addition increment with the highest BCR for each plant .
[2] Incremental generation shown is for the capacity addition with the highest BCR.
BCR - Benefit to Cost Ratio
NPV - Net Present Value

Great Plains Region

Of the 21 plants in the Great Plains region, three plants, Shoshone, Canyon Ferry, and Guernsey, have both BCRs equal to or greater than one and positive NPVs (Table 9-3). The maximum BCR for Shoshone of 3.50 occurs at a capacity increase of 50% over the existing installed capacity, which corresponds to a 1.5 MW capacity increase. The incremental capacity factor for the 1.5 MW capacity increase at Shoshone is 94%. However, the simulated generation for Shoshone was in the range of 20 - 25% higher than the actual recorded generation, which indicates a moderate degree of uncertainty in the results for this plant.

The maximum BCR for Canyon Ferry of 1.53 occurs at a capacity increase of 10% over the existing installed capacity which corresponds to a 5.0 MW capacity increase and an incremental capacity factor of 40%. The maximum BCR for Guernsey of 1.52 occurs at a capacity increase of 50% over the existing installed capacity which corresponds to a 3.2 MW capacity increase and an incremental capacity factor at Guernsey of 32%. The remaining plants in the Great Plains region have BCRs less than one and negative NPVs; thus, capacity additions at these plants would not be economically beneficial.

Table 9-3. Capacity Addition Results - Great Plains Region

Rank [1]	Plant	Existing Installed Capacity (MW)	Maximum BCR Percent Increase	Maximum NPV Percent Increase	Capacity Increase (MW)	Incremental Generation from Capacity Addition [2] (MWh/yr)	Incremental Capacity Factor	Maximum BCR	Maximum NPV ($M)
1	Shoshone	3.0	50%	50%	1.5	12,347	94%	3.50	$12.2
2	Canyon Ferry	50	10%	40%	5.0	17,576	40%	1.53	$13.4
3	Guernsey	6.4	50%	50%	3.2	8,887	32%	1.52	$4.6
4	Pilot Butte	1.6	50%	50%	0.8	1,800	26%	0.96	-$0.1
5	Buffalo Bill	18	10%	10%	1.8	3,985	25%	0.81	-$1.1
6	Glendo	38	20%	10%	7.6	8,726	13%	0.73	-$2.8
7	Fremont Canyon	67	10%	10%	6.7	9,238	16%	0.62	-$6.0
8	Boysen	15	40%	10%	6.0	5,322	10%	0.56	-$2.2
9	Kortes	36	50%	10%	18	4,594	2.9%	0.33	-$6.9
10	Big Thompson	4.5	10%	10%	0.5	494	13%	0.30	-$1.3
11	Alcova	41	20%	10%	8.3	2,003	2.8%	0.27	-$8.0
12	Seminoe	52	30%	10%	16	5,592	4.1%	0.27	-$9.9
13	Yellowtail	250	30%	10%	75	8,526	1.3%	0.27	-$34.8
14	Green Mountain	26	50%	10%	13	2,065	1.8%	0.23	-$6.0
15	Mount Elbert	200	50%	10%	100	3,965	0.5%	0.14	-$34.4
16	Flatiron [3]	94.5	50%	10%	41	4,153	1.2%	0.12	-$17.0
17	Estes	45	50%	10%	23	1,854	0.9%	0.11	-$10.7
18	Pole Hill	38	50%	10%	19	3,173	1.9%	0.10	-$9.5
19	Heart Mountain	5.0	50%	10%	2.5	481	2.2%	0.09	-$1.9
20	Marys Lake	8.1	50%	10%	4.1	687	1.9%	0.08	-$2.8
21	Spirit Mountain	4.5	50%	10%	2.3	220	1.1%	0.07	-$1.8

Notes

[1] Plants are ranked based on the capacity addition increment with the highest BCR for each plant .

[2] Incremental generation shown is for the capacity addition with the highest BCR.

[3] Installed capacity at Flatiron is 94.5 MW. Only Units 1 and 2 (81.3 MW) were included in the modeling.

BCR - Benefit to Cost Ratio

NPV - Net Present Value

Pacific Northwest Region

Of the ten plants in the Pacific Northwest region, four plants, Black Canyon, Boise Diversion, Palisades, and Minidoka, have both BCRs equal to or greater than one and positive NPVs (Table 9-4). The maximum BCR for Black Canyon of 2.52 occurs at a capacity increase of 50% over the existing installed capacity, which corresponds to a 5.1 MW capacity increase and an incremental capacity factor of 43%. The maximum BCR for Boise Diversion of 2.48 occurs at a capacity increase of 40% over the existing installed capacity, which corresponds to a 1.4 MW capacity increase and an incremental capacity factor at Boise Diversion of 52%. The simulated generation for Boise Diversion was in the range of 20 - 25% higher than the actual recorded generation, which indicates a moderate degree of uncertainty in the results for this plant.

The maximum BCR for Palisades of 2.28 occurs at a capacity increase of 20% over the existing installed capacity which corresponds to a 35 MW capacity increase. The incremental capacity factor for the 35 MW capacity increase at Palisades is 24%. The maximum BCR for Minidoka of 1.21 occurs at a capacity increase of 10% over the existing installed capacity which corresponds to a 2.8 MW capacity increase. The incremental capacity factor for the 2.8 MW capacity increase at Minidoka is 13%. The remaining plants in the Pacific Northwest region have BCRs less than one and negative NPVs; thus, capacity additions at these plants would not be economically beneficial.

Table 9-4. Capacity Addition Results - Pacific Northwest Region

Rank [1]	Plant	Existing Installed Capacity (MW)	Maximum BCR Percent Increase	Maximum NPV Percent Increase	Capacity Increase (MW)	Incremental Generation from Capacity Addition [2] (MWh/yr)	Incremental Capacity Factor	Maximum BCR	Maximum NPV ($M)
1	Black Canyon	10	50%	50%	5.1	19,026	43%	2.52	$19.6
2	Boise Diversion	3.5	40%	50%	1.4	6,231	52%	2.48	$7.8
3	Palisades	177	20%	50%	35	72,778	24%	2.28	$123
4	Minidoka	28	10%	20%	2.8	3,098	13%	1.21	$2.6
5	Anderson Ranch	40	50%	10%	20	19,805	11%	0.91	-$3.2
6	Chandler	12	10%	10%	1.2	594	5.6%	0.32	-$2.8
7	Grand Coulee	6,495	50%	10%	3,248	141	0.0%	0.27	-$510
8	Hungry Horse	428	50%	10%	214	19,275	1.0%	0.19	-$59.9
9	Green Springs	17	50%	10%	8.6	0.0	0.0%	0.09	-$5.1
10	Roza	13	50%	10%	6.5	1,062	1.9%	0.08	-$4.1

Notes
[1] Plants are ranked based on the capacity addition increment with the highest BCR for each plant .
[2] Incremental generation shown is for the capacity addition with the highest BCR.
BCR - Benefit to Cost Ratio
NPV - Net Present Value

Lower Colorado Region

None of the plants in the Lower Colorado regionhave both BCRs equal to or greater than one and positive NPVs (Table 9-5). Therefore, capacity additions at the plants in the Lower Colorado region would not be economically beneficial.

Table 9-5. Capacity Addition Results - Lower Colorado Region

Rank [1]	Plant	Existing Installed Capacity (MW)	Maximum BCR Percent Increase	Maximum NPV Percent Increase	Capacity Increase (MW)	Incremental Generation from Capacity Addition [2] (MWh/yr)	Incremental Capacity Factor	Maximum BCR	Maximum NPV ($M)
1	Davis	255	10%	10%	26	15,784	7.1%	0.76	-$11.1
3	Parker	120	20%	10%	24	15,049	7.2%	0.76	-$7.1
2	Hoover	2,079	50%	10%	1,039	0	0%	0.22	-$212

Notes
[1] Plants are ranked based on the capacity addition increment with the highest BCR for each plant .
[2] Incremental generation shown is for the capacity addition with the highest BCR.
BCR - Benefit to Cost Ratio
NPV - Net Present Value

Summary of Capacity Addition Results

Of the 58 plants included in the assessment, ten plants have both BCRs equal to or greater than one and positive NPVs. These ten opportunities for capacity additions based on BCRs are summarized in Table 9-6. Three of these plants are located in the Great Plains region, four plants are located in the Pacific Northwest region, two plants are located in the Upper Colorado region, and one plant is located in the Mid-Pacific region. The plant with the highest BCR of 3.50 is Shoshone in the Great Plains region. Shoshone also has the highest incremental capacity factor of 94%. The plant with the largest potential

capacity increase of 35 MW is Palisades in the Pacific Northwest region which ranked fourth overall based on BCR.

Table 9-6. Summary - Capacity Addition Opportunities Ranked by BCR

Rank [1]	Plant	Region	Existing Installed Capacity (MW)	Maximum BCR Percent Increase	Maximum NPV Percent Increase	Maximum BCR Capacity Increase (MW)	Incremental Generation from Capacity Addition [2] (MWh/yr)	Incremental Capacity Factor	Maximum BCR	Maximum NPV ($M)
1	Shoshone	Great Plains	3.0	50%	50%	1.5	12,347	94%	3.50	$12.2
2	Black Canyon	Pacific Northwest	10	50%	50%	5.1	19,026	43%	2.52	$19.6
3	Boise Diversion	Pacific Northwest	3.5	40%	50%	1.4	6,231	52%	2.48	$7.8
4	Palisades	Pacific Northwest	177	20%	50%	35	72,778	24%	2.28	$123
5	Canyon Ferry	Great Plains	50	10%	40%	5.0	17,576	40%	1.53	$13.4
6	Guernsey	Great Plains	6.4	50%	50%	3.2	8,887	32%	1.52	$4.6
7	Nimbus	Mid-Pacific	13.5	20%	50%	2.7	6,104	26%	1.39	$5.8
8	Minidoka	Pacific Northwest	28	10%	20%	2.8	3,098	13%	1.21	$2.6
9	Deer Creek	Upper Colorado	5.0	10%	20%	0.5	1,023	24%	1.04	$0.1
10	Crystal	Upper Colorado	31.5	30%	30%	9.5	10,950	13%	1.00	$0.1

Notes
[1] Plants are ranked based on the capacity addition increment with the highest BCR for each plant .
[2] Incremental generation shown is for the capacity addition with the highest BCR.
BCR - Benefit to Cost Ratio
NPV - Net Present Value

The opportunities for capacity additions based on NPV are shown in Table 9-7. The same ten plants that represented the top opportunities for capacity additions based on BCR are the plants with the top opportunities for capacity additions based on NPV, but with a shift in the ranking order. Palisades has the highest NPV for a capacity addition of $123 million which corresponds to a 50% increase over the existing installed capacity and an actual increase of 88 MW. However, the incremental capacity factor for the 88 MW capacity increase at Palisades is only 17%. At an 88 MW capacity increase, Palisades has the largest capacity increase potential of all the plants with a positive NPV. The plant with the highest incremental capacity factor based on NPV of 94% is Shoshone with a capacity increase 50% greater than its existing capacity, or 1.5 MW, which is unchanged from the BCR rankings.

Table 9-7. Summary - Capacity Addition Opportunities Ranked by NPV

Rank [1]	Plant	Region	Existing Installed Capacity (MW)	Maximum BCR Percent Increase	Maximum NPV Percent Increase	Maximum NPV Capacity Increase (MW)	Incremental Generation from Capacity Addition [2] (MWh/yr)	Incremental Capacity Factor	Maximum BCR	Maximum NPV ($M)
1	Palisades	Pacific Northwest	177	20%	50%	88	129,245	17%	2.28	$123
2	Black Canyon	Pacific Northwest	10	50%	50%	5.1	19,026	43%	2.52	$19.6
3	Canyon Ferry	Great Plains	50	10%	40%	20	35,538	20%	1.53	$13.4
4	Shoshone	Great Plains	3.0	50%	50%	1.5	12,347	94%	3.50	$12.2
5	Boise Diversion	Pacific Northwest	3.5	40%	50%	1.7	7,234	48%	2.48	$7.8
6	Nimbus	Mid-Pacific	14	20%	50%	6.8	11,041	19%	1.39	$5.8
7	Guernsey	Great Plains	6.4	50%	50%	3.2	8,887	32%	1.52	$4.6
8	Minidoka	Pacific Northwest	27.7	10%	20%	5.5	6,595	14%	1.21	$2.6
9	Deer Creek	Upper Colorado	5.0	10%	20%	1.0	1,816	21%	1.04	$0.1
10	Crystal	Upper Colorado	32	30%	30%	9.5	10,950	13%	1.00	$0.1

Notes
[1] Plants are ranked based on the capacity addition increment with the highest NPV for each plant .
[2] Incremental generation shown is for the capacity addition with the highest BCR.
BCR - Benefit to Cost Ratio
NPV - Net Present Value

Efficiency Gains

Additional generation from efficiency improvements can be gained in two ways. These are by rehabilitating the turbine to improve its condition such that it operates similar to a new turbine of the original vintage in its original condition, or by replacing an older turbine runner and appurtenant parts with new components of modern design. The incremental generation from efficiency improvements shown in the results tables is the potential additional generation based on both the generation gain from the efficiency deterioration of the existing turbine due to its age and the generation gain from replacing the existing turbine with a new, modern turbine design. Turbines that have been replaced within the past 15 years were assumed to have been replaced with a modern design at that time and thus would not achieve the 1.5% efficiency increase. The age of the turbine was used to determine the efficiency deterioration up to a maximum of 5%, but this particular study did not consider the actual condition of the turbine in estimating performance degradation. The condition will be incorporated in the upcoming Asset Investment Planning (AIP) program and the potential additional generation from turbine upgrades will be refined in the AIP tool.

Where results in the tables show incremental generation increases from efficiency improvements of less than about 2%, it is an indication that improvements have been made in recent years. Where efficiency gains of at least 3% can be made, this represents a potential opportunity.

Costs and economic benefits were not assigned to the efficiency gains in this study. A cost/benefit analysis was not performed for potential efficiency gains because this more detailed level of analysis is performed in the AIP program. .

The efficiency gain results are shown by region in Tables 9-8 through 9-12 for each of the five Reclamation regions and summarized below. The plants are ranked in each region based on the maximum BCR from the five capacity addition increments included in the analysis. For each plant, the existing installed capacity, the average annual existing generation from the energy model simulation and the potential incremental are shown in the table. The generation percent increase over the simulated average annual existing generation is also shown. The energy model simulated existing generation was used because it provides a more uniform long-term average for generation from the current existing installed capacity among the 58 plants than recorded generation, which has been subject shifts from upgrades at various points in time for the 58 plants.

Mid-Pacific Region

The plant with the highest potential incremental generation increase from efficiency improvements in the Mid-Pacific region is Spring Creek with a gain of 36,681 MWh/yr (Table 9-8). The additional generation at Spring Creek corresponds to a 6.2% increase over its existing annual generation. The plants

with the highest percent increases in generation over their existing annual generation are Nimbus, San Luis, and O'Neill with potential increases of 4,671 MWh/yr, 20,490 MWh/yr, and 371 MWh/yr, respectively. The generation increases for each of these plants corresponds to a 6.7% increase over their existing annual generation. The Judge Francis Carr plant shows a zero efficiency improvement because the turbine replacement in-service date was within the past two years.

Table 9-8. Efficiency Gain Results - Mid-Pacific Region

Plant	Installed Capacity	Annual Average Existing Generation	Incremental Generation from Efficiency Improvements	
	(MW)	(MWh/yr)	(MWh/yr)	(%)
Nimbus	13.5	69,746	4,671	6.7
Folsom	207	627,943	14,127	2.2
Shasta	714	2,181,077	22,831	1.0
Stampede	3.65	12,915	761	5.9
Keswick	117	461,014	25,762	5.6
Trinity	140	517,251	31,209	6.0
Judge Francis Carr	154	486,896	0	0.0
Spring Creek	180	590,037	36,681	6.2
San Luis [1]	424	304,679	20,490	6.7
New Melones	382	470,677	29,916	6.4
O'Neill	25	5,503	371	6.7

Notes

[1] Installed capacity of 424 MW for San Luis includes the Federal and CA shares. The Federal share is 202 MW.

Upper Colorado Region

The plant with the highest potential incremental generation increase from efficiency improvements in the Upper Colorado region is Glen Canyon with a gain of 38,055 MWh/yr (Table 9-9). The additional generation at Glen Canyon corresponds to a 0.8% increase over its existing annual generation. The plant with the highest percent increase in generation over its existing annual generation is Fontenelle with a potential increase of 6.7% which corresponds to an additional 3,722 MWh/yr. Deer Creek and Crystal, the two plants with BCRs greater than one in the Upper Colorado region, have potential generation increases from efficiency improvements of 391 MWh/yr and 3,386 MWh/yr, respectively,

Table 9-9. Efficiency Gain Results - Upper Colorado Region

Plant	Installed Capacity	Annual Average Existing Generation	Incremental Generation from Efficiency Improvements	
	(MW)	(MWh/yr)	(MWh/yr)	(%)
Deer Creek	5.0	26,968	391	1.4
Crystal	32	187,173	3,386	1.8
McPhee	1.3	5,679	301	5.3
Fontenelle	10	55,444	3,722	6.7
Glen Canyon	1,320	4,982,479	38,055	0.8
Towaoc	11	19,381	1,014	5.2
Flaming Gorge	152	509,422	3,891	0.8
Blue Mesa	86	265,164	8,673	3.3
Morrow Point	173	363,625	19,421	5.3
Elephant Butte	28	116,635	2,374	2.0
Lower Molina	4.9	19,003	250	1.3
Upper Molina	8.6	32,284	150	0.5

Great Plains Region

The plant with the highest potential incremental generation increase from efficiency improvements in the Great Plains region is Canyon Ferry with a gain of 25,391 MWh/yr (Table 9-10). The additional generation at Canyon Ferry corresponds to a 6.7% increase over its existing annual generation. The other plants with generation increases corresponding to 6.7% over their existing annual generation, the highest potential percent increase in generation from efficiency improvements, are Big Thompson, Boysen, Estes, Heart Mountain, Marys Lake, and Pilot Butte, which have potential generation increases ranging from 269 MWh/yr at Pilot Butte to 7,232 MWh/yr at Estes. In addition to Canyon Ferry, the other plants with BCRs greater than one in the Great Plains region were Shoshone and Guernsey which have potential increases in generation from efficiency improvements of 1,374 MWh/yr and 934 MWh/yr, respectively, that correspond to 5.4% and 4.6% increases over their existing annual generation, respectively.

Table 9-10. Efficiency Gain Results - Great Plains Region

Plant	Installed Capacity (MW)	Annual Average Existing Generation (MWh/yr)	Incremental Generation from Efficiency Improvements (MWh/yr)	(%)
Shoshone	3.0	25,487	1,374	5.4
Canyon Ferry	50	380,509	25,391	6.7
Guernsey	6.4	20,194	934	4.6
Pilot Butte	1.6	4,013	269	6.7
Buffalo Bill	18	74,174	4,268	5.8
Glendo	38	65,902	4,130	6.3
Fremont Canyon	67	247,405	14,075	5.7
Boysen	15	71,996	4,825	6.7
Kortes	36	147,781	1,943	1.3
Big Thompson	4.5	12,248	824	6.7
Alcova	41	118,203	2,406	2.0
Seminoe	52	141,940	8,288	5.8
Yellowtail	250	818,027	21,612	2.6
Green Mountain	26	64,728	2,037	3.1
Mount Elbert	200	226,803	14,379	6.3
Flatiron [1]	94.5	241,042	14,436	6.0
Estes	45	107,555	7,232	6.7
Pole Hill	38	184,741	10,906	5.9
Heart Mountain	5.0	21,782	1,465	6.7
Marys Lake	8.1	40,514	2,713	6.7
Spirit Mountain	4.5	12,570	652	5.2

Notes

[1] Installed capacity at Flatiron is 94.5 MW. Only Units 1 and 2 (81.3 MW) were included in the modeling.

Pacific Northwest Region

The plant with the highest potential incremental generation increase from efficiency improvements in the Pacific Northwest region is Grand Coulee with a gain of 101,669 MWh/yr (Table 9-11). The additional generation at Grand Coulee is only a 0.5% increase over its existing annual generation. The magnitude of the incremental generation is likely due to the fact that there are 33 units at the plant and not that the units have undergone significant efficiency deterioration due to age. The plant with the highest percent increase in generation over its existing annual generation is Anderson Ranch with a potential increase of 6.2% which corresponds to an additional 9,215 MWh/yr. The plants with BCRs greater than one in the Pacific Northwest region, Black Canyon, Boise Diversion, Palisades, and Minidoka, have potential increases in generation from efficiency improvements of 2,211 MWh/yr, 104 MWh/yr, 22,716 MWh/yr, and 2,403 MWh/yr, respectively. These increases in generation represent 3.3%, 0.7%, 3.2%, and 1.7% increases over their existing annual generation, respectively.

Table 9-11. Efficiency Gain Results - Pacific Northwest Region

Plant	Installed Capacity	Annual Average Existing Generation	Incremental Generation from Efficiency Improvements	
	(MW)	(MWh/yr)	(MWh/yr)	(%)
Black Canyon	10	67,078	2,211	3.3
Boise Diversion	3.5	15,247	104	0.7
Palisades	177	706,936	22,716	3.2
Minidoka	28	137,585	2,403	1.7
Anderson Ranch	40	148,136	9,215	6.2
Chandler	12	60,349	461	0.8
Grand Coulee	6,495	21,850,471	101,669	0.5
Hungry Horse	428	930,345	49,272	5.3
Green Springs	17	63,822	1,686	2.6
Roza	13	61,990	3,753	6.1

Lower Colorado Region

The plant with the highest potential incremental generation increase from efficiency improvements in the Lower Colorado region is Hoover with a gain or 107,275 MWh/yr (Table 9-12). The additional generation at Hoover corresponds to a 2.0% increase over its existing annual generation. Like Grand Coulee, the magnitude of the incremental generation is likely due to the fact that there are 19 units at the plant and not that the units have undergone significant efficiency deterioration due to age. The other two plants in the Lower Colorado region, Davis and Parker, have potential incremental generation increases of 26,471 MWh/yr and 7,445 MWh/yr, respectively, which correspond to relatively small increases over their existing annual generation of 2.0% and 1.3%, respectively.

Table 9-12. Efficiency Gain Results - Lower Colorado Region

Plant	Installed Capacity	Annual Average Existing Generation	Incremental Generation from Efficiency Improvements	
	(MW)	(MWh/yr)	(MWh/yr)	(%)
Davis	255	1,300,376	26,471	2.0
Parker	120	566,182	7,445	1.3
Hoover	2,079	5,269,763	107,275	2.0

Summary of Efficiency Gains Results

Significant potential for annual generation increases from efficiency improves exist at the Reclamation plants based on this screening level assessment. As was previously described, the efficiency improvements are based on a

standardized efficiency degradation curve that considers the age of the units and assumes replacement with a modern turbine design. A total of 36 plants could potentially increase their annual generation by greater than 3%. The plants are ranked based on the percent increase in generation over the simulated annual generation (Table 9-13). The plant with largest potential generation increase from efficiency gains is Hungry Horse in the Pacific Northwest. Several of the plants in the Mid-Pacific Region also have potential gains from efficiency related opportunities. The plant with the largest potential percent increase over its existing annual generation is O'Neill in the Mid-Pacific region.

Table 9-13. Summary - Efficiency Gain Opportunities >3%

Rank [1]	Plant	Region	Installed Capacity	Annual Average Existing Generation	Incremental Generation from Efficiency Improvements	
			(MW)	(MWh/yr)	(MWh/yr)	(%)
1	O'Neill	Mid-Pacific	25	5,503	371	6.7
2	Big Thompson	Great Plains	4.5	12,248	824	6.7
3	Heart Mountain	Great Plains	5.0	21,782	1,465	6.7
4	San Luis [2]	Mid-Pacific	424	304,679	20,490	6.7
5	Estes	Great Plains	45	107,555	7,232	6.7
6	Fontenelle	Upper Colorado	10	55,444	3,722	6.7
7	Boysen	Great Plains	15	71,996	4,825	6.7
8	Pilot Butte	Great Plains	1.6	4,013	269	6.7
9	Nimbus	Mid-Pacific	13.5	69,746	4,671	6.7
10	Marys Lake	Great Plains	8.1	40,514	2,713	6.7
11	Canyon Ferry	Great Plains	50	380,509	25,391	6.7
12	New Melones	Mid-Pacific	382	470,677	29,916	6.4
13	Mount Elbert	Great Plains	200	226,803	14,379	6.3
14	Glendo	Great Plains	38	65,902	4,130	6.3
15	Anderson Ranch	Pacific Northwest	40	148,136	9,215	6.2
16	Spring Creek	Mid-Pacific	180	590,037	36,681	6.2
17	Roza	Pacific Northwest	13	61,990	3,753	6.1
18	Trinity	Mid-Pacific	140	517,251	31,209	6.0
19	Flatiron [3]	Great Plains	94.5	241,042	14,436	6.0
20	Pole Hill	Great Plains	38	184,741	10,906	5.9
21	Stampede	Mid-Pacific	3.65	12,915	761	5.9
22	Seminoe	Great Plains	52	141,940	8,288	5.8
23	Buffalo Bill	Great Plains	18	74,174	4,268	5.8
24	Fremont Canyon	Great Plains	67	247,405	14,075	5.7
25	Keswick	Mid-Pacific	117	461,014	25,762	5.6
26	Shoshone	Great Plains	3.0	25,487	1,374	5.4
27	Morrow Point	Upper Colorado	173	363,625	19,421	5.3
28	Hungry Horse	Pacific Northwest	428	930,345	49,272	5.3
29	McPhee	Upper Colorado	1.3	5,679	301	5.3
30	Towaoc	Upper Colorado	11	19,381	1,014	5.2
31	Spirit Mountain	Great Plains	4.5	12,570	652	5.2
32	Guernsey	Great Plains	6.4	20,194	934	4.6
33	Black Canyon	Pacific Northwest	10.2	67,078	2,211	3.3
34	Blue Mesa	Upper Colorado	86.4	265,164	8,673	3.3
35	Palisades	Pacific Northwest	176.6	706,936	22,716	3.2
36	Green Mountain	Great Plains	26.0	64,728	2,037	3.1

Notes

[1] Plants are ranked based on the percent of additional generation from efficiency improvements over their existing annual (simulated) generation.

[2] Installed capacity of 424 MW for San Luis includes the Federal and CA shares. The Federal share is 202 MW.

[3] Installed capacity at Flatiron is 94.5 MW. Only Units 1 and 2 (81.3 MW) were included in the modeling.

Greenhouse Gas Reduction Opportunities

Three potential opportunities for GHG reduction have been determined in this assessment. These reduction opportunities, or offsets, are from efficiency improvements, capacity additions, and avoided outage losses, Since GHG offsets are directly related to generation, the incremental generation, or avoided lost generation for outages, and the GHG offsets are shown in the results tables. The GHG offsets are summarized by region in Tables 9-14 through 9-18 for each of the five Reclamation regions and the plants are ranked within each region based on the maximum BCR from the five capacity addition increments included in the analysis. Economic benefits were not assigned to greenhouse gas offsets in this study. GHG offsets were not assigned dollar values because there is currently a great deal of uncertainty regarding their future valuation. The energy and economics model does include an input placeholder for potential valuation of GHG offsets in future studies. Individual state Green Energy incentives are generally not applicable to Federal projects and also contain restrictions on incremental capacity size and run-of-river operation that would preclude application to the capacity addition alternatives considered in this report.

The GHG offsets for efficiency improvements are based on generation increases from an upgrade to a new, modern turbine, which corresponds to 1.5% efficiency increase for plants that have not been rehabilitated in the last 15 years, and the increase in generation from rehabilitating a turbine to its original condition from its current state where the efficiency deterioration is a function of the age. The additional generation and GHG offsets shown for capacity additions correspond to the capacity addition increment with the highest BCR. The GHG offsets from an avoided outage of a unit on an annual basis are shown for the generation potentially lost from the final logical unit. For the majority of plants, the largest opportunity for GHG offsets is from an avoided outage of a unit, which supports investment in Reclamation's assets to minimize risk of failure based on the potential risk of generation lost and GHG emissions.

Mid-Pacific Region

The GHG offsets and associated generation for each of the 11 plants in the Mid-Pacific region are presented in Table 9-14.

Table 9-14. GHG Reduction Results - Mid-Pacific Region

Plant	GHG Offsets from Incremental Generation from Efficiency Improvements		GHG Offsets from Incremental Generation from Hydraulic Capacity Increases [1]		GHG Offsets from Avoided Energy Losses [2]	
	(MWh/yr)	metric tons CO2e/yr	(MWh/yr)	metric tons CO2e/yr	(MWh/yr)	metric tons CO2e/yr
Nimbus	4,671	1,890	6,104	2,068	21,275	8,607
Folsom	14,127	6,611	32,607	11,034	59,560	27,871
Shasta	22,831	10,684	73,426	24,380	64,233	30,058
Stampede	761	308	1,669	514	7,983	3,230
Keswick	25,762	11,239	26,278	9,419	44,802	19,545
Trinity	31,209	14,604	17,625	8,038	106,815	49,984
Judge Francis Carr	0	0	4,476	2,095	129,142	60,431
Spring Creek	36,681	17,165	12,180	5,662	88,337	41,337
San Luis	20,490	8,289	5,289	2,140	326	132
New Melones	29,916	13,999	7,830	3,664	4,568	2,138
O'Neill	371	173	251	117	306	143

Notes

[1] Incremental GHG offsets are based on the hydraulic capacity increase increment with the highest BCR.

[2] GHG offsets from avoided energy losses are based on a generic split between on-peak and off-peak hours depending on whether the plant is operated as a peaking, base load or intermediate plant.

GHG - Greenhouse Gas

The largest potential GHG offsets shown in Table 9-14 come from efficiency improvements for three of the plants, New Melones, O'Neill, and San Luis. The largest opportunity for GHG offsets for the remaining plants comes from a year-long avoided outage of the final logical unit. Overall, the largest GHG offset opportunity results from a year-long avoided outage of the final logical unit at Judge Francis Carr which would equate to a generation loss of 129,142 MWh/yr and 60,431 metric tons of CO_2e/yr from an alternate generation source in the region.

Upper Colorado Region

The GHG offsets and associated generation for each of the 12 plants in the Upper Colorado region are presented in Table 9-15. The largest potential GHG offsets come from efficiency an installed capacity increase for only one plant in the region, Glen Canyon. For the rest of the plants, the largest opportunity for GHG offsets comes from a year-long avoided outage of the final logical unit. Overall, the largest GHG offset opportunity results from a year-long avoided outage of the final logical unit at Crystal which would result in 187,173 MWh/yr of additional generation and 150,177 metric tons of CO_2e/yr offset from generation of other energy sources in the region.

Table 9-15. GHG Reduction Results - Upper Colorado Region

Plant	GHG Offsets from Incremental Generation from Efficiency Improvements		GHG Offsets from Incremental Generation from Hydraulic Capacity Increases [1]		GHG Offsets from Avoided Energy Losses [2]	
	(MWh/yr)	metric tons CO2e/yr	(MWh/yr)	metric tons CO2e/yr	(MWh/yr)	metric tons CO2e/yr
Deer Creek	391	304	1,023	796	9,380	7,304
Crystal	3,386	2,716	10,950	6,308	187,173	150,177
McPhee	301	227	413	312	5,771	4,357
Fontenelle	3,722	2,987	4,774	2,605	56,394	45,248
Glen Canyon	38,055	29,631	71,082	39,686	46,093	35,890
Towaoc	1,014	814	1,120	899	19,704	15,809
Flaming Gorge	3,891	3,030	13,495	7,302	41,896	32,622
Blue Mesa	8,673	6,547	3,219	1,929	24,308	18,351
Morrow Point	19,421	14,662	10,279	7,052	20,681	15,613
Elephant Butte	2,374	1,905	357	287	10,535	8,452
Lower Molina	250	195	133	64	19,003	14,797
Upper Molina	150	117	8	6	32,284	25,137

Notes

[1] Incremental GHG offsets are based on the hydraulic capacity increase increment with the highest BCR.

[2] GHG offsets from avoided energy losses are based on a generic split between on-peak and off-peak hours depending on whether the plant is operated as a peaking, base load or intermediate plant.

GHG - Greenhouse Gas

The GHG offsets and associated generation for each of the 21 plants in the Great Plains region are presented in Table 9-16. The largest potential GHG offsets come from efficiency improvements at five plants in the region, Estes, Flatiron, Mount Elbert, Seminoe, and Yellowtail. The largest opportunity for GHG offsets for the remaining plants comes from a year-long avoided outage of the final logical unit. Overall, the largest GHG offset opportunity results from a year-long avoided outage of the final logical unit at Pole Hill which would equate to a generation loss of 187,914 MWh/yr and 98,135 metric tons of CO_2e/yr from an alternate generation source in the region.

Table 9-16. GHG Reduction Results - Great Plains Region

Plant	GHG Offsets from Incremental Generation from Efficiency Improvements		GHG Offsets from Incremental Generation from Hydraulic Capacity Increases [1]		GHG Offsets from Avoided Energy Losses [2]	
	(MWh/yr)	metric tons CO2e/yr	(MWh/yr)	metric tons CO2e/yr	(MWh/yr)	metric tons CO2e/yr
Shoshone	1,374	734	12,347	4,055	25,922	13,514
Canyon Ferry	25,391	12,742	17,576	8,820	72,993	36,630
Guernsey	934	489	8,887	2,580	9,928	4,624
Pilot Butte	269	133	1,800	518	1,947	926
Buffalo Bill	4,268	2,277	3,985	2,077	15,231	7,941
Glendo	4,130	2,146	8,726	3,126	27,946	13,020
Fremont Canyon	14,075	7,588	9,238	4,960	64,793	34,789
Boysen	4,825	2,583	5,322	2,176	16,163	8,423
Kortes	1,943	1,124	4,594	1,625	13,075	6,845
Big Thompson	824	432	494	237	12,460	5,979
Alcova	2,406	1,392	2,003	944	23,517	12,583
Seminoe	8,288	4,451	5,592	2,486	7,507	3,978
Yellowtail	21,612	12,502	8,526	3,370	21,586	11,498
Green Mountain	2,037	1,100	2,065	725	6,331	3,243
Mount Elbert	14,379	8,434	3,965	2,410	0	0
Flatiron [3]	14,436	7,762	4,153	2,207	625	332
Estes	7,232	3,909	1,854	1,005	0	0
Pole Hill	10,906	5,538	3,173	1,657	187,914	98,135
Heart Mountain	1,465	778	481	227	22,158	11,150
Marys Lake	2,713	1,389	687	372	41,201	22,326
Spirit Mountain	652	321	220	105	12,790	6,090

Notes

[1] Incremental GHG offsets are based on the hydraulic capacity increase increment with the highest BCR.

[2] GHG offsets from avoided energy losses are based on a generic split between on-peak and off-peak hours depending on whether the plant is operated as a peaking, base load or intermediate plant.

[3] Only Units 1 and 2 (81.3 MW) at Flatiron were included in the modeling.

GHG - Greenhouse Gas

Pacific Northwest Region

The GHG offsets and associated generation for each of the ten plants in the Pacific Northwest region are presented in Table 9-17. The largest potential GHG offsets come from efficiency improvements at two plants in the region, Grand Coulee and Hungry Horse. The largest potential GHG offsets come from capacity additions for one plant in the Pacific Northwest, Boise Diversion. The largest opportunity for GHG offsets for the remaining plants comes from a year-long avoided outage of the final logical unit. Overall, the largest GHG offset opportunity results from a year-long avoided outage of the final logical unit at Palisades which would equate to a generation loss of 112,976 MWh/yr and 61,024 metric tons of CO_2e/yr from an alternate generation source in the region.

Table 9-17. GHG Reduction Results - Pacific Northwest Region

Plant	GHG Offsets from Incremental Generation from Efficiency Improvements		GHG Offsets from Incremental Generation from Hydraulic Capacity Increases [1]		GHG Offsets from Avoided Energy Losses [2]	
	(MWh/yr)	metric tons CO2e/yr	(MWh/yr)	metric tons CO2e/yr	(MWh/yr)	metric tons CO2e/yr
Black Canyon	2,211	1,194	19,026	6,815	28,133	15,196
Boise Diversion	104	60	6,231	2,778	4,738	2,741
Palisades	22,716	12,270	72,778	34,565	112,976	61,024
Minidoka	2,403	1,298	3,098	1,673	34,500	18,635
Anderson Ranch	9,215	4,978	19,805	6,039	47,816	25,828
Chandler	461	249	594	321	22,232	12,008
Grand Coulee	101,669	54,916	141	76	8,431	4,554
Hungry Horse	49,272	28,502	19,275	10,963	12,551	7,260
Green Springs	1,686	911	0	0	63,822	34,473
Roza	3,753	2,027	1,062	574	63,053	34,058

Notes

[1] Incremental GHG offsets are based on the hydraulic capacity increase increment with the highest BCR.

[2] GHG offsets from avoided energy losses are based on a generic split between on-peak and off-peak hours depending on whether the plant is operated as a peaking, base load or intermediate plant.

GHG - Greenhouse Gas

Lower Colorado Region

The GHG offsets and associated generation for each of the three plants in the Lower Colorado region are presented in Table 9-18. The largest potential GHG offsets come from efficiency improvements for Hoover, while the largest opportunity for GHG offsets at Davis and Parker come from a year-long avoided outage of the final logical unit. Overall, the largest GHG offset opportunity results from efficiency improvements at Hoover which would result in 107,275 MWh/yr of additional generation and 60,488 metric tons of CO_2e/yr offset from generation of other energy sources in the region.

Table 9-18. GHG Reduction Results - Lower Colorado Region

Plant	GHG Offsets from Incremental Generation from Efficiency Improvements		GHG Offsets from Incremental Generation from Hydraulic Capacity Increases [1]		GHG Offsets from Avoided Energy Losses [2]	
	(MWh/yr)	metric tons CO2e/yr	(MWh/yr)	metric tons CO2e/yr	(MWh/yr)	metric tons CO2e/yr
Davis	26,471	14,926	15,784	8,900	47,473	26,768
Parker	7,445	4,198	15,049	7,093	30,107	16,976
Hoover	107,275	60,488	0	0	69	39

Notes

[1] Incremental GHG offsets are based on the hydraulic capacity increase increment with the highest BCR.

[2] GHG offsets from avoided energy losses are based on a generic split between on-peak and off-peak hours depending on whether the plant is operated as a peaking, base load or intermediate plant.

GHG - Greenhouse Gas

Summary of Greenhouse Gas Reduction Opportunities Results

The potential GHG reduction opportunities and associated generation increases for each of the five Reclamation regions is summarized in Table 9-19. The largest potential GHG offsets and the largest annual generation increases from efficiency improvements is in the Pacific Northwest region. The largest potential GHG offsets and associated generation increases from capacity additions is in the Mid-Pacific region. The largest opportunity for GHG offsets from avoided outages lasting a year is in the Upper Colorado region. However the largest opportunity for avoided energy loss from outages lasting a year is in Great Plains Region. The difference in regions for GHG offsets and avoided energy loss opportunities associated with avoided outages can be explained by the regional mix of GHG emission sources that contribute to the GHG emission rates. Overall, the largest GHG offset opportunity results from a year-long avoided outage of the final logical unit for 4 of the 5 regions; the exception being Lower Colorado which has the largest GHG offset opportunity attributed to efficiency improvements. The results for the Lower Colorado region are primarily driven by Hoover which is the majority of the capacity in that region.

Table 9-19. Cumulative GHG Reduction Results by Region

Region	GHG Offsets from Incremental Generation from Efficiency Improvements		GHG Offsets from Incremental Generation from Hydraulic Capacity Increases [1]		GHG Offsets from Avoided Energy Losses [2]	
	(MWh/yr)	metric tons CO2e/yr	(MWh/yr)	metric tons CO2e/yr	(MWh/yr)	metric tons CO2e/yr
Mid Pacific	186,818	84,961	187,735	69,129	527,348	243,476
Upper Colorado	81,627	63,134	116,853	67,246	473,221	373,756
Lower Colorado	141,191	79,612	30,833	15,993	77,649	43,783
Pacific Northwest	193,491	106,405	142,011	63,803	398,253	215,777
Great Plains	144,159	77,825	105,692	45,683	584,088	302,024

Notes

[1] Incremental GHG offsets are based on the summation of the hydraulic capacity increase increment for each plant with the highest BCR.

[2] GHG offsets from avoided energy losses are based on a generic split between on-peak and off-peak hours depending on whether the plant is operated as a peaking, base load or intermediate plant.

GHG - Greenhouse Gas

This page left blank intentionally.

Chapter 10
Conclusions

Based on the results of this planning-level study, the following conclusions can be made:

1. There is no indication of economically feasible capacity additions at over 80% of the existing Reclamation hydropower plants. This is generally a confirmation of an indication that excluded the existing Reclamation plants from a 2007 Federal study of potential hydropower development at Federal facilities. Most of the original plants that showed promise for capacity additions have been studied and capacity additions already completed in a power uprating program initiated by Reclamation in 1978.

2. Results show economically feasible potential capacity additions at 10 of the 58 plants. The 10 plants that show initial promise for capacity additions are mostly among the smallest of the 58 plants. Based on the highest benefit to cost ratio, the Shoshone plant is the highest ranked for capacity addition. Based on maximum net present value, the Palisades plant is the highest ranked. These 10 plants would be candidates for more detailed feasibility studies of capacity addition.

3. Selecting the capacity addition at each of the 10 plants that has the highest benefit to cost ratio would result in a total capacity addition of about 67 megawatts across the Reclamation power system. The 67 megawatt capacity addition would represent less than one-half of one percent of the existing total nameplate capacity of the 58 plants. If maximum net present value was the criterion for selecting the capacity addition, the economic capacity addition would rise to about 143 megawatts, still less than one percent of the existing total nameplate capacity. The Palisades plant alone has over 50% of the potentially economically feasible capacity addition.

4. There is substantial potential for generation increases from efficiency gains and substantial offsets of greenhouse gasses from fossil fuel-fired generation. Costs and benefits were not assigned to the efficiency gains or greenhouse gas offsets in this study.

This page left blank intentionally.

Chapter 11
References

Electric Power Research Institute (EPRI), 2007. *Assessment of Waterpower Potential and Development Needs*, report 1014762.

Hall, D.G., and K.S. Reeves, 2006. *A Study of United States Hydroelectric Plant Ownership*, Idaho National Laboratory, Idaho Falls, ID, report INL/Ext-06-11519.

Intergovernmental Panel on Climate Change (IPCC), 2007a. *Climate Change 2007: The Physical Science Basis*. Contribution of Working Group I to the Fourth Assessment Report of the Intergovernmental Panel on Climate Change [Solomon, S., D. Qin, M. Manning, Z. Chen, M. Marquis, K.B. Averyt, M. Tignor and H.L. Miller (eds.)]. Cambridge University Press, Cambridge, United Kingdom and New York, NY, USA. 996 pp.

Intergovernmental Panel on Climate Change (IPCC), 2007b. *Climate Change 2007: Mitigation of Climate Change.* Contribution of Working Group III to the Fourth Assessment Report of the Intergovernmental Panel on Climate Change [Metz., B., O. Davidson, P. Bosch, R. Dave, L. Meyer (eds.)]. Cambridge University Press, Cambridge, United Kingdom and New York, NY, USA. 851 pp.

Energy Information Administration (EIA), 2010a. *Annual Energy Outlook 2010*, with Projections to 2035, Department of Energy, April.

Energy Information Administration (EIA), 2010b. "2016 Levelized Cost of New Generation Resources from the Annual Energy Outlook 2010".

Energy Information Administration (EIA), 2010c. "Short-Term Energy Outlook", Table 7c – U.S. Regional Electricity Prices, accessed at: http://www.eia.doe.gov/emeu/steo/pub/xls/STEO_m.xls

Federal Register, February 23, 2010. "Change in Discount Rate for Water Resources Planning", DOCID: fr23fe10-106, Federal Register Volume 75, Number 35.

Hall, Douglas G., Richard T. Hunt, Kelly S. Reeves, and Greg R. Carroll, 2003. *Estimation of Economic Parameters of U.S. Hydropower Resources.* Idaho National Engineering and Environmental Laboratory. Prepared for the U.S. Department of Energy, Contract DE-AC07-99ID13727.

Office of Management and Budget (OMB), December 8, 2009. "2010 Discount Rates for OMB Circular No. A-94", memorandum from Peter R. Orszag, Director.

U.S. Army Corps of Engineers (USACE), December 31, 1985. *Hydropower*, EM-1110-2-1701.

U.S. Army Corps of Engineers (USACE), March 31, 2010. *Civil Works Construction Cost Index System*, EM-1110-2-1304.

U.S. Bureau of Reclamation (Reclamation), 2010. "Construction Cost Trends", Web site http://www.usbr.gov/pmts/estimate/cost_trend.html, accessed on August 12, 2010.

U.S. Department of the Interior, U.S. Army Corps of Engineers, and U.S. Department of Energy, May 2007. *Potential Hydroelectric Development at Existing Federal Facilities*, for Section 1834 of the Energy Policy Act of 2005.

U.S. Environmental Protection Agency (USEPA), 2008. *The Emission & Generation Resource Integrated Database for 2007* – (eGRID2007) Technical Support Document. Office of Atmospheric Programs. September.

Chapter 12
List of Preparers

MWH AMERICAS, INC.

Nancy Walker – Project Manager; Climate Change/Sustainable Development; B.S. Geology, California State University; M.S. Geology, University of Reno, Mackay School of Mines

John Haapala, P.E. – Energy model prototype, economics, and report author; Hydrologic/Hydraulic Engineer; B.S. and M.S., Civil Engineering, University of Washington.

Jill Gray – Energy model development, initial and final energy model runs, and report author; Professional Environmental Scientist; B.S. Environmental Science and Economics, Rensselaer Polytechnic Institute.

Patrick Hartel, P.E. – Energy and capacity value development, and report reviewer; Hydroelectric Systems Planning Specialist; B.S., Civil Engineering, Bradley University; M.S., Civil Engineering, Colorado State University.

Stanley Hayes, P.E. – Unit efficiencies and report reviewer; Vice-President; B.S. Mechanical Engineering, University of Illinois.

Eric Wooden – Energy model data preparation and initial runs; Mechanical Engineer; B.S. Mechanical Engineering, University of Missouri, Rolla.

RECLAMATION AND USACE

MWH wishes to acknowledge the constructive comments and coordination efforts from Michael Pulskamp of Reclamation and Michael Berger of the USACE Hydroelectric Design Center. We also wish to acknowledge the efforts of Reclamation personnel in each Region to respond to our extensive data requests in a timely manner.

This page left blank intentionally.

APPENDIX A

Capacity Addition Detailed Economic Results

This page left blank intentionally.

Summary of Capacity Increase Benefits and Costs
Alcova

Percent Capacity Increase	Capacity Increase (MW)	Average Incremental Energy (MWh/yr)	Total Incremental Capacity Factor	Construction & Mitigation Total Cost ($M)	Construction & Mitigation Total Cost ($/kW)	PV of Total Costs ($M)	PV of Energy Benefits ($M)	PV of Capacity Benefits ($M)	PV of Total Benefits ($M)	NPV of Total Benefits ($M)	B/C Ratio
10%	4.1	1,162	3%	$7.5	$1,823	$10.9	$1.3	$1.6	$2.9	-$8.0	0.26
20%	8.3	2,003	3%	$13.3	$1,605	$18.9	$2.2	$3.0	$5.2	-$13.7	0.27
30%	12.4	2,647	2%	$18.5	$1,491	$26.2	$2.9	$4.3	$7.2	-$19.0	0.27
40%	16.6	3,186	2%	$23.4	$1,416	$33.0	$3.5	$5.5	$8.9	-$24.1	0.27
50%	20.7	3,662	2%	$28.2	$1,361	$39.5	$4.0	$6.6	$10.6	-$28.9	0.27



Summary of Capacity Increase Benefits and Costs
Anderson Ranch

Percent Capacity Increase	Capacity Increase (MW)	Average Incremental Energy (MWh/yr)	Total Incremental Capacity Factor	Construction & Mitigation Total Cost ($M)	Construction & Mitigation Total Cost ($/kW)	PV of Total Costs ($M)	PV of Energy Benefits ($M)	PV of Capacity Benefits ($M)	PV of Total Benefits ($M)	NPV of Total Benefits ($M)	B/C Ratio
10%	4.0	3,701	11%	$7.3	$1,835	$10.6	$4.1	$3.3	$7.4	-$3.2	0.70
20%	8.0	6,108	9%	$12.9	$1,615	$18.4	$6.8	$5.8	$12.5	-$5.9	0.68
30%	12.0	8,595	8%	$18.0	$1,500	$25.5	$9.5	$8.3	$17.8	-$7.7	0.70
40%	16.0	14,201	10%	$22.8	$1,425	$32.1	$15.7	$12.9	$28.6	-$3.5	0.89
50%	20.0	17,220	10%	$27.4	$1,369	$38.4	$19.0	$15.8	$34.8	-$3.6	0.91



Summary of Capacity Increase Benefits and Costs
Big Thompson

Percent Capacity Increase	Capacity Increase (MW)	Average Incremental Energy (MWh/yr)	Total Incremental Capacity Factor	Construction & Mitigation Total Cost ($M)	Construction & Mitigation Total Cost ($/kW)	PV of Total Costs ($M)	PV of Energy Benefits ($M)	PV of Capacity Benefits ($M)	PV of Total Benefits ($M)	NPV of Total Benefits ($M)	B/C Ratio
10%	0.5	283	7%	$1.3	$2,797	$1.9	$0.3	$0.3	$0.6	-$1.3	0.30
20%	0.9	409	5%	$2.2	$2,438	$3.2	$0.4	$0.5	$0.9	-$2.4	0.27
30%	1.4	493	4%	$3.0	$2,254	$4.5	$0.5	$0.6	$1.1	-$3.4	0.24
40%	1.8	545	3%	$3.8	$2,133	$5.6	$0.5	$0.7	$1.3	-$4.4	0.23
50%	2.3	571	3%	$4.6	$2,044	$6.7	$0.6	$0.8	$1.4	-$5.3	0.21



Summary of Capacity Increase Benefits and Costs
Black Canyon

Percent Capacity Increase	Capacity Increase (MW)	Average Incremental Energy (MWh/yr)	Total Incremental Capacity Factor	Construction & Mitigation Total Cost ($M)	Construction & Mitigation Total Cost ($/kW)	PV of Total Costs ($M)	PV of Energy Benefits ($M)	PV of Capacity Benefits ($M)	PV of Total Benefits ($M)	NPV of Total Benefits ($M)	B/C Ratio
10%	1.0	4,022	45%	$2.4	$2,379	$3.6	$4.4	$2.3	$6.8	$3.2	1.89
20%	2.0	8,529	48%	$4.2	$2,082	$6.2	$9.4	$4.8	$14.2	$8.0	2.29
30%	3.1	12,616	47%	$5.9	$1,929	$8.6	$13.9	$7.1	$21.0	$12.5	2.46
40%	4.1	16,027	45%	$7.5	$1,828	$10.8	$17.7	$9.3	$27.0	$16.2	2.51
50%	5.1	19,026	43%	$8.9	$1,754	$12.9	$21.0	$11.4	$32.4	$19.6	2.52



Summary of Capacity Increase Benefits and Costs
Blue Mesa

Percent Capacity Increase	Capacity Increase (MW)	Average Incremental Energy (MWh/yr)	Total Incremental Capacity Factor	Construction & Mitigation Total Cost ($M)	Construction & Mitigation Total Cost ($/kW)	PV of Total Costs ($M)	PV of Energy Benefits ($M)	PV of Capacity Benefits ($M)	PV of Total Benefits ($M)	NPV of Total Benefits ($M)	B/C Ratio
10%	8.6	1,188	2%	$13.8	$1,592	$19.6	$1.7	$2.5	$4.2	-$15.4	0.21
20%	17.3	2,073	1%	$24.3	$1,405	$34.1	$2.9	$4.9	$7.8	-$26.4	0.23
30%	25.9	2,735	1%	$33.9	$1,307	$47.3	$3.9	$7.0	$10.9	-$36.4	0.23
40%	34.6	3,286	1%	$43.0	$1,243	$59.6	$4.6	$9.1	$13.8	-$45.8	0.23
50%	43.2	3,739	1%	$51.6	$1,195	$71.3	$5.3	$11.2	$16.5	-$54.8	0.23



Summary of Capacity Increase Benefits and Costs
Boise Diversion

Percent Capacity Increase	Capacity Increase (MW)	Average Incremental Energy (MWh/yr)	Total Incremental Capacity Factor	Construction & Mitigation Total Cost ($M)	Construction & Mitigation Total Cost ($/kW)	PV of Total Costs ($M)	PV of Energy Benefits ($M)	PV of Capacity Benefits ($M)	PV of Total Benefits ($M)	NPV of Total Benefits ($M)	B/C Ratio
10%	0.3	1,825	60%	$1.0	$2,951	$1.5	$2.3	$0.9	$3.2	$1.7	2.09
20%	0.7	3,527	58%	$1.8	$2,569	$2.6	$4.4	$1.7	$6.2	$3.5	2.35
30%	1.0	5,062	56%	$2.5	$2,373	$3.6	$6.3	$2.6	$8.9	$5.3	2.46
40%	1.4	6,327	52%	$3.1	$2,244	$4.6	$7.9	$3.3	$11.3	$6.7	2.48
50%	1.7	7,330	49%	$3.7	$2,150	$5.4	$9.2	$4.1	$13.2	$7.8	2.44



Summary of Capacity Increase Benefits and Costs
Boysen

Percent Capacity Increase	Capacity Increase (MW)	Average Incremental Energy (MWh/yr)	Total Incremental Capacity Factor	Construction & Mitigation Total Cost ($M)	Construction & Mitigation Total Cost ($/kW)	PV of Total Costs ($M)	PV of Energy Benefits ($M)	PV of Capacity Benefits ($M)	PV of Total Benefits ($M)	NPV of Total Benefits ($M)	B/C Ratio
10%	1.5	1,366	10%	$3.3	$2,208	$4.9	$1.4	$1.2	$2.6	-$2.2	0.54
20%	3.0	2,360	9%	$5.8	$1,936	$8.4	$2.4	$2.2	$4.6	-$3.8	0.55
30%	4.5	3,267	8%	$8.1	$1,795	$11.6	$3.4	$3.1	$6.5	-$5.1	0.56
40%	6.0	4,097	8%	$10.2	$1,702	$14.6	$4.2	$4.0	$8.2	-$6.4	0.56
50%	7.5	4,776	7%	$12.3	$1,634	$17.5	$4.9	$4.8	$9.7	-$7.8	0.55



Summary of Capacity Increase Benefits and Costs
Buffalo Bill

Percent Capacity Increase	Capacity Increase (MW)	Average Incremental Energy (MWh/yr)	Total Incremental Capacity Factor	Construction & Mitigation Total Cost ($M)	Construction & Mitigation Total Cost ($/kW)	PV of Total Costs ($M)	PV of Energy Benefits ($M)	PV of Capacity Benefits ($M)	PV of Total Benefits ($M)	NPV of Total Benefits ($M)	B/C Ratio
10%	1.8	2,452	16%	$3.8	$2,133	$5.6	$2.5	$2.0	$4.6	-$1.1	0.81
20%	3.6	3,920	12%	$6.7	$1,871	$9.7	$4.0	$3.4	$7.4	-$2.3	0.76
30%	5.4	5,174	11%	$9.4	$1,736	$13.5	$5.3	$4.6	$10.0	-$3.5	0.74
40%	7.2	6,392	10%	$11.9	$1,646	$16.9	$6.6	$5.8	$12.4	-$4.5	0.73
50%	9.0	7,579	10%	$14.2	$1,581	$20.3	$7.8	$7.0	$14.8	-$5.5	0.73



Summary of Capacity Increase Benefits and Costs
Canyon Ferry

Percent Capacity Increase	Capacity Increase (MW)	Average Incremental Energy (MWh/yr)	Total Incremental Capacity Factor	Construction & Mitigation Total Cost ($M)	Construction & Mitigation Total Cost ($/kW)	PV of Total Costs ($M)	PV of Energy Benefits ($M)	PV of Capacity Benefits ($M)	PV of Total Benefits ($M)	NPV of Total Benefits ($M)	B/C Ratio
10%	5.0	11,211	26%	$8.8	$1,760	$12.7	$10.7	$8.7	$19.4	$6.7	1.53
20%	10.0	18,956	22%	$15.5	$1,551	$22.0	$18.1	$15.0	$33.1	$11.0	1.50
30%	15.0	24,524	19%	$21.6	$1,441	$30.5	$23.4	$19.8	$43.2	$12.7	1.42
40%	20.0	29,173	17%	$27.4	$1,369	$38.4	$27.9	$23.9	$51.8	$13.4	1.35
50%	25.0	32,781	15%	$32.9	$1,316	$45.9	$31.3	$27.4	$58.7	$12.8	1.28



Summary of Capacity Increase Benefits and Costs
Chandler

Percent Capacity Increase	Capacity Increase (MW)	Average Incremental Energy (MWh/yr)	Total Incremental Capacity Factor	Construction & Mitigation Total Cost ($M)	Construction & Mitigation Total Cost ($/kW)	PV of Total Costs ($M)	PV of Energy Benefits ($M)	PV of Capacity Benefits ($M)	PV of Total Benefits ($M)	NPV of Total Benefits ($M)	B/C Ratio
10%	1.2	594	6%	$2.8	$2,305	$4.1	$0.7	$0.6	$1.3	-$2.8	0.32
20%	2.4	606	3%	$4.8	$2,019	$7.1	$0.7	$0.9	$1.6	-$5.5	0.22
30%	3.6	606	2%	$6.7	$1,871	$9.7	$0.7	$1.1	$1.8	-$7.9	0.18
40%	4.8	606	1%	$8.5	$1,774	$12.3	$0.7	$1.4	$2.0	-$10.2	0.17
50%	6.0	606	1%	$10.2	$1,702	$14.6	$0.7	$1.6	$2.3	-$12.4	0.16



Summary of Capacity Increase Benefits and Costs
Crystal

Percent Capacity Increase	Capacity Increase (MW)	Average Incremental Energy (MWh/yr)	Total Incremental Capacity Factor	Construction & Mitigation Total Cost ($M)	Construction & Mitigation Total Cost ($/kW)	PV of Total Costs ($M)	PV of Energy Benefits ($M)	PV of Capacity Benefits ($M)	PV of Total Benefits ($M)	NPV of Total Benefits ($M)	B/C Ratio
10%	3.2	4,306	16%	$6.0	$1,918	$8.8	$4.6	$3.6	$8.2	-$0.6	0.94
20%	6.3	7,862	14%	$10.6	$1,687	$15.2	$8.5	$6.6	$15.1	-$0.1	0.99
30%	9.5	10,950	13%	$14.8	$1,567	$21.1	$11.8	$9.4	$21.2	$0.1	1.00
40%	12.6	13,378	12%	$18.7	$1,487	$26.5	$14.4	$11.7	$26.1	-$0.4	0.98
50%	15.8	15,466	11%	$22.5	$1,429	$31.7	$16.6	$13.7	$30.4	-$1.3	0.96



Summary of Capacity Increase Benefits and Costs
Davis

Percent Capacity Increase	Capacity Increase (MW)	Average Incremental Energy (MWh/yr)	Total Incremental Capacity Factor	Construction & Mitigation Total Cost ($M)	Construction & Mitigation Total Cost ($/kW)	PV of Total Costs ($M)	PV of Energy Benefits ($M)	PV of Capacity Benefits ($M)	PV of Total Benefits ($M)	NPV of Total Benefits ($M)	B/C Ratio
10%	25.5	15,784	7%	$33.4	$1,311	$46.7	$19.6	$15.9	$35.5	-$11.1	0.76
20%	51.0	24,770	6%	$59.2	$1,161	$81.5	$30.8	$27.1	$57.9	-$23.6	0.71
30%	76.5	30,034	4%	$82.8	$1,082	$113.0	$37.3	$35.8	$73.2	-$39.8	0.65
40%	102.0	34,096	4%	$105.1	$1,030	$142.5	$42.4	$43.7	$86.1	-$56.4	0.60
50%	127.5	36,470	3%	$126.5	$992	$170.7	$45.4	$50.4	$95.7	-$74.9	0.56



Summary of Capacity Increase Benefits and Costs
Deer Creek

Percent Capacity Increase	Capacity Increase (MW)	Average Incremental Energy (MWh/yr)	Total Incremental Capacity Factor	Construction & Mitigation Total Cost ($M)	Construction & Mitigation Total Cost ($/kW)	PV of Total Costs ($M)	PV of Energy Benefits ($M)	PV of Capacity Benefits ($M)	PV of Total Benefits ($M)	NPV of Total Benefits ($M)	B/C Ratio
10%	0.5	1,120	26%	$1.4	$2,744	$2.0	$1.2	$0.9	$2.1	$0.1	1.04
20%	1.0	1,913	22%	$2.4	$2,393	$3.5	$2.1	$1.5	$3.6	$0.1	1.03
30%	1.5	2,507	19%	$3.3	$2,213	$4.8	$2.8	$2.0	$4.8	$0.0	0.99
40%	2.0	2,981	17%	$4.1	$2,094	$6.1	$3.3	$2.4	$5.7	-$0.3	0.95
50%	2.5	3,372	16%	$5.0	$2,008	$7.2	$3.7	$2.8	$6.5	-$0.7	0.90



Summary of Capacity Increase Benefits and Costs
Elephant Butte

Percent Capacity Increase	Capacity Increase (MW)	Average Incremental Energy (MWh/yr)	Total Incremental Capacity Factor	Construction & Mitigation Total Cost ($M)	Construction & Mitigation Total Cost ($/kW)	PV of Total Costs ($M)	PV of Energy Benefits ($M)	PV of Capacity Benefits ($M)	PV of Total Benefits ($M)	NPV of Total Benefits ($M)	B/C Ratio
10%	2.8	357	1%	$5.5	$1,962	$8.0	$0.4	$0.8	$1.2	-$6.8	0.15
20%	5.6	363	1%	$9.6	$1,725	$13.8	$0.4	$1.4	$1.8	-$12.1	0.13
30%	8.4	363	0%	$13.4	$1,601	$19.1	$0.4	$1.9	$2.3	-$16.8	0.12
40%	11.2	363	0%	$17.0	$1,520	$24.1	$0.4	$2.5	$2.9	-$21.2	0.12
50%	14.0	363	0%	$20.4	$1,460	$28.8	$0.4	$3.0	$3.4	-$25.4	0.12



Summary of Capacity Increase Benefits and Costs
Estes

Percent Capacity Increase	Capacity Increase (MW)	Average Incremental Energy (MWh/yr)	Total Incremental Capacity Factor	Construction & Mitigation Total Cost ($M)	Construction & Mitigation Total Cost ($/kW)	PV of Total Costs ($M)	PV of Energy Benefits ($M)	PV of Capacity Benefits ($M)	PV of Total Benefits ($M)	NPV of Total Benefits ($M)	B/C Ratio
10%	4.5	0	0%	$8.1	$1,795	$11.6	$0.0	$0.9	$0.9	-$10.7	0.08
20%	9.0	0	0%	$14.2	$1,581	$20.3	$0.0	$1.8	$1.8	-$18.5	0.09
30%	13.5	0	0%	$19.8	$1,469	$28.0	$0.0	$2.7	$2.7	-$25.3	0.10
40%	18.0	0	0%	$25.1	$1,395	$35.3	$0.0	$3.6	$3.6	-$31.7	0.10
50%	22.5	0	0%	$30.2	$1,341	$42.2	$0.0	$4.5	$4.5	-$37.7	0.11



Summary of Capacity Increase Benefits and Costs
Flaming Gorge

Percent Capacity Increase	Capacity Increase (MW)	Average Incremental Energy (MWh/yr)	Total Incremental Capacity Factor	Construction & Mitigation Total Cost ($M)	Construction & Mitigation Total Cost ($/kW)	PV of Total Costs ($M)	PV of Energy Benefits ($M)	PV of Capacity Benefits ($M)	PV of Total Benefits ($M)	NPV of Total Benefits ($M)	B/C Ratio
10%	15.2	4,211	3%	$21.8	$1,438	$30.8	$4.7	$5.9	$10.6	-$20.2	0.34
20%	30.4	6,881	3%	$38.6	$1,271	$53.7	$7.6	$10.8	$18.4	-$35.3	0.34
30%	45.6	9,378	2%	$54.0	$1,184	$74.4	$10.4	$15.5	$25.9	-$48.6	0.35
40%	60.8	11,526	2%	$68.5	$1,126	$93.8	$12.7	$20.0	$32.8	-$61.1	0.35
50%	76.0	13,495	2%	$82.3	$1,084	$112.3	$14.9	$24.4	$39.3	-$73.0	0.35



Summary of Capacity Increase Benefits and Costs
Flatiron

Percent Capacity Increase	Capacity Increase (MW)	Average Incremental Energy (MWh/yr)	Total Incremental Capacity Factor	Construction & Mitigation Total Cost ($M)	Construction & Mitigation Total Cost ($/kW)	PV of Total Costs ($M)	PV of Energy Benefits ($M)	PV of Capacity Benefits ($M)	PV of Total Benefits ($M)	NPV of Total Benefits ($M)	B/C Ratio
10%	8.1	0	0%	$13.1	$1,610	$18.7	$0.0	$1.6	$1.6	-$17.0	0.09
20%	16.3	0	0%	$23.1	$1,421	$32.5	$0.0	$3.2	$3.2	-$29.3	0.10
30%	24.4	0	0%	$32.2	$1,322	$45.0	$0.0	$4.9	$4.9	-$40.1	0.11
40%	32.5	0	0%	$40.8	$1,256	$56.7	$0.0	$6.5	$6.5	-$50.2	0.11
50%	40.6	0	0%	$49.1	$1,208	$67.9	$0.0	$8.1	$8.1	-$59.7	0.12



Summary of Capacity Increase Benefits and Costs
Folsom

Percent Capacity Increase	Capacity Increase (MW)	Average Incremental Energy (MWh/yr)	Total Incremental Capacity Factor	Construction & Mitigation Total Cost ($M)	Construction & Mitigation Total Cost ($/kW)	PV of Total Costs ($M)	PV of Energy Benefits ($M)	PV of Capacity Benefits ($M)	PV of Total Benefits ($M)	NPV of Total Benefits ($M)	B/C Ratio
10%	20.7	12,591	7%	$28.2	$1,361	$39.5	$22.5	$12.7	$35.3	-$4.2	0.89
20%	41.4	23,579	7%	$49.8	$1,204	$68.9	$42.2	$24.4	$66.6	-$2.3	0.97
30%	62.1	32,607	6%	$69.7	$1,122	$95.5	$58.4	$34.7	$93.1	-$2.4	0.97
40%	82.8	40,555	6%	$88.4	$1,068	$120.4	$72.6	$44.3	$116.8	-$3.6	0.97
50%	103.5	47,195	5%	$106.4	$1,028	$144.2	$84.5	$52.9	$137.4	-$6.8	0.95



Summary of Capacity Increase Benefits and Costs
Fontenelle

Percent Capacity Increase	Capacity Increase (MW)	Average Incremental Energy (MWh/yr)	Total Incremental Capacity Factor	Construction & Mitigation Total Cost ($M)	Construction & Mitigation Total Cost ($/kW)	PV of Total Costs ($M)	PV of Energy Benefits ($M)	PV of Capacity Benefits ($M)	PV of Total Benefits ($M)	NPV of Total Benefits ($M)	B/C Ratio
10%	1.0	884	10%	$2.4	$2,388	$3.5	$0.8	$0.8	$1.6	-$1.9	0.47
20%	2.0	1,595	9%	$4.2	$2,090	$6.1	$1.5	$1.5	$3.0	-$3.1	0.49
30%	3.0	2,296	9%	$5.8	$1,936	$8.4	$2.2	$2.2	$4.4	-$4.1	0.52
40%	4.0	3,050	9%	$7.3	$1,835	$10.6	$2.9	$2.9	$5.8	-$4.8	0.55
50%	5.0	3,824	9%	$8.8	$1,760	$12.7	$3.7	$3.6	$7.3	-$5.4	0.57



Summary of Capacity Increase Benefits and Costs
Fremont Canyon

Percent Capacity Increase	Capacity Increase (MW)	Average Incremental Energy (MWh/yr)	Total Incremental Capacity Factor	Construction & Mitigation Total Cost ($M)	Construction & Mitigation Total Cost ($/kW)	PV of Total Costs ($M)	PV of Energy Benefits ($M)	PV of Capacity Benefits ($M)	PV of Total Benefits ($M)	NPV of Total Benefits ($M)	B/C Ratio
10%	6.7	4,831	8%	$11.1	$1,669	$16.0	$5.3	$4.6	$9.9	-$6.0	0.62
20%	13.4	8,128	7%	$19.7	$1,472	$27.8	$8.9	$8.2	$17.1	-$10.7	0.62
30%	20.0	10,512	6%	$27.4	$1,369	$38.5	$11.5	$11.2	$22.7	-$15.8	0.59
40%	26.7	12,231	5%	$34.7	$1,300	$48.4	$13.4	$13.7	$27.1	-$21.4	0.56
50%	33.4	13,583	5%	$41.8	$1,250	$58.0	$14.8	$16.0	$30.8	-$27.2	0.53



Summary of Capacity Increase Benefits and Costs
Glen Canyon

Percent Capacity Increase	Capacity Increase (MW)	Average Incremental Energy (MWh/yr)	Total Incremental Capacity Factor	Construction & Mitigation Total Cost ($M)	Construction & Mitigation Total Cost ($/kW)	PV of Total Costs ($M)	PV of Energy Benefits ($M)	PV of Capacity Benefits ($M)	PV of Total Benefits ($M)	NPV of Total Benefits ($M)	B/C Ratio
10%	132.0	23,719	2%	$130.2	$986	$175.5	$29.5	$42.6	$72.1	-$103.4	0.41
20%	264.0	50,969	2%	$231.7	$878	$307.7	$63.4	$87.5	$150.9	-$156.7	0.49
30%	396.0	71,082	2%	$324.9	$820	$427.6	$88.4	$127.6	$216.0	-$211.5	0.51
40%	528.0	86,174	2%	$413.2	$783	$540.3	$107.2	$164.3	$271.5	-$268.8	0.50
50%	660.0	94,012	2%	$498.0	$755	$647.9	$116.9	$196.0	$312.9	-$334.9	0.48



Summary of Capacity Increase Benefits and Costs
Glendo

Percent Capacity Increase	Capacity Increase (MW)	Average Incremental Energy (MWh/yr)	Total Incremental Capacity Factor	Construction & Mitigation Total Cost ($M)	Construction & Mitigation Total Cost ($/kW)	PV of Total Costs ($M)	PV of Energy Benefits ($M)	PV of Capacity Benefits ($M)	PV of Total Benefits ($M)	NPV of Total Benefits ($M)	B/C Ratio
10%	3.8	4,425	13%	$7.0	$1,852	$10.2	$3.6	$3.8	$7.4	-$2.8	0.73
20%	7.6	7,585	11%	$12.4	$1,630	$17.7	$6.2	$6.7	$12.9	-$4.8	0.73
30%	11.4	9,144	9%	$17.3	$1,514	$24.5	$7.5	$8.5	$16.0	-$8.5	0.65
40%	15.2	10,169	8%	$21.9	$1,438	$30.8	$8.3	$10.0	$18.3	-$12.5	0.59
50%	19.0	11,105	7%	$26.2	$1,382	$36.8	$9.1	$11.4	$20.5	-$16.4	0.56



Summary of Capacity Increase Benefits and Costs
Grand Coulee

Percent Capacity Increase	Capacity Increase (MW)	Average Incremental Energy (MWh/yr)	Total Incremental Capacity Factor	Construction & Mitigation Total Cost ($M)	Construction & Mitigation Total Cost ($/kW)	PV of Total Costs ($M)	PV of Energy Benefits ($M)	PV of Capacity Benefits ($M)	PV of Total Benefits ($M)	NPV of Total Benefits ($M)	B/C Ratio
10%	649.5	141	0%	$491.4	$757	$639.5	$0.2	$129.8	$129.9	-$509.5	0.20
20%	1,299.0	141	0%	$878.8	$676	$1,125.5	$0.2	$259.4	$259.6	-$865.9	0.23
30%	1,948.5	141	0%	$1,236.0	$634	$1,568.0	$0.2	$389.1	$389.2	-$1,178.8	0.25
40%	2,598.0	141	0%	$1,575.1	$606	$1,984.7	$0.2	$518.7	$518.9	-$1,465.8	0.26
50%	3,247.5	141	0%	$1,901.5	$586	$2,383.3	$0.2	$648.4	$648.5	-$1,734.8	0.27



Summary of Capacity Increase Benefits and Costs
Green Mountain

Percent Capacity Increase	Capacity Increase (MW)	Average Incremental Energy (MWh/yr)	Total Incremental Capacity Factor	Construction & Mitigation Total Cost ($M)	Construction & Mitigation Total Cost ($/kW)	PV of Total Costs ($M)	PV of Energy Benefits ($M)	PV of Capacity Benefits ($M)	PV of Total Benefits ($M)	NPV of Total Benefits ($M)	B/C Ratio
10%	2.6	540	2%	$5.2	$1,989	$7.5	$0.6	$0.9	$1.5	-$6.0	0.20
20%	5.2	1,003	2%	$9.1	$1,748	$13.1	$1.1	$1.7	$2.8	-$10.2	0.22
30%	7.8	1,415	2%	$12.7	$1,622	$18.1	$1.6	$2.5	$4.1	-$14.0	0.23
40%	10.4	1,762	2%	$16.0	$1,540	$22.7	$2.0	$3.3	$5.3	-$17.5	0.23
50%	13.0	2,065	2%	$19.2	$1,479	$27.2	$2.3	$4.0	$6.3	-$20.9	0.23



Summary of Capacity Increase Benefits and Costs
Green Springs

Percent Capacity Increase	Capacity Increase (MW)	Average Incremental Energy (MWh/yr)	Total Incremental Capacity Factor	Construction & Mitigation Total Cost ($M)	Construction & Mitigation Total Cost ($/kW)	PV of Total Costs ($M)	PV of Energy Benefits ($M)	PV of Capacity Benefits ($M)	PV of Total Benefits ($M)	NPV of Total Benefits ($M)	B/C Ratio
10%	1.7	0	0%	$3.7	$2,149	$5.4	$0.0	$0.3	$0.3	-$5.1	0.06
20%	3.5	0	0%	$6.5	$1,885	$9.4	$0.0	$0.7	$0.7	-$8.8	0.07
30%	5.2	0	0%	$9.1	$1,748	$13.0	$0.0	$1.0	$1.0	-$12.0	0.08
40%	6.9	0	0%	$11.5	$1,658	$16.4	$0.0	$1.4	$1.4	-$15.0	0.08
50%	8.6	0	0%	$13.8	$1,592	$19.6	$0.0	$1.7	$1.7	-$17.9	0.09



Summary of Capacity Increase Benefits and Costs
Guernsey

Percent Capacity Increase	Capacity Increase (MW)	Average Incremental Energy (MWh/yr)	Total Incremental Capacity Factor	Construction & Mitigation Total Cost ($M)	Construction & Mitigation Total Cost ($/kW)	PV of Total Costs ($M)	PV of Energy Benefits ($M)	PV of Capacity Benefits ($M)	PV of Total Benefits ($M)	NPV of Total Benefits ($M)	B/C Ratio
10%	0.6	1,830	33%	$1.7	$2,607	$2.5	$1.5	$1.3	$2.8	$0.3	1.13
20%	1.3	3,599	32%	$2.9	$2,277	$4.3	$2.9	$2.6	$5.5	$1.3	1.29
30%	1.9	5,325	32%	$4.0	$2,107	$5.9	$4.3	$3.9	$8.2	$2.3	1.39
40%	2.6	7,011	31%	$5.1	$1,995	$7.4	$5.7	$5.2	$10.9	$3.5	1.47
50%	3.2	8,673	31%	$6.1	$1,913	$8.9	$7.1	$6.4	$13.5	$4.6	1.52



Summary of Capacity Increase Benefits and Costs
Heart Mountain

Percent Capacity Increase	Capacity Increase (MW)	Average Incremental Energy (MWh/yr)	Total Incremental Capacity Factor	Construction & Mitigation Total Cost ($M)	Construction & Mitigation Total Cost ($/kW)	PV of Total Costs ($M)	PV of Energy Benefits ($M)	PV of Capacity Benefits ($M)	PV of Total Benefits ($M)	NPV of Total Benefits ($M)	B/C Ratio
10%	0.5	40	1%	$1.4	$2,739	$2.0	$0.0	$0.1	$0.2	-$1.9	0.08
20%	1.0	58	1%	$2.4	$2,388	$3.5	$0.1	$0.2	$0.3	-$3.2	0.08
30%	1.5	75	1%	$3.3	$2,208	$4.9	$0.1	$0.4	$0.4	-$4.4	0.09
40%	2.0	90	1%	$4.2	$2,090	$6.1	$0.1	$0.5	$0.5	-$5.6	0.09
50%	2.5	105	0%	$5.0	$2,004	$7.3	$0.1	$0.6	$0.7	-$6.6	0.09



Summary of Capacity Increase Benefits and Costs
Hoover

Percent Capacity Increase	Capacity Increase (MW)	Average Incremental Energy (MWh/yr)	Total Incremental Capacity Factor	Construction & Mitigation Total Cost ($M)	Construction & Mitigation Total Cost ($/kW)	PV of Total Costs ($M)	PV of Energy Benefits ($M)	PV of Capacity Benefits ($M)	PV of Total Benefits ($M)	NPV of Total Benefits ($M)	B/C Ratio
10%	207.9	0	0%	$189.9	$913	$253.5	$0.0	$41.5	$41.5	-$212.0	0.16
20%	415.8	0	0%	$338.4	$814	$444.8	$0.0	$83.0	$83.0	-$361.8	0.19
30%	623.6	0	0%	$474.9	$762	$618.6	$0.0	$124.5	$124.5	-$494.2	0.20
40%	831.5	0	0%	$604.3	$727	$782.0	$0.0	$166.0	$166.0	-$616.0	0.21
50%	1,039.4	0	0%	$728.7	$701	$938.2	$0.0	$207.5	$207.5	-$730.7	0.22



Summary of Capacity Increase Benefits and Costs
Hungry Horse

Percent Capacity Increase	Capacity Increase (MW)	Average Incremental Energy (MWh/yr)	Total Incremental Capacity Factor	Construction & Mitigation Total Cost ($M)	Construction & Mitigation Total Cost ($/kW)	PV of Total Costs ($M)	PV of Energy Benefits ($M)	PV of Capacity Benefits ($M)	PV of Total Benefits ($M)	NPV of Total Benefits ($M)	B/C Ratio
10%	42.8	1,198	0%	$51.2	$1,197	$70.7	$1.5	$9.4	$10.9	-$59.9	0.15
20%	85.6	2,103	0%	$90.9	$1,062	$123.7	$2.6	$18.5	$21.2	-$102.5	0.17
30%	128.4	2,850	0%	$127.2	$991	$171.6	$3.6	$27.6	$31.2	-$140.5	0.18
40%	171.2	3,173	0%	$161.5	$944	$216.6	$4.0	$36.3	$40.3	-$176.3	0.19
50%	214.0	3,173	0%	$194.5	$909	$259.5	$4.0	$44.9	$48.9	-$210.6	0.19



Summary of Capacity Increase Benefits and Costs
Judge Francis Carr

Percent Capacity Increase	Capacity Increase (MW)	Average Incremental Energy (MWh/yr)	Total Incremental Capacity Factor	Construction & Mitigation Total Cost ($M)	Construction & Mitigation Total Cost ($/kW)	PV of Total Costs ($M)	PV of Energy Benefits ($M)	PV of Capacity Benefits ($M)	PV of Total Benefits ($M)	NPV of Total Benefits ($M)	B/C Ratio
10%	15.4	4,476	3%	$22.1	$1,434	$31.2	$8.0	$6.1	$14.2	-$17.0	0.45
20%	30.9	5,028	2%	$39.1	$1,268	$54.4	$9.0	$9.6	$18.6	-$35.8	0.34
30%	46.3	5,054	1%	$54.7	$1,181	$75.4	$9.0	$12.7	$21.7	-$53.6	0.29
40%	61.8	5,054	1%	$69.4	$1,123	$95.1	$9.0	$15.8	$24.8	-$70.2	0.26
50%	77.2	5,054	1%	$83.4	$1,081	$113.8	$9.0	$18.9	$27.9	-$85.9	0.25



Summary of Capacity Increase Benefits and Costs
Keswick

Percent Capacity Increase	Capacity Increase (MW)	Average Incremental Energy (MWh/yr)	Total Incremental Capacity Factor	Construction & Mitigation Total Cost ($M)	Construction & Mitigation Total Cost ($/kW)	PV of Total Costs ($M)	PV of Energy Benefits ($M)	PV of Capacity Benefits ($M)	PV of Total Benefits ($M)	NPV of Total Benefits ($M)	B/C Ratio
10%	11.7	5,517	5%	$17.6	$1,507	$25.0	$8.8	$6.1	$14.9	-$10.1	0.60
20%	23.4	10,308	5%	$31.2	$1,331	$43.5	$16.4	$11.7	$28.2	-$15.4	0.65
30%	35.1	14,427	5%	$43.5	$1,239	$60.3	$23.0	$16.9	$39.9	-$20.4	0.66
40%	46.8	18,040	4%	$55.2	$1,179	$76.0	$28.8	$21.7	$50.4	-$25.6	0.66
50%	58.5	21,245	4%	$66.3	$1,134	$91.0	$33.9	$26.2	$60.1	-$30.9	0.66



Summary of Capacity Increase Benefits and Costs
Kortes

Percent Capacity Increase	Capacity Increase (MW)	Average Incremental Energy (MWh/yr)	Total Incremental Capacity Factor	Construction & Mitigation Total Cost ($M)	Construction & Mitigation Total Cost ($/kW)	PV of Total Costs ($M)	PV of Energy Benefits ($M)	PV of Capacity Benefits ($M)	PV of Total Benefits ($M)	NPV of Total Benefits ($M)	B/C Ratio
10%	3.6	1,236	4%	$6.7	$1,871	$9.7	$1.3	$1.6	$2.8	-$6.9	0.29
20%	7.2	2,248	4%	$11.9	$1,646	$16.9	$2.3	$3.0	$5.3	-$11.6	0.31
30%	10.8	3,104	3%	$16.5	$1,529	$23.4	$3.2	$4.3	$7.5	-$15.9	0.32
40%	14.4	3,864	3%	$20.9	$1,452	$29.5	$4.0	$5.5	$9.5	-$20.0	0.32
50%	18.0	4,594	3%	$25.1	$1,395	$35.3	$4.8	$6.7	$11.5	-$23.8	0.33



Summary of Capacity Increase Benefits and Costs
Lower Molina

Percent Capacity Increase	Capacity Increase (MW)	Average Incremental Energy (MWh/yr)	Total Incremental Capacity Factor	Construction & Mitigation Total Cost ($M)	Construction & Mitigation Total Cost ($/kW)	PV of Total Costs ($M)	PV of Energy Benefits ($M)	PV of Capacity Benefits ($M)	PV of Total Benefits ($M)	NPV of Total Benefits ($M)	B/C Ratio
10%	0.5	31	1%	$1.3	$2,754	$2.0	$0.0	$0.1	$0.2	-$1.8	0.08
20%	1.0	57	1%	$2.3	$2,402	$3.4	$0.1	$0.2	$0.3	-$3.1	0.09
30%	1.5	83	1%	$3.2	$2,220	$4.8	$0.1	$0.3	$0.5	-$4.3	0.09
40%	1.9	108	1%	$4.1	$2,102	$6.0	$0.1	$0.5	$0.6	-$5.4	0.10
50%	2.4	133	1%	$4.9	$2,014	$7.1	$0.2	$0.6	$0.7	-$6.4	0.10



Summary of Capacity Increase Benefits and Costs
Marys Lake

Percent Capacity Increase	Capacity Increase (MW)	Average Incremental Energy (MWh/yr)	Total Incremental Capacity Factor	Construction & Mitigation Total Cost ($M)	Construction & Mitigation Total Cost ($/kW)	PV of Total Costs ($M)	PV of Energy Benefits ($M)	PV of Capacity Benefits ($M)	PV of Total Benefits ($M)	NPV of Total Benefits ($M)	B/C Ratio
10%	0.8	0	0%	$2.0	$2,489	$3.0	$0.0	$0.2	$0.2	-$2.8	0.05
20%	1.6	0	0%	$3.5	$2,176	$5.2	$0.0	$0.3	$0.3	-$4.8	0.06
30%	2.4	0	0%	$4.9	$2,014	$7.1	$0.0	$0.5	$0.5	-$6.6	0.07
40%	3.2	0	0%	$6.2	$1,908	$9.0	$0.0	$0.6	$0.6	-$8.3	0.07
50%	4.1	0	0%	$7.4	$1,831	$10.7	$0.0	$0.8	$0.8	-$9.9	0.08



Summary of Capacity Increase Benefits and Costs
McPhee

Percent Capacity Increase	Capacity Increase (MW)	Average Incremental Energy (MWh/yr)	Total Incremental Capacity Factor	Construction & Mitigation Total Cost ($M)	Construction & Mitigation Total Cost ($/kW)	PV of Total Costs ($M)	PV of Energy Benefits ($M)	PV of Capacity Benefits ($M)	PV of Total Benefits ($M)	NPV of Total Benefits ($M)	B/C Ratio
10%	0.1	322	29%	$0.5	$3,627	$0.7	$0.5	$0.2	$0.7	$0.0	1.00
20%	0.3	539	24%	$0.8	$3,136	$1.2	$0.8	$0.4	$1.2	$0.0	0.98
30%	0.4	724	21%	$1.1	$2,887	$1.7	$1.0	$0.6	$1.6	-$0.1	0.96
40%	0.5	897	20%	$1.4	$2,724	$2.1	$1.3	$0.7	$2.0	-$0.1	0.95
50%	0.6	1,051	19%	$1.7	$2,606	$2.5	$1.5	$0.8	$2.3	-$0.2	0.94



Summary of Capacity Increase Benefits and Costs
Minidoka

Percent Capacity Increase	Capacity Increase (MW)	Average Incremental Energy (MWh/yr)	Total Incremental Capacity Factor	Construction & Mitigation Total Cost ($M)	Construction & Mitigation Total Cost ($/kW)	PV of Total Costs ($M)	PV of Energy Benefits ($M)	PV of Capacity Benefits ($M)	PV of Total Benefits ($M)	NPV of Total Benefits ($M)	B/C Ratio
10%	2.8	5,025	21%	$5.4	$1,965	$7.9	$5.6	$4.0	$9.5	$1.6	1.21
20%	5.5	8,523	18%	$9.6	$1,727	$13.7	$9.4	$6.9	$16.4	$2.6	1.19
30%	8.3	11,009	15%	$13.3	$1,604	$19.0	$12.2	$9.2	$21.4	$2.4	1.12
40%	11.1	13,040	13%	$16.9	$1,522	$23.9	$14.4	$11.1	$25.5	$1.6	1.07
50%	13.9	14,807	12%	$20.2	$1,462	$28.6	$16.4	$12.9	$29.3	$0.7	1.02



Summary of Capacity Increase Benefits and Costs
Morrow Point

Percent Capacity Increase	Capacity Increase (MW)	Average Incremental Energy (MWh/yr)	Total Incremental Capacity Factor	Construction & Mitigation Total Cost ($M)	Construction & Mitigation Total Cost ($/kW)	PV of Total Costs ($M)	PV of Energy Benefits ($M)	PV of Capacity Benefits ($M)	PV of Total Benefits ($M)	NPV of Total Benefits ($M)	B/C Ratio
10%	17.3	1,152	1%	$24.3	$1,404	$34.2	$1.6	$4.2	$5.9	-$28.4	0.17
20%	34.7	2,139	1%	$43.1	$1,242	$59.7	$3.0	$8.4	$11.4	-$48.3	0.19
30%	52.0	2,884	1%	$60.2	$1,157	$82.8	$4.1	$12.4	$16.4	-$66.3	0.20
40%	69.3	3,401	1%	$76.3	$1,101	$104.3	$4.8	$16.2	$21.0	-$83.4	0.20
50%	86.7	3,823	1%	$91.8	$1,059	$124.9	$5.4	$19.9	$25.3	-$99.6	0.20



Summary of Capacity Increase Benefits and Costs
Mount Elbert

Percent Capacity Increase	Capacity Increase (MW)	Average Incremental Energy (MWh/yr)	Total Incremental Capacity Factor	Construction & Mitigation Total Cost ($M)	Construction & Mitigation Total Cost ($/kW)	PV of Total Costs ($M)	PV of Energy Benefits ($M)	PV of Capacity Benefits ($M)	PV of Total Benefits ($M)	NPV of Total Benefits ($M)	B/C Ratio
10%	20.0	0	0%	$27.4	$1,369	$38.4	$0.0	$4.0	$4.0	-$34.4	0.10
20%	40.0	0	0%	$48.5	$1,211	$67.0	$0.0	$8.0	$8.0	-$59.0	0.12
30%	60.0	0	0%	$67.7	$1,129	$92.9	$0.0	$12.0	$12.0	-$80.9	0.13
40%	80.0	0	0%	$85.9	$1,074	$117.1	$0.0	$16.0	$16.0	-$101.1	0.14
50%	100.0	0	0%	$103.4	$1,034	$140.2	$0.0	$20.0	$20.0	-$120.3	0.14



Summary of Capacity Increase Benefits and Costs
New Melones

Percent Capacity Increase	Capacity Increase (MW)	Average Incremental Energy (MWh/yr)	Total Incremental Capacity Factor	Construction & Mitigation Total Cost ($M)	Construction & Mitigation Total Cost ($/kW)	PV of Total Costs ($M)	PV of Energy Benefits ($M)	PV of Capacity Benefits ($M)	PV of Total Benefits ($M)	NPV of Total Benefits ($M)	B/C Ratio
10%	38.2	0	0%	$46.6	$1,221	$64.6	$0.0	$7.6	$7.6	-$56.9	0.12
20%	76.4	0	0%	$82.7	$1,083	$112.8	$0.0	$15.3	$15.3	-$97.6	0.14
30%	114.6	0	0%	$115.8	$1,010	$156.6	$0.0	$22.9	$22.9	-$133.7	0.15
40%	152.8	0	0%	$147.0	$962	$197.6	$0.0	$30.5	$30.5	-$167.1	0.15
50%	191.0	0	0%	$176.9	$926	$236.7	$0.0	$38.1	$38.1	-$198.5	0.16



Summary of Capacity Increase Benefits and Costs
Nimbus

Percent Capacity Increase	Capacity Increase (MW)	Average Incremental Energy (MWh/yr)	Total Incremental Capacity Factor	Construction & Mitigation Total Cost ($M)	Construction & Mitigation Total Cost ($/kW)	PV of Total Costs ($M)	PV of Energy Benefits ($M)	PV of Capacity Benefits ($M)	PV of Total Benefits ($M)	NPV of Total Benefits ($M)	B/C Ratio
10%	1.4	2,664	23%	$3.0	$2,254	$4.5	$3.7	$2.1	$5.8	$1.3	1.30
20%	2.7	4,920	21%	$5.3	$1,975	$7.8	$6.9	$3.9	$10.8	$3.0	1.39
30%	4.1	6,734	19%	$7.4	$1,831	$10.7	$9.4	$5.4	$14.8	$4.1	1.39
40%	5.4	8,384	18%	$9.4	$1,736	$13.5	$11.7	$6.8	$18.5	$5.1	1.38
50%	6.8	9,857	17%	$11.2	$1,666	$16.1	$13.8	$8.1	$21.9	$5.8	1.36



Summary of Capacity Increase Benefits and Costs
ONeill

Percent Capacity Increase	Capacity Increase (MW)	Average Incremental Energy (MWh/yr)	Total Incremental Capacity Factor	Construction & Mitigation Total Cost ($M)	Construction & Mitigation Total Cost ($/kW)	PV of Total Costs ($M)	PV of Energy Benefits ($M)	PV of Capacity Benefits ($M)	PV of Total Benefits ($M)	NPV of Total Benefits ($M)	B/C Ratio
10%	2.5	155	1%	$5.0	$2,001	$7.3	$0.3	$0.6	$0.9	-$6.5	0.12
20%	5.0	158	0%	$8.9	$1,758	$12.7	$0.3	$1.1	$1.4	-$11.3	0.11
30%	7.6	158	0%	$12.3	$1,632	$17.6	$0.3	$1.6	$1.9	-$15.7	0.11
40%	10.1	158	0%	$15.6	$1,548	$22.2	$0.3	$2.1	$2.4	-$19.8	0.11
50%	12.6	158	0%	$18.7	$1,487	$26.5	$0.3	$2.6	$2.9	-$23.6	0.11



Summary of Capacity Increase Benefits and Costs
Palisades

Percent Capacity Increase	Capacity Increase (MW)	Average Incremental Energy (MWh/yr)	Total Incremental Capacity Factor	Construction & Mitigation Total Cost ($M)	Construction & Mitigation Total Cost ($/kW)	PV of Total Costs ($M)	PV of Energy Benefits ($M)	PV of Capacity Benefits ($M)	PV of Total Benefits ($M)	NPV of Total Benefits ($M)	B/C Ratio
10%	17.7	39,931	26%	$24.7	$1,400	$34.7	$44.1	$30.8	$75.0	$40.2	2.16
20%	35.3	73,362	24%	$43.7	$1,238	$60.6	$81.1	$57.2	$138.3	$77.7	2.28
30%	53.0	99,993	22%	$61.1	$1,153	$84.0	$110.5	$78.9	$189.5	$105.5	2.26
40%	70.6	118,090	19%	$77.5	$1,097	$105.9	$130.5	$94.8	$225.4	$119.4	2.13
50%	88.3	129,829	17%	$93.2	$1,056	$126.8	$143.5	$106.4	$249.9	$123.1	1.97



Summary of Capacity Increase Benefits and Costs
Parker

Percent Capacity Increase	Capacity Increase (MW)	Average Incremental Energy (MWh/yr)	Total Incremental Capacity Factor	Construction & Mitigation Total Cost ($M)	Construction & Mitigation Total Cost ($/kW)	PV of Total Costs ($M)	PV of Energy Benefits ($M)	PV of Capacity Benefits ($M)	PV of Total Benefits ($M)	NPV of Total Benefits ($M)	B/C Ratio
10%	12.0	8,289	8%	$18.0	$1,500	$25.5	$10.3	$8.1	$18.4	-$7.1	0.72
20%	24.0	15,049	7%	$31.8	$1,325	$44.4	$18.7	$15.1	$33.8	-$10.6	0.76
30%	36.0	19,454	6%	$44.4	$1,234	$61.6	$24.2	$20.5	$44.7	-$16.9	0.73
40%	48.0	20,113	5%	$56.3	$1,173	$77.6	$25.0	$23.3	$48.3	-$29.2	0.62
50%	60.0	19,365	4%	$67.7	$1,129	$92.9	$24.1	$25.2	$49.3	-$43.6	0.53



Summary of Capacity Increase Benefits and Costs
Pilot Butte

Percent Capacity Increase	Capacity Increase (MW)	Average Incremental Energy (MWh/yr)	Total Incremental Capacity Factor	Construction & Mitigation Total Cost ($M)	Construction & Mitigation Total Cost ($/kW)	PV of Total Costs ($M)	PV of Energy Benefits ($M)	PV of Capacity Benefits ($M)	PV of Total Benefits ($M)	NPV of Total Benefits ($M)	B/C Ratio
10%	0.2	342	24%	$0.6	$3,460	$0.8	$0.3	$0.3	$0.6	-$0.3	0.67
20%	0.3	679	24%	$1.0	$2,997	$1.4	$0.6	$0.5	$1.1	-$0.3	0.77
30%	0.5	1,021	24%	$1.3	$2,761	$2.0	$0.9	$0.8	$1.7	-$0.3	0.84
40%	0.6	1,368	24%	$1.7	$2,607	$2.5	$1.2	$1.1	$2.2	-$0.2	0.90
50%	0.8	1,732	25%	$2.0	$2,495	$3.0	$1.5	$1.3	$2.8	-$0.1	0.96



Summary of Capacity Increase Benefits and Costs
Pole Hill

Percent Capacity Increase	Capacity Increase (MW)	Average Incremental Energy (MWh/yr)	Total Incremental Capacity Factor	Construction & Mitigation Total Cost ($M)	Construction & Mitigation Total Cost ($/kW)	PV of Total Costs ($M)	PV of Energy Benefits ($M)	PV of Capacity Benefits ($M)	PV of Total Benefits ($M)	NPV of Total Benefits ($M)	B/C Ratio
10%	3.8	0	0%	$7.1	$1,850	$10.2	$0.0	$0.8	$0.8	-$9.5	0.07
20%	7.6	0	0%	$12.5	$1,628	$17.8	$0.0	$1.5	$1.5	-$16.3	0.09
30%	11.5	0	0%	$17.4	$1,513	$24.6	$0.0	$2.3	$2.3	-$22.3	0.09
40%	15.3	0	0%	$22.0	$1,436	$31.0	$0.0	$3.1	$3.1	-$27.9	0.10
50%	19.1	0	0%	$26.4	$1,380	$37.0	$0.0	$3.8	$3.8	-$33.2	0.10



Summary of Capacity Increase Benefits and Costs
Roza

Percent Capacity Increase	Capacity Increase (MW)	Average Incremental Energy (MWh/yr)	Total Incremental Capacity Factor	Construction & Mitigation Total Cost ($M)	Construction & Mitigation Total Cost ($/kW)	PV of Total Costs ($M)	PV of Energy Benefits ($M)	PV of Capacity Benefits ($M)	PV of Total Benefits ($M)	NPV of Total Benefits ($M)	B/C Ratio
10%	1.3	0	0%	$2.9	$2,272	$4.3	$0.0	$0.3	$0.3	-$4.1	0.06
20%	2.6	0	0%	$5.2	$1,991	$7.5	$0.0	$0.5	$0.5	-$7.0	0.07
30%	3.9	0	0%	$7.2	$1,845	$10.3	$0.0	$0.8	$0.8	-$9.6	0.07
40%	5.2	0	0%	$9.1	$1,749	$13.0	$0.0	$1.0	$1.0	-$12.0	0.08
50%	6.5	0	0%	$10.9	$1,679	$15.6	$0.0	$1.3	$1.3	-$14.3	0.08



Summary of Capacity Increase Benefits and Costs
San Luis

Percent Capacity Increase	Capacity Increase (MW)	Average Incremental Energy (MWh/yr)	Total Incremental Capacity Factor	Construction & Mitigation Total Cost ($M)	Construction & Mitigation Total Cost ($/kW)	PV of Total Costs ($M)	PV of Energy Benefits ($M)	PV of Capacity Benefits ($M)	PV of Total Benefits ($M)	NPV of Total Benefits ($M)	B/C Ratio
10%	42.4	33	0%	$50.8	$1,199	$70.2	$0.0	$8.5	$8.5	-$61.7	0.12
20%	84.8	33	0%	$90.2	$1,063	$122.8	$0.0	$17.0	$17.0	-$105.8	0.14
30%	127.2	33	0%	$126.2	$992	$170.3	$0.0	$25.4	$25.5	-$144.9	0.15
40%	169.6	33	0%	$160.3	$945	$215.0	$0.0	$33.9	$33.9	-$181.0	0.16
50%	212.0	33	0%	$193.0	$910	$257.5	$0.0	$42.3	$42.4	-$215.2	0.16



Summary of Capacity Increase Benefits and Costs
Seminoe

Percent Capacity Increase	Capacity Increase (MW)	Average Incremental Energy (MWh/yr)	Total Incremental Capacity Factor	Construction & Mitigation Total Cost ($M)	Construction & Mitigation Total Cost ($/kW)	PV of Total Costs ($M)	PV of Energy Benefits ($M)	PV of Capacity Benefits ($M)	PV of Total Benefits ($M)	NPV of Total Benefits ($M)	B/C Ratio
10%	5.2	1,174	3%	$9.1	$1,749	$13.0	$1.3	$1.8	$3.1	-$9.9	0.24
20%	10.4	2,222	2%	$15.9	$1,541	$22.6	$2.4	$3.6	$6.0	-$16.7	0.26
30%	15.5	3,123	2%	$22.2	$1,432	$31.3	$3.3	$5.2	$8.6	-$22.8	0.27
40%	20.7	3,788	2%	$28.2	$1,361	$39.5	$4.0	$6.7	$10.8	-$28.7	0.27
50%	25.9	4,224	2%	$33.8	$1,308	$47.2	$4.5	$8.1	$12.6	-$34.7	0.27



Summary of Capacity Increase Benefits and Costs
Shasta

Percent Capacity Increase	Capacity Increase (MW)	Average Incremental Energy (MWh/yr)	Total Incremental Capacity Factor	Construction & Mitigation Total Cost ($M)	Construction & Mitigation Total Cost ($/kW)	PV of Total Costs ($M)	PV of Energy Benefits ($M)	PV of Capacity Benefits ($M)	PV of Total Benefits ($M)	NPV of Total Benefits ($M)	B/C Ratio
10%	71.4	27,813	4%	$78.2	$1,095	$106.8	$49.8	$33.3	$83.1	-$23.8	0.78
20%	142.8	52,099	4%	$138.9	$973	$187.0	$93.3	$64.1	$157.4	-$29.7	0.84
30%	214.2	73,426	4%	$194.6	$909	$259.7	$131.4	$93.0	$224.4	-$35.3	0.86
40%	285.6	90,794	4%	$247.4	$866	$327.9	$162.5	$119.1	$281.6	-$46.3	0.86
50%	357.0	103,991	3%	$298.0	$835	$393.0	$186.1	$142.4	$328.5	-$64.5	0.84



Summary of Capacity Increase Benefits and Costs
Shoshone

Percent Capacity Increase	Capacity Increase (MW)	Average Incremental Energy (MWh/yr)	Total Incremental Capacity Factor	Construction & Mitigation Total Cost ($M)	Construction & Mitigation Total Cost ($/kW)	PV of Total Costs ($M)	PV of Energy Benefits ($M)	PV of Capacity Benefits ($M)	PV of Total Benefits ($M)	NPV of Total Benefits ($M)	B/C Ratio
10%	0.3	2,502	95%	$0.9	$3,037	$1.4	$2.6	$1.0	$3.6	$2.2	2.60
20%	0.6	4,980	95%	$1.6	$2,641	$2.4	$5.1	$1.9	$7.1	$4.7	3.00
30%	0.9	7,343	93%	$2.2	$2,438	$3.2	$7.6	$2.9	$10.5	$7.2	3.22
40%	1.2	9,653	92%	$2.8	$2,305	$4.1	$10.0	$3.8	$13.8	$9.7	3.38
50%	1.5	11,913	91%	$3.3	$2,208	$4.9	$12.3	$4.7	$17.0	$12.2	3.50



Summary of Capacity Increase Benefits and Costs
Spirit Mountain

Percent Capacity Increase	Capacity Increase (MW)	Average Incremental Energy (MWh/yr)	Total Incremental Capacity Factor	Construction & Mitigation Total Cost ($M)	Construction & Mitigation Total Cost ($/kW)	PV of Total Costs ($M)	PV of Energy Benefits ($M)	PV of Capacity Benefits ($M)	PV of Total Benefits ($M)	NPV of Total Benefits ($M)	B/C Ratio
10%	0.5	0	0%	$1.3	$2,797	$1.9	$0.0	$0.1	$0.1	-$1.8	0.05
20%	0.9	0	0%	$2.2	$2,438	$3.2	$0.0	$0.2	$0.2	-$3.1	0.06
30%	1.4	0	0%	$3.0	$2,254	$4.5	$0.0	$0.3	$0.3	-$4.2	0.06
40%	1.8	0	0%	$3.8	$2,133	$5.6	$0.0	$0.4	$0.4	-$5.3	0.06
50%	2.3	0	0%	$4.6	$2,044	$6.7	$0.0	$0.4	$0.4	-$6.3	0.07



Summary of Capacity Increase Benefits and Costs
Spring Creek

Percent Capacity Increase	Capacity Increase (MW)	Average Incremental Energy (MWh/yr)	Total Incremental Capacity Factor	Construction & Mitigation Total Cost ($M)	Construction & Mitigation Total Cost ($/kW)	PV of Total Costs ($M)	PV of Energy Benefits ($M)	PV of Capacity Benefits ($M)	PV of Total Benefits ($M)	NPV of Total Benefits ($M)	B/C Ratio
10%	18.0	1,499	1%	$25.1	$1,395	$35.3	$2.7	$4.6	$7.3	-$28.0	0.21
20%	36.0	2,260	1%	$44.4	$1,234	$61.6	$4.0	$8.7	$12.8	-$48.8	0.21
30%	54.0	2,783	1%	$62.1	$1,150	$85.3	$5.0	$12.7	$17.7	-$67.6	0.21
40%	72.0	3,173	1%	$78.8	$1,094	$107.6	$5.7	$16.5	$22.2	-$85.4	0.21
50%	90.0	3,450	0%	$94.7	$1,053	$128.8	$6.2	$20.3	$26.5	-$102.3	0.21



Summary of Capacity Increase Benefits and Costs
Stampede

Percent Capacity Increase	Capacity Increase (MW)	Average Incremental Energy (MWh/yr)	Total Incremental Capacity Factor	Construction & Mitigation Total Cost ($M)	Construction & Mitigation Total Cost ($/kW)	PV of Total Costs ($M)	PV of Energy Benefits ($M)	PV of Capacity Benefits ($M)	PV of Total Benefits ($M)	NPV of Total Benefits ($M)	B/C Ratio
10%	0.4	568	18%	$1.1	$2,918	$1.6	$0.8	$0.5	$1.3	-$0.3	0.79
20%	0.7	1,050	16%	$1.9	$2,540	$2.7	$1.5	$0.9	$2.3	-$0.4	0.85
30%	1.1	1,449	15%	$2.6	$2,347	$3.8	$2.0	$1.2	$3.2	-$0.6	0.85
40%	1.5	1,801	14%	$3.2	$2,220	$4.8	$2.5	$1.5	$4.0	-$0.7	0.85
50%	1.8	2,138	13%	$3.9	$2,127	$5.7	$3.0	$1.8	$4.8	-$0.9	0.85



Summary of Capacity Increase Benefits and Costs
Towaoc

Percent Capacity Increase	Capacity Increase (MW)	Average Incremental Energy (MWh/yr)	Total Incremental Capacity Factor	Construction & Mitigation Total Cost ($M)	Construction & Mitigation Total Cost ($/kW)	PV of Total Costs ($M)	PV of Energy Benefits ($M)	PV of Capacity Benefits ($M)	PV of Total Benefits ($M)	NPV of Total Benefits ($M)	B/C Ratio
10%	1.1	797	8%	$2.7	$2,325	$3.9	$0.9	$0.8	$1.6	-$2.3	0.41
20%	2.3	1,300	6%	$4.7	$2,036	$6.8	$1.4	$1.3	$2.7	-$4.1	0.40
30%	3.4	1,715	6%	$6.5	$1,886	$9.4	$1.8	$1.9	$3.7	-$5.7	0.39
40%	4.6	1,922	5%	$8.2	$1,788	$11.8	$2.1	$2.2	$4.3	-$7.5	0.36
50%	5.7	1,925	4%	$9.9	$1,716	$14.2	$2.1	$2.5	$4.5	-$9.6	0.32



Summary of Capacity Increase Benefits and Costs
Trinity

Percent Capacity Increase	Capacity Increase (MW)	Average Incremental Energy (MWh/yr)	Total Incremental Capacity Factor	Construction & Mitigation Total Cost ($M)	Construction & Mitigation Total Cost ($/kW)	PV of Total Costs ($M)	PV of Energy Benefits ($M)	PV of Capacity Benefits ($M)	PV of Total Benefits ($M)	NPV of Total Benefits ($M)	B/C Ratio
10%	14.0	4,999	4%	$20.4	$1,459	$28.8	$8.9	$6.2	$15.2	-$13.7	0.53
20%	28.0	9,229	4%	$36.1	$1,290	$50.3	$16.5	$11.9	$28.4	-$21.9	0.57
30%	42.0	12,066	3%	$50.4	$1,201	$69.7	$21.6	$16.6	$38.2	-$31.5	0.55
40%	56.0	14,002	3%	$64.0	$1,142	$87.8	$25.1	$20.8	$45.8	-$42.0	0.52
50%	70.0	15,384	3%	$76.9	$1,099	$105.2	$27.5	$24.5	$52.0	-$53.1	0.49



Summary of Capacity Increase Benefits and Costs
Upper Molina

Percent Capacity Increase	Capacity Increase (MW)	Average Incremental Energy (MWh/yr)	Total Incremental Capacity Factor	Construction & Mitigation Total Cost ($M)	Construction & Mitigation Total Cost ($/kW)	PV of Total Costs ($M)	PV of Energy Benefits ($M)	PV of Capacity Benefits ($M)	PV of Total Benefits ($M)	NPV of Total Benefits ($M)	B/C Ratio
10%	0.9	8	0%	$2.1	$2,458	$3.1	$0.0	$0.2	$0.2	-$3.0	0.06
20%	1.7	8	0%	$3.7	$2,149	$5.4	$0.0	$0.4	$0.4	-$5.1	0.07
30%	2.6	8	0%	$5.2	$1,990	$7.5	$0.0	$0.5	$0.5	-$7.0	0.07
40%	3.5	8	0%	$6.5	$1,885	$9.4	$0.0	$0.7	$0.7	-$8.7	0.07
50%	4.3	8	0%	$7.8	$1,809	$11.3	$0.0	$0.9	$0.9	-$10.4	0.08



Summary of Capacity Increase Benefits and Costs
Yellowtail

Percent Capacity Increase	Capacity Increase (MW)	Average Incremental Energy (MWh/yr)	Total Incremental Capacity Factor	Construction & Mitigation Total Cost ($M)	Construction & Mitigation Total Cost ($/kW)	PV of Total Costs ($M)	PV of Energy Benefits ($M)	PV of Capacity Benefits ($M)	PV of Total Benefits ($M)	NPV of Total Benefits ($M)	B/C Ratio
10%	25.0	3,458	2%	$32.9	$1,316	$45.9	$3.7	$7.4	$11.1	-$34.8	0.24
20%	50.0	6,327	1%	$58.3	$1,165	$80.2	$6.8	$14.3	$21.1	-$59.1	0.26
30%	75.0	8,526	1%	$81.5	$1,086	$111.2	$9.2	$20.8	$30.0	-$81.2	0.27
40%	100.0	10,049	1%	$103.4	$1,034	$140.2	$10.8	$26.8	$37.6	-$102.6	0.27
50%	125.0	11,286	1%	$124.4	$995	$167.9	$12.1	$32.7	$44.8	-$123.1	0.27



This page left blank intentionally.

U.S. Department of the Interior
Bureau of Reclamation
Denver, Colorado

MWH

BUILDING A BETTER WORLD

RECLAMATION

Managing Water in the West

Bureau of Reclamation Renewable Energy Update

Fiscal Year 2016, Q1

U.S. Department of the Interior
Bureau of Reclamation

January 2016

Contents

Page

Executive Summary

The Bureau of Reclamation Renewable Energy Update identifies federal and non-federal renewable energy projects currently online or in development on Reclamation land, facilities, and water bodies and highlights current Reclamation renewable activities. The update provides Reclamation-wide and regional summaries, renewable energy portfolios, and project updates as well as a listing of WaterSMART Grant projects that feature a renewable energy component.

The quarterly update is a compilation of monthly updates submitted by regional offices, with input received from area offices. Reclamation personnel, including Daniel Vallejo, Rick Clayton, Robert Ross, Dale Lentz, and James Stauffer were instrumental in developing this document.

Renewable Activities

Advanced Hydropower Technology Development Projects

A 2010 Memorandum of Understanding (MOU) for Hydropower action item, the Departments of Energy and Interior awarded approximately $17 million in 2011 to 16 projects in order to demonstrate innovative hydropower technologies. Two of the three projects sited on Reclamation infrastructure were brought online in 2015.

The Mile 45 project, developed by Earth by Design on the Reclamation North Unit Main Canal (Oregon), features low-head hydropower technology. The project was acquired by Apple in 2013 and was brought online May 15, 2015.

The Monroe Drop project, developed by Natel Energy also on the Reclamation North Unit Main Canal, demonstrates a modular Schneider Linear hydroEngine. The project was also acquired by Apple in 2014 and was brought online October 29, 2015.

The South Canal, Drop 2 project, developed by Percheron Power, in partnership with the Uncompahgre Valley Water Users Association on the Reclamation South Canal (Colorado) demonstrates an Archimedes hydrodynamic screw system. The project is in development and has received a Lease of Power Privilege (LOPP) Contract.

Reclamation Renewable Energy Summary

Online Hydropower Facilities	GP		LC		MP		PN		UC		USBR	
	#	MW[1]	#	MW	#	MW	#	MW	#	MW	#	MW
Reserved Facilities	21	1004[2]	3	2454	10	1910	10	7537	9	1816	53	14721
Transferred Facilities[3]	0	0	10	297	3	452	0	0	10	41	23	790
Other Plants on USBR Facilities	0	0	7	85	0	0	0	0	0	0	7	85
FERC Facilities[4]	7	29	0	0	13	60	27	326	5	50	52	465
LOPP Facilities[5]	1	3	0	0	1	1	0	0	9	38	11	42
Total	**29**	**1036**	**20**	**2836**	**27**	**2423**	**37**	**7863**	**33**	**1945**	**146**	**16103**

In Development FERC Facilities	GP		LC		MP		PN		UC		USBR	
	#	MW	#	MW	#	MW	#	MW	#	MW	#	MW
Licenses	1	15	0	0	2	8	0	0	0	0	3	23
Exemptions	1	1	0	0	0	0	4	2	0	0	5	3
Preliminary Permits (C)[6]	4	8	0	0	0	0	10	27	0	0	14	35
Preliminary Permits (PS)[7]	3	2132	4	3645	1	1250	1	1000	2	800	11	8827
Total	**9**	**2156**	**4**	**3645**	**3**	**1258**	**15**	**1029**	**2**	**800**	**33**	**8888**

In Development LOPP Facilities	GP		LC		MP		PN		UC		USBR	
	#	MW	#	MW	#	MW	#	MW	#	MW	#	MW
Contracts	1	1	0	0	0	0	0	0	2	3	3	4
Preliminary Leases	3	21	0	0	0	0	0	0	1	8	4	29
Posted Solicitations	0	0	0	0	0	0	0	0	1	0.1	1	0.1
Requests for Development (C)	3	3	2	3	2	0.4	0	0	2	13	9	19
Requests for Development (PS)	0	0	0	0	0	0	1	400	0	0	1	400
Total	**7**	**25**	**2**	**3**	**2**	**0.4**	**1**	**400**	**6**	**24**	**18**	**452**

[1] Megawatt (MW).
[2] Flatiron (G1and G2) capacity has been revised.
[3] Power from five of the 23 plants is marketed by the Western Area Power Administration (Western): Deer Creek, Towaoc, McPhee, O'Neill, and San Luis.
[4] Non-federal hydropower facilities developed on Reclamation infrastructure, licensed by the Federal Energy Regulatory Commission (FERC).
[5] Non-federal hydropower facilities developed on Reclamation infrastructure, authorized through a LOPP Contract. Reclamation holds title to the Grand Valley Powerplant LOPP.
[6] Conventional hydropower facilities.
[7] Pump storage hydropower facilities.

In Progress Capital Improvements	GP	LC	MP	PN	UC	USBR
Generator Rewinds	1	0	1	0	1	3[8]
Turbine Replacements	0	0	1	2	0	3[9]
Total	**1**	**0**	**2**	**2**	**1**	**6**

Online Solar Facilities	Region	State	MW
Alamosa	UC	New Mexico	.01
Grand Coulee Warehouse	PN	Washington	.005
Boulder City Regional Office Building	LC	Nevada	.276
Boulder City Regional Office Building (Parking)	LC	Nevada	.006
Hoover Spillway House Renovation	LC	Nevada	.048
River Mountains	LC	Nevada	14
Total			**14.35**

In Development Solar Facilities	Region	State	MW
First Solar	LC	Nevada	50
San Luis Facility	MP	California	26
Blythe Office	LC	California	0.02
Total			**76**

In Development Wind Facilities	Region	State	MW
Mohave County Wind Farm	LC	Arizona	500
Total			**500**

Hydropower Pilot Projects	Region	State	MW
Hydrokinetic Installation on Roza Canal (Instream Energy)	PN	Washington	.01
Low-head Technology Installation on Monroe Drop[10]	PN	Oregon	.3
Low-head Technology Installation on North Unit Irrigation Canal, Mile 45[11]	PN	Oregon	5
Hydrodynamic Screw Technology Installation on South Canal, Drop 2[12]	UC	Colorado	1
Total			**6**

[8] Rewinds are in progress at Yellowtail (G3), Folsom (G3), and Glen Canyon (G5). Rewind work was completed at Spring Creek (G2) October 2015.
[9] Turbine replacements are in progress at Trinity (G1), Palisades (G2), and Minidoka (G9). A turbine replacement project was completed at Glen Canyon (G2) November 2015.
[10] Monroe Drop began commercial operation October 2015 and is included in the Online FERC Facilities statistic.
[11] Mile 45 began commercial operation May 2015 and is included in the Online FERC Facilities statistic.
[12] South Canal, Drop 2 has a LOPP Contract and is included in the LOPP Contracts statistic.

WaterSMART

Through WaterSMART Grants (formerly Challenge Grants), Reclamation provides 50/50 cost share funding to irrigation and water districts, tribes, states, and other entities with water or power delivery authority. Projects should seek to conserve and use water more efficiently, increase the use of renewable energy, protect endangered species, or facilitate water markets. Projects are selected through a competitive process and the focus is on projects that can be completed within 24 to 36 months that will help sustainable water supplies in the Western United States. For additional information see the WaterSMART Web site.

WaterSMART Updates

The FY 2016 WaterSMART Water and Energy Efficiency Grant (WEEG) Funding Opportunity Announcement (FOA) was posted November 3, 2015. The closing date for applications is January 20, 2016.

WaterSMART Summary

All active, FY 2011-2015 WaterSMART WEEG projects that feature a renewable energy component are listed in the table below. Full project summaries are available on the WaterSMART Web site.

	Fiscal Year	Recipient and *Project Title*	Renewable Component Status
1	2011	Three Sisters Irrigation District *Main Canal Pipeline Penstock Hydro Project*	Online (8/2014)
2	2011	Pershing County Water Conservation District *Humboldt River Automation Metering and Hydropower Project*	In development, FERC License
3	2011	Boise Project Board of Control *Hydroelectric Project*	Online (4/2013)
4	2012	Consolidated Irrigation Company *Improve Irrigation Efficiencies and Provide Sustainability*	Online (9/2015)
5	2013	Cub River Irrigation Company *Middle Ditch Water Conservation & Renewable Energy Piping Project*	In development
6	2014	Nevada Irrigation District *Hydroelectric Project*	In development
7	2014	Rosedale-Rio Bravo Water Storage District *Water Conservation, Energy Efficiency, and Solar Power Project*	In development
8	2014	Uncompahgre Valley Water Users Association *Shavano Falls Hydropower Development*	Online (5/2015)

	Fiscal Year	Recipient and *Project Title*	Renewable Component Status
9	2014	Oxford Reservoir and Irrigation Company *Innovative Energy Production and Irrigation Efficiencies*	In development
10	2014	Elephant Butte Irrigation District *Water-Habitat-Energy-Nexus*	In development
11	2014	Davis and Weber Counties Canal Company *Main Piping and Small Hydro Project*	In development
12	2014	Fremont Irrigation Company *Extension to Improve Irrigation Efficiency and Provide Sustainability*	In development
13	2014	Richmond Irrigation District *Upper High Creek Canal Enclosure and Hydropower Development Project*	In development
14	2015	Bella Vista Water District *Renewable Energy, Advanced Metering Infrastructure, and Water Conservation Improvements*	In development
15	2015	Uncompahgre Valley Water Users Association *South Canal Drop 4 Hydropower Development*	Online (6/2015)
16	2015	Navajo Agricultural Product Industry *Create and Implement a Comprehensive Water Management Web-Based Tool for Ordering and Delivering Irrigation Water*	In development
17	2015	Three Sisters Irrigation District *Main Canal Pipeline and Micro Hydro Generation Project*	In development
18	2015	Cameron County Irrigation District No. 6 *Conversion of the Saldana Canal into Pipeline, Elimination of the Saldana Pump by Construction of Aerial Crossing and Solar Powered Second Lift Pump*	In development
19	2015	Santa Cruz Irrigation District No. 15 *Shotcrete Lining of the N-Canal, Installation of a VFD at Pump-15, and Wind Powered Alternative at Pump 15*	In development
20	2015	Davis and Weber Counties Canal Company *Canal Piping and Hydro Project*	In development
21	2015	Davis and Weber Counties Canal Company *Secondary Water Irrigation Metering and Hydro Project*	In development
22	2015	Marion Upper Ditch Company *Main Canal Pipeline and Micro Hydro Generation Project*	In development

Great Plains Renewable Energy Updates

FERC Projects

Project: Clark Canyon Dam
Developer: Clark Canyon Hydro, LLC
Status: Preliminary Permit (P-14677)

On December 4, 2015, FERC filed the "Notice of Application Tendered for Filing with the Commission, Soliciting Additional Study Requests, Intent to Waive Parts of the Pre-Filing Three Stage Consultation Process, and Intent to Waive Scoping." Per the filing, the Clark Canyon Dam Environmental Assessment will be available for review by May 1, 2016.

Reclamation is currently conducting design review with Clark Canyon Hydro, LLC.

Concurrently, Senate Bill 1103, which, in part, reinstates the terminated Clark Canyon Dam FERC License (P-12429), was reported to the Senate Committee on Energy and Natural Resources on September 9, 2015.

LOPP Projects

Project: Granby Dam
Developer: Northern Water Conservancy District
Status: LOPP Contract

The powerhouse foundation, building structure, bifurcation, and penstock installation are complete. Equipment installation, including two horizontal turbine-generator units, will begin spring of 2016 and continue through June of 2016.

Project: Pueblo Dam
Developer: Southeastern Colorado Water Conservancy District, Colorado Springs Utilities, and Board of Water Works of Pueblo, Colorado
Status: Preliminary Lease

The draft Pueblo Dam LOPP Environmental Assessment was released for public comment December 22, 2015. Public comments are due January 15, 2016. The Assessment can be accessed on the Eastern Colorado Area Office website.

Project: Yellowtail Afterbay

Developer: Crow Tribe
Status: Preliminary Lease

Project Management Team meetings were held in November and December. The next meeting is scheduled for January 28, 2016.

Based on a 25% project design, National Environmental Policy Act (NEPA) compliance is expected to take eight months (assuming limited complications and environmental impacts). At this time, the Tribe has not identified a power customer or powerline route.

Western is currently evaluating what impacts (if any) the Yellowtail Afterbay project will pose on Reclamation Yellowtail facility operations. This evaluation will help inform Yellowtail Afterbay operating criteria, to be developed by Reclamation, Western, and the Tribe.

Project: Helena Valley Pumping Plant
Developer: Helena Valley Irrigation District
Status: Preliminary Lease

The final Helena Valley Pumping Plant LOPP Environmental Assessment was published on December 11, 2015 and a Finding of No Significant Impact (FONSI) was signed by the Montana Area Office Manager on December 16, 2015. The Assessment and FONSI can be accessed on the Montana Area Office website.

A draft LOPP has been transmitted to the District for review.

Lower Colorado Renewable Energy Updates

Solar Projects

Project: River Mountains
Developer: Southern Nevada Water Authority and SunEdison
Status: Online

The 14 MW array began generating power in January. Generation will help offset the Authority's River Mountains Water Treatment Facility energy demand.

Mid-Pacific Renewable Energy Updates

Solar Projects

Project: San Luis Facility
Developer: San Luis Renewables, LLC
Status: In Development

The draft San Luis Solar Project Environmental Assessment and FONSI were released for public comment on December 14, 2015. Public comments are due January 15, 2016. The Assessment and FONSI can be accessed on the Mid Pacific Region website.

Per the draft Assessment and FONSI, proposed project capacity is 26 MW.

Pacific Northwest Renewable Energy Updates

FERC Projects

Project: Monroe Drop
Developer: Apple
Status: Online (P-14430)

Monroe Drop began commercial operation on October 29, 2015.

Project received funding through the 2011 Advanced Hydropower Technology Development FOA. The FOA (jointly funded by Reclamation and the Department of Energy through the 2010 Hydropower MOU) awarded funding to demonstrate new hydropower technologies.

Located on the North Unit Main Canal (12.5 miles south of Madras, Oregon), the Monroe Drop project features a modular Schneider Linear hydroEngine, developed by Natel Energy.

Upper Colorado Renewable Energy Updates

LOPP Projects

Project: South Canal (Drop 2)
Developer: Uncompahgre Valley Water Users Association
Status: LOPP Contract

The Lessee has requested written Reclamation approval to commence construction. Reclamation has evaluated and rejected the request, as not all construction authorization requirements (per the Lease Contract) have been satisfied. Project is currently on hold while the Lessee and Percheron Power secure additional funding.

Project: South Canal (Drop 5)
Developer: Uncompahgre Valley Water Users Association
Status: LOPP Contract

The South Canal (Drop 5) LOPP Environmental Assessment and FONSI are complete and the LOPP Contract was executed on November 5, 2015. Construction was authorized on November 17, 2015 with expected completion in late spring 2016.

The Assessment and FONSI can be accessed on the Upper Colorado Environmental Assessments website.

Project: San Juan-Chama Project
Developer: Albuquerque Bernalillo County Water Utility Authority
Status: Posted Solicitation

Currently, the Authority is coordinating project funding and logistics.

Appendix – Regional Renewable Energy Portfolios

Great Plains Renewable Portfolio

State	Project Status	Project Name	FERC ID	Area Office	Operating Entity	Hydropower Type	Capacity (kW)	Project Initiation Date	Preliminary Permit or Lease Date	Exemption or CE Date	License or Lease Date	Online Date
RECLAMATION OWNED AND OPERATED												
WY	Online	Alcova		Wyoming	USBR	Conventional	41,400.00					1955
CO	Online	Big Thompson		Eastern Colorado	USBR	Conventional	4,500.00					1959
WY	Online	Boysen		Wyoming	USBR	Conventional	15,000.00					1952
WY	Online	Buffalo Bill		Wyoming	USBR	Conventional	18,000.00					1992
MT	Online	Canyon Ferry		Montana	USBR	Conventional	50,001.00					1953
CO	Online	Estes		Eastern Colorado	USBR	Conventional	45,000.00					1950
CO	Online	Flatiron (Unit 1, 2, 3)		Eastern Colorado	USBR	Conventional/Pump Storage	94,500.00					1954
WY	Online	Fremont Canyon		Wyoming	USBR	Conventional	66,800.00					1960
WY	Online	Glendo		Wyoming	USBR	Conventional	38,000.00					1959
CO	Online	Green Mountain		Eastern Colorado	USBR	Conventional	26,000.00					1943
WY	Online	Guernsey		Wyoming	USBR	Conventional	6,400.00					1928
WY	Online	Heart Mountain		Wyoming	USBR	Conventional	5,000.00					1948
WY	Online	Kortes		Wyoming	USBR	Conventional	36,000.00					1950
CO	Online	Marys Lake		Eastern Colorado	USBR	Conventional	8,100.00					1951
CO	Online	Mt. Elbert PS		Eastern Colorado	USBR	Pump Storage	200,000.00					1981
WY	Online	Pilot Butte		Wyoming	USBR	Conventional	1,600.00					1929
CO	Online	Pole Hill		Eastern Colorado	USBR	Conventional	38,238.00					1954
WY	Online	Seminoe		Wyoming	USBR	Conventional	51,750.00					1939
WY	Online	Shoshone		Wyoming	USBR	Conventional	3,000.00					1992
WY	Online	Spirit Mountain		Wyoming	USBR	Conventional	4,500.00					1994
MT	Online	Yellowtail		Montana	USBR	Conventional	250,000.00					1966
FEDERAL ENERGY REGULATORY COMMISSION PROJECTS												
WY	Online	Garland Canal	3031	Wyoming	Shoshone I.D.	Conventional	2,610.00				10/9/1981	1980
MT	Online	Lower Turnbull Drop	12597	Montana	Turnbull Hydro, LLC	Conventional	7,700.00	6/21/2005			7/28/2006	6/22/2011
OK	Online	McGee Creek Dam	8492	Oklahoma Texas	McGee Creek Authority	Conventional	175.00	7/26/1984	3/14/1985		6/23/1986	1980
CO	Online	Ruedi Dam	3603	Western Colorado	City of Aspen	Conventional	3,200.00				9/8/1983	1980
CO	Online	Sugarloaf Dam	3819	Eastern Colorado	STS Hydropower Ltd.	Conventional	2,800.00				11/18/1982	1980
MO	Online	Tiber Dam	3574	Montana	Tiber Montana LLC	Conventional	7,500.00		11/20/1990		6/2/1997	6/14/2004
MT	Online	Upper Turnbull Drop	12598	Montana	Turnbull Hydro, LLC	Conventional	5,300.00	6/24/2005			7/28/2006	6/24/2011
MT	License	Gibson Dam	12478	Montana	Gibson Dam Hydroelectric Company, LLC.	Conventional	15,000.00	10/28/2003	4/20/2004		1/12/2012	
MT	Exemption	Mary Taylor Drop	14294	Montana	Turnbull Hydro, LLC	Conventional	890.00	9/23/2011		6/28/2012		
WY	Preliminary	Deer Creek Drop	14370	Wyoming	Willwood Irrigation District	Conventional	780.00	3/6/2012	9/19/2012			
NE	Preliminary	Medicine Creek Dam	13648	Nebraska-Kansas	Twin Valleys Public Power District	Conventional	800.00	12/30/2009	6/15/2010			
WY	Preliminary	Willwood Diversion Dam	13423	Wyoming	Willwood Irrigation District	Conventional	2,000.00	4/6/2009	7/7/2009			
MT	Preliminary	Clark Canyon Dam	14677	Montana	Clark Canyon Hydro, LLC	Conventional	4,700.00	4/20/2015	9/18/2015			
WY	Preliminary	Black Canyon Pumped Storage Project	14087	Wyoming	Black Canyon Hydro, LLC	Pump Storage	700,000.00	1/25/2011	7/15/2011			
WY	Preliminary	Medicine Bow Pumped Storage	13836	Wyoming	Medicine Bow Hydro, LLC	Pump Storage	400,000.00	8/30/2010	12/3/2010			
MT	Preliminary	Square Butte Pumped Storage	13349	Montana	Square Butte Hydro LLC	Pump Storage	1,032,000.00	12/23/2008	7/23/2012			
LEASE OF POWER PRIVILEGE PROJECTS												
CO	Online	Carter Lake Outlet		Eastern Colorado	Northern Water Conservancy District	Conventional	2,600.00	5/7/2009	11/24/2009		4/22/2011	5/18/2012
CO	Contract	Granby Dam	LP11-3	Eastern Colorado	Northern Water Conservancy District	Conventional	700.00	4/20/2011	6/26/2012		3/31/2015	
CO	Preliminary	Pueblo Dam	LP11-4	Eastern Colorado	Southeastern Colorado Water Conservancy District, Colorado Springs Utilities, and Board of Water Works of Pueblo, Colorado	Conventional	7,010.00	4/20/2011	2/27/2012			
MT	Preliminary	Yellowtail Afterbay		Montana	Crow Tribe	Conventional	9,000.00	1/11/2012	3/6/2015			
MT	Preliminary	Helena Valley Pumping Plant		Montana	Helena Valley Irrigation District	Conventional	4,800.00	9/13/2013	8/20/2015			
MT	Request for Development	A Drop		Montana	Turnbull Hydro, LLC	Conventional	1,000.00	6/1/2014				

Great Plains Renewable Portfolio

State	Project Status	Project Name	FERC ID	Area Office	Operating Entity	Hydropower Type	Capacity (kW)	Project Initiation Date	Preliminary Permit or Lease Date	Exemption or CE Date	License or Lease Date	Online Date
MT	Request for Development	Johnson Drop		Montana	Turnbull Hydro, LLC	Conventional	700.00	6/1/2014				
MT	Request for Development	Woods Drop		Montana	Turnbull Hydro, LLC	Conventional	900.00	6/1/2014				

Lower Colorado Renewable Portfolio

State	Project Status	Project Name	FERC ID	Area Office	Operating Entity	Hydropower Type	Capacity (kW)	Project Initiation Date	Preliminary Permit or Lease Date	Exemption or CE Date	License or Lease Date	Online Date
RECLAMATION OWNED AND OPERATED												
AZ	Online	Davis		Yuma	USBR	Conventional	255,000.00					1951
AZ/NV	Online	Hoover		Lower Colorado	USBR	Conventional	2,078,800.00					1936
AZ	Online	Parker		Yuma	USBR	Conventional	120,000.00					1943
RECLAMATION OWNED AND OPERATED BY OTHERS												
AZ	Online	Arizona Falls Powerplant		Phoenix	Salt River Valley Water User's Association	Conventional	750.00					1902
AZ	Online	Cross Cut Powerplant		Phoenix	Salt River Valley Water User's Association	Conventional	3,000.00					1914
AZ	Online	Horse Mesa Powerplant		Phoenix	Salt River Valley Water User's Association	Conventional/Pump Storage	129,000.00					1927
AZ	Online	Mormon Flat Powerplant		Phoenix	Salt River Valley Water User's Association	Conventional/Pump Storage	60,000.00					1926
AZ	Online	New Waddell Pump/Generating Plant		Phoenix	Central Arizona Water Conservation District	Pump Storage	45,000.00					1993
CA	Online	Senator Wash Pump/Generating Plant		Yuma	Imperial Irrigation District	Pump Storage	7,200.00					1966
AZ	Online	Siphon Drop Powerplant		Yuma	Yuma County Water User's Association	Conventional	4,600.00					1926
AZ	Online	South Consolidated Powerplant		Phoenix	Salt River Valley Water User's Association	Conventional	1,400.00					1912
AZ	Online	Stewart Mountain Powerplant		Phoenix	Salt River Valley Water User's Association	Conventional	10,400.00					1930
AZ	Online	Theodore Roosevelt Powerplant		Phoenix	Salt River Valley Water User's Association	Conventional	36,020.00					1973
OTHER PLANTS ON RECLAMATION FACILITIES												
AZ	Online	C.C. Craigin Dam and Powerplant	2304	Phoenix	Salt River Project	Conventional	3,000.00					1965
AZ	Online	Drop Five Powerplant		Yuma	Imperial Irrigation District	Conventional	4,000.00					1982
AZ	Online	Drop Four Powerplant		Yuma	Imperial Irrigation District	Conventional	19,600.00					1941
AZ	Online	Drop One Powerplant		Yuma	Imperial Irrigation District	Conventional	6,000.00					1984
AZ	Online	Drop Three Powerplant		Yuma	Imperial Irrigation District	Conventional	9,800.00					1941
AZ	Online	Drop Two Powerplant		Yuma	Imperial Irrigation District	Conventional	10,000.00					1953
AZ	Online	Pilot Knob Powerplant		Yuma	Imperial Irrigation District	Conventional	33,000.00					1961
FEDERAL ENERGY REGULATORY COMMISSION PROJECTS												
NV	Preliminary	Blue Diamond Pumped Storage Project	14344	Regional Office	The International Consortium of Energy Managers	Pump Storage	450,000.00	1/6/2012	7/11/2012			
NV	Preliminary	Eldorado Pumped Storage Project	13861	Regional Office	Eldorado Pumped Storage, LLC	Pump Storage	400,000.00	10/13/2010	2/3/2012			
AZ	Preliminary	Longview Pumped Storage Project	14341	Regional Office	Longview Energy Exchange, LLC	Pump Storage	2,000,000.00	1/3/2012	5/4/2012			
AZ	Preliminary	Verde Pumped Storage Project	14061	Phoenix	Arizona Independent Power	Pump Storage	795,000.00	1/12/2011	8/15/2011			
LEASE OF POWER PRIVILEGE PROJECTS												
AZ	Request for Development	Laguna Dam		Yuma		Conventional	2,200.00	1/28/2013				
AZ	Request for Development	Santa Rosa Canal		Phoenix	Maricopa-Stanfield Irrigation and Drainage District	Conventional	375.00	9/4/2012				
SOLAR PROJECTS												
NV	Online	Boulder City Regional Office Building		Regional Office	Boulder City Regional Office Building		276.36					
NV	Online	Boulder City Regional Office Building (parking)		Regional Office	Boulder City Regional Office Building		5.97					
NV	Online	Hoover Spillway House Renovation		Regional Office	Boulder City Regional Office Building		48.00					Aug-13
NV	Online	River Mountains		Regional Office	Southern Nevada Water Authority and SunEdison		14,000.00					Jan-16

Lower Colorado Renewable Portfolio

State	Project Status	Project Name	FERC ID	Area Office	Operating Entity	Hydropower Type	Capacity (kW)	Project Initiation Date	Preliminary Permit or Lease Date	Exemption or CE Date	License or Lease Date	Online Date
NV	In Development	First Solar		Regional Office	First Solar Development, LLC		50,000.00	Jun-14				
CA	In Development	Blythe Office Solar Installation		Regional Office	USBR		19.00					
WIND PROJECTS												
AZ	In Development	Mohave County Wind Farm		Regional Office	BP Wind Energy North America		500,000.00					

Mid-Pacific Renewable Portfolio

State	Project Status	Project Name	FERC ID	Area Office	Operating Entity	Hydropower Type	Capacity (kW)	Project Initiation Date	Preliminary Permit or Lease Date	Exemption or CE Date	License or Lease Date	Online Date
RECLAMATION OWNED AND OPERATED												
CA	Online	Folsom		Central California	USBR	Conventional	207,000.00					1955
CA	Online	Judge Francis Carr		Northern California	USBR	Conventional	154,400.00					1963
CA	Online	Keswick		Northern California	USBR	Conventional	117,000.00					1950
CA	Online	Lewiston		Northern California	USBR	Conventional	350.00					1964
CA	Online	New Melones		Central California	USBR	Conventional	380,000.00					1979
CA	Online	Nimbus		Central California	USBR	Conventional	13,500.00					1955
CA	Online	Shasta		Northern California	USBR	Conventional	714,000.00					1944
CA	Online	Spring Creek		Northern California	USBR	Conventional	180,000.00					1964
CA	Online	Stampede		Lahontan Basin	USBR	Conventional	3,650.00					1988
CA	Online	Trinity		Northern California	USBR	Conventional	140,000.00					1964
RECLAMATION OWNED AND OPERATED BY OTHERS												
CA	Online	San Luis/Gianelli Pumping-Generating Plant		South Central California	California Department of Water Resources	Pump Storage	424,000.00					1968
NV	Online	Lahontan Powerplant		Lahontan Basin	Truckee-Carson Irrigation District	Conventional	2,400.00					1911
CA	Online	O'Neill Pumping-Generating Plant		South Central California	San Luis Delta-Mendota Water Authority	Pump Storage	25,200.00					1967
FEDERAL ENERGY REGULATORY COMMISSION PROJECTS												
OR	Online	East Side	2082	Klamath Basin	Scottish Power (PacifiCorp)	Conventional	3,200.00					
CA	Online	Friant Fishwater Release	11068	South Central California	Orange County Irrigation District	Conventional	510.00				5/16/1991	
CA	Online	Friant Power	2892	South Central California	Friant Power Authority	Conventional	27,360.00				9/30/1982	1991
CA	Online	High Line Canal	7252	Northern California	Santa Clara	Conventional	530.00				7/17/1984	
CA	Online	Madera Canal	5765	South Central California	Madera-Chowchilla Water & Power Authority	Conventional	440.00	11/16/1981	4/27/1982		9/8/1983	
CA	Online	Madera Canal Water Power STA 1174+84	2958	South Central California	Madera-Chowchilla Water & Power Authority	Conventional	563.00	11/23/1981			6/8/1982	
CA	Online	Madera Canal Water Power STA 1923+10	2958	South Central California	Madera-Chowchilla Water & Power Authority	Conventional	916.00	11/23/1981			6/8/1982	
CA	Online	Madera Canal Water Power STA 980+65	2958	South Central California	Madera-Chowchilla Water & Power Authority	Conventional	2,125.00	11/23/1981			6/8/1982	
CA	Online	Monticello	2780	Central California	Solano I.D.	Conventional	11,500.00				1/29/1981	Jun-83
NV	Online	New Lahontan	7828	Lahontan Basin	Truckee-Carson I.D.	Conventional	4,000.00				12/26/1985	6/12/1989
CA	Online	Stony Gorge Hydroelectric	3193	Northern California	Santa Clara, City of	Conventional	4,900.00				8/31/1982	Apr-86
OR	Online	West Side	2082	Klamath Basin	Scottish Power (PacifiCorp)	Conventional	600.00					
CA	Online	Whiskey Dam Power Project	2888	Northern California	City of Redding	Conventional	3,530.00	2/17/1982			3/10/1983	1986
CA	License	Friant Fishwater Release	11068	South Central California	Orange County Irrigation District	Conventional	7,000.00				5/16/1991	
CA	License	Humboldt River Hydropower Project (Rye Patch)	14327	Lahontan Basin	Pershing County Water Conservation District	Conventional	750.00	1/22/2011			1/31/2014	
OR	Preliminary	Bryant Mountain (Pumped Storage)	13680	Klamath Basin	Bryant Mountain LLC	Pump Storage	1,250,000.00	3/1/2010	9/24/2010			
LEASE OF POWER PRIVILEGE PROJECTS												
OR	Online	Klamath Canal Drop C		Klamath Basin	Klamath Irrigation District	Conventional	900.00	2/8/2011			11/8/2011	5/3/2012

Mid-Pacific Renewable Portfolio

State	Project Status	Project Name	FERC ID	Area Office	Operating Entity	Hydropower Type	Capacity (kW)	Project Initiation Date	Preliminary Permit or Lease Date	Exemption or CE Date	License or Lease Date	Online Date
CA	Request for Development	A-C3 (Panicker Drop)		Lahontan Basin	Truckee Carson Irrigation District	Conventional	125.00	2014				
CA	Request for Development	V-C2 (Lewis Wasteway)		Lahontan Basin	Truckee Carson Irrigation District	Conventional	250.00	2014				
SOLAR PROJECTS												
CA	In Development	San Luis Facility		South Central California	San Luis Renewables, LLC		26,000.00	8/5/2011				

Pacific Northwest Renewable Portfolio

State	Project Status	Project Name	FERC ID	Area Office	Operating Entity	Hydropower Type	Capacity (kW)	Project Initiation Date	Preliminary Permit or Lease Date	Exemption or CE Date	License or Lease Date	Online Date
RECLAMATION OWNED AND OPERATED												
ID	Online	Anderson Ranch		Snake River	USBR	Conventional	40,000.00					1950
ID	Online	Black Canyon		Snake River	USBR	Conventional	10,200.00					1925
ID	Online	Boise River Diversion		Snake River	USBR	Conventional	3,450.00					1912
WA	Online	Chandler		Columbia Cascades	USBR	Conventional	12,000.00					1956
WA	Online	Grand Coulee		Columbia Cascades	USBR	Conventional/Pump Storage	6,809,000.00					1941
OR	Online	Green Springs		Columbia Cascades	USBR	Conventional	17,290.00					1960
MT	Online	Hungry Horse		Columbia Cascades	USBR	Conventional	428,000.00					1952
ID	Online	Minidoka		Snake River	USBR	Conventional	27,700.00					1942
ID	Online	Palisades		Snake River	USBR	Conventional	176,564.00					1957
WA	Online	Roza		Columbia Cascades	USBR	Conventional	12,937.00					1958
FEDERAL ENERGY REGULATORY COMMISSION PROJECTS												
ID	Online	American Falls	2736	Snake River	Idaho Power Co	Conventional	92,400.00				3/31/1975	1975
ID	Online	ARROWROCK DAM	4656	Snake River	Big Bend Irrigation District, et. al.	Conventional	15,000.00		8/15/1983		3/27/1989	Mar-10
ID	Online	CASCADE	2848	Snake River	Idaho Power Co.	Conventional	12,420.00				2/17/1981	3/4/1985
WA	Online	COWICHE	7337	Columbia Cascades	Yakima-Tieton ID	Conventional	1,470.00				7/6/1984	1986
ID	Online	Dietrich Drop	8909	Snake River	Big Wood Canal Company	Conventional	4,770.00	3/7/1985			5/22/1987	1989
WA	Online	ELTOPIA BRANCH CANAL	3842	Columbia Cascades	East, Quincy, & South, Columbia Basin ID's	Conventional	2,200.00				12/9/1981	1982
WA	Online	ESQUATZEL POWER	12638	Columbia Cascades	Green Energy Today LLC	Conventional	900.00	1/4/2006		6/6/2008		Apr-12
ID	Online	FARGO DROP NO. 1	5042	Snake River	Boise Project Board of Control	Conventional	1,100.00			10/23/1981		Jun-13
ID	Online	FELT HYDRO	5089	Snake River	Fall River Rural Cooperative	Conventional	7,450.00				9/9/1983	1985
ID	Online	ISLAND PARK	2973	Snake River	Fall River Rural Electric	Conventional	4,800.00		7/8/1983		10/19/1988	1982
ID	Online	Little Wood Reservoir	7427	Snake River	Little Wood Irrigation District	Conventional	3,000.00			4/13/1984		1989
ID	Online	LOW LINE NO. 8 ARENA DROP	5056	Snake River	Boise Project Board of Control	Conventional	385.00	6/10/1981		10/23/1981		Apr-12
WA	Online	MAIN CANAL HEADWORKS	2849	Columbia Cascades	East, Quincy, & South, Columbia Basin I.D.'s	Conventional	26,000.00				11/16/1981	1987
ID	Online	Mile 28	10552	Snake River	Contractor's Power Group	Conventional	1,500.00	12/2/1987	9/15/1988		8/12/1992	1996
OR	Online	MITCHELL BUTTE LATERAL	5357	Snake River	Owyhee ID et. al.	Conventional	1,880.00		2/26/1982		12/14/1984	1990
ID	Online	Mora Drop Hydro	3403	Snake River	Boise Kuna Irrigation District et. Al	Conventional	1,900.00			12/18/1980		9/15/2006
WA	Online	ORCHARD AVENUE	7338	Columbia Cascades	Yakima-Tieton ID	Conventional	1,441.00				7/6/1984	1986
OR	Online	OWYHEE DAM	4354	Snake River	Gem I.D., Owyhee I.D., & Ridgeview I.D	Conventional	4,340.00				5/9/1984	1985
OR	Online	OWYHEE TUNNEL NO. 1	4359	Snake River	Gem ID et. al.	Conventional	8,120.00				2/28/1986	6/1/1983
WA	Online	POTHOLES EAST CANAL	3843	Snake River	East, Quincy, & South, Columbia Basin ID's	Conventional	2,400.00				12/9/1981	1982
WA	Online	POTHOLES EAST CANAL HEADWORKS	2840	Columbia Cascades	Grand Coulee Project Hydroelectric Authority	Conventional	6,500.00				9/21/1982	1991
WA	Online	QUINCY CHUTE	2937	Columbia Cascades	East, Quincy, & South, Columbia Basin I.D.'s	Conventional	9,367.00				8/20/1982	1983
WA	Online	RUSSEL D SMITH PEC 22.7	2926	Columbia Cascades	East, Quincy, & South, Columbia Basin I.D.'s	Conventional	6,100.00				3/27/1980	1982
WA	Online	SUMMER FALLS	3295	Columbia Cascades	East, Quincy, & South, Columbia Basin I.D.'s	Conventional	92,000.00				8/14/1981	1983
WA	Online	TIETON DAM	3701	Columbia Cascades	Yakima-Tieton Irrigation District	Conventional	13,600.00				6/27/1991	2007
OR	Online	45-Mile	13817	Columbia Cascades	Apple, Inc.	Conventional	5,000.00	7/16/2010		12/17/2010		5/13/2015

Pacific Northwest Renewable Portfolio

State	Project Status	Project Name	FERC ID	Area Office	Operating Entity	Hydropower Type	Capacity (kW)	Project Initiation Date	Preliminary Permit or Lease Date	Exemption or CE Date	License or Lease Date	Online Date
OR	Online	Monroe Drop	14430	Columbia Cascades	Apple, Inc.	Conventional	300.00	7/2/2012	3/28/2013	2/18/2015		10/29/2015
ID	Exemption	FARGO DROP NO. 2	5040	Snake River	Boise Project Board of Control	Conventional	175.00			10/23/1981		
ID	Exemption	MAIN CANAL NO. 10	5041	Snake River	East, Quincy, & South, Columbia Basin I.D.'s	Conventional	500.00			10/23/1981		
ID	Exemption	MAIN CANAL NO. 6	5038	Snake River	East, Quincy, & South, Columbia Basin I.D.'s	Conventional	1,055.00			10/23/1981		
ID	Exemption	WALDVOGEL BLUFF	5043	Snake River	Boise Project Board of Control	Conventional	300.00	6/30/1981		12/23/1981		
WA	Preliminary	16.4 Wasteway	14349	Columbia Cascades	Grand Coulee Project Hydroelectric Authority	Conventional	1,750.00	7/29/2011	3/26/2013			
WA	Preliminary	46A Wasteway	14351	Columbia Cascades	Grand Coulee Project Hydroelectric Authority	Conventional	1,600.00	7/29/2011	3/26/2013			
ID	Preliminary	Mason Dam Hydro	12686	Snake River	Baker County	Conventional	3,400.00	4/25/2006	5/26/2010			
WA	Preliminary	McKay Dam	14546	Columbia Cascades	Houtama Hydropower, LLC	Conventional	2,300.00	8/13/2013	2/6/2014			
WA	Preliminary	PEC 1973 Drop	14316	Columbia Cascades	Grand Coulee Project Hydroelectric Authority	Conventional	2,200.00	11/8/2011	3/26/2013			
WA	Preliminary	Pinto Dam	14380	Columbia Cascades	Grand Coulee Project Hydroelectric Authority	Conventional	3,400.00	4/4/2012	10/10/2012			
WA	Preliminary	Scooteney Inlet Drop	14318	Columbia Cascades	Grand Coulee Project Hydroelectric Authority	Conventional	1,700.00	5/31/2011	3/26/2013			
OR	Preliminary	Unity Dam by Warm Springs Hydro	14576	Snake River	Warm Springs Hydro, LLC	Conventional	800.00	1/13/2014	6/16/2014			
ID	Preliminary	Warm Springs Dam	13570	Snake River	Ted Sorenson	Conventional	2,700.00	8/12/2009	2/22/2010			
WA	Preliminary	Wickiup Dam Hydro	12965	Columbia Cascades	Symbiotics	Conventional	7,150.00	8/17/2007	5/15/2008			
WA	Preliminary	Banks Lake Pumped Storage Project	14329	Columbia Cascades	Grand Coulee Project Hydroelectric Authority	Pump Storage	1,000,000.00	11/30/2011	8/22/2013			
LEASE OF POWER PRIVILEGE PROJECTS												
ID	Request for Development	Cat Creek Energy Pump Storage Facility		Snake River	Cat Creek Energy, LLC	Pump Storage	400,000.00	11/5/2014				
SOLAR PROJECTS												
WA	Online	Grand Coulee Solar		Columbia Cascades	Grand Coulee		4.70					Oct-12
PILOT PROJECTS												
WA	Testing	Instream Energy Roza Division Hydrokinetics		Columbia Cascades	Instream Energy	Hydrokinetics	10.00					Aug-13

Upper Colorado Renewable Portfolio

State	Project Status	Project Name	FERC ID	Area Office	Operating Entity	Hydropower Type	Capacity (kW)	Project Initiation Date	Preliminary Permit or Lease Date	Exemption or CE Date	License or Lease Date	Online Date
RECLAMATION OWNED AND OPERATED												
CO	Online	Blue Mesa		Western Colorado	USBR	Conventional	86,400.00					1967
CO	Online	Crystal		Western Colorado	USBR	Conventional	31,500.00					1978
NM	Online	Elephant Butte		Albuquerque	USBR	Conventional	27,945.00					1940
UT	Online	Flaming Gorge		Provo	USBR	Conventional	151,500.00					1963
WY	Online	Fontenelle		Provo	USBR	Conventional	10,000.00					1968
AZ	Online	Glen Canyon		Western Colorado	USBR	Conventional	1,320,000.00					1965
CO	Online	Lower Molina		Western Colorado	USBR	Conventional	5,589.00					1962
CO	Online	Morrow Point		Western Colorado	USBR	Conventional	173,334.00					1971
CO	Online	Upper Molina		Western Colorado	USBR	Conventional	9,936.00					1962
RECLAMATION OWNED AND OPERATED BY OTHERS												
UT	Online	Causey Powerplant		Provo	Weber Basin Water Conservancy District	Conventional	1,900.00					1999
UT	Online	Deer Creek Powerplant		Provo	Provo River Water Users Association	Conventional	4,950.00					1958
UT	Online	Gateway Powerplant		Provo	Weber Basin Water Conservancy District	Conventional	4,275.00					1958
UT	Online	Lower Spanish Fork Powerplant		Provo	Strawberry Water User's Association	Conventional	250.00					1937
CO	Online	McPhee Powerplant		Western Colorado	Dolores Water Conservancy District	Conventional	1,283.00					1992
UT	Online	Olmsted Powerplant		Provo	Purchased from PacifiCorp in 1990	Conventional	10,300.00					1904
UT	Online	Payson Powerplant		Provo	Strawberry Water User's Association	Conventional	400.00					1941
CO	Online	Towaoc Powerplant		Western Colorado	Dolores Water Conservancy District	Conventional	11,495.00					1994
UT	Online	Upper Spanish Fork		Provo	Strawberry Water User's Association	Conventional	3,900.00					1909
UT	Online	Wanship Powerplant		Provo	Weber Basin Water Conservancy District	Conventional	1,900.00					1958
FEDERAL ENERGY REGULATORY COMMISSION PROJECTS												
UT	Online	Echo Dam	3755	Provo	City of Bountiful	Conventional	4,500.00		11/30/1981		12/7/1984	1987
NM	Online	El Vado Dam	5226	Albuquerque	County of Los Alamos	Conventional	8,000.00		1/4/1982		10/31/1985	7/1/1988
CO	Online	Navajo Dam	4720	Western Colorado	City of Farmington	Conventional	30,000.00				10/15/1985	2/1/1988
UT	Online	Pineview Dam	4597	Provo	Weber-Box Elder Conservancy District	Conventional	1,800.00				3/16/1984	1991
CO	Online	Vallecito Dam	3174	Western Colorado	Ptarmigan Resources & Energy, Inc.	Conventional	5,880.00				10/5/1983	5/1/1989
UT	Preliminary	Lake Powel Hurricane Cliffs Pumping Plant	12966	Regional Office	State of Utah	Pump Storage	300,000.00	8/21/2007	5/20/2011			
CO	Preliminary	Plateau Creek Pumped Storage	14426	Western Colorado	Dolores Water Conservancy District	Pump Storage	500,000.00	5/10/2012	10/1/2012			
LEASE OF POWER PRIVILEGE PROJECTS												
CO	Online	Grand Valley Project		Western Colorado	Grand Valley Water Users Assoc., Orchard Mesa Irrigation Dist., PSCO	Conventional	3,000.00				1933	1938
CO	Online	Jackson Gulch Dam		Western Colorado	Mancos Water Conservancy Dist.	Conventional	260.00				1995	1995
UT	Online	Jordanelle Dam		Provo	Central Utah Water Conservancy Dist., Heber Light and Power	Conventional	13,000.00	7/2/1999			2008	7/1/2008
CO	Online	Lemon Dam		Western Colorado	Florida Water Conservancy District	Conventional	120.00				1988	9/1/1988
CO	Online	South Canal (Drop 1)		Western Colorado	Uncompahgre Valley Water Users and the Delta-Montrose Electric Association	Conventional	4,000.00	8/26/2009			3/16/2012	6/3/2013
CO	Online	South Canal (Drop 3)		Western Colorado	Uncompahgre Valley Water Users and the Delta-Montrose Electric Association	Conventional	3,500.00	8/26/2009			3/16/2012	8/1/2013

Upper Colorado Renewable Portfolio

State	Project Status	Project Name	FERC ID	Area Office	Operating Entity	Hydropower Type	Capacity (kW)	Project Initiation Date	Preliminary Permit or Lease Date	Exemption or CE Date	License or Lease Date	Online Date
CO	Online	Ridgway Dam		Western Colorado	Tri-County Water Conservancy District	Conventional	7,000.00	6/2/2010			2/6/2012	4/3/2014
CO	Online	Shavano Falls		Western Colorado	Uncompahgre Valley Water Users Association	Conventional	2,800.00	8/21/2013	1/27/2014		6/18/2014	6/24/2015
CO	Online	South Canal (Drop 4)		Western Colorado	Uncompahgre Valley Water Users Association	Conventional	4,800.00	8/21/2013	5/14/2014		9/8/2014	6/24/2015
CO	Contract	South Canal (Drop 5)		Western Colorado	Uncompahgre Valley Water Users Association	Conventional	2,400.00	3/3/2015	6/18/2015		11/5/2015	
UT	Preliminary	Spanish Fork Flow Control Structure	LP11-2	Provo	Central Utah Water Conservancy District, Strawberry Water users Association, and South Utah Valley Electric Service District	Conventional	8,000.00	5/11/2011	3/9/2012			
NM	Posted Solicitation	San Juan Chama Project	LP12-1-000	Albuquerque	Albuquerque Bernalillo County Water Utility Authority	Conventional	100.00	7/6/2012				
CO	Request for Development	Rifle Gap Dam		Western Colorado		Conventional	341.00	4/1/2013				
UT	Request for Development	Diamond Fork		Central Utah Project Completion Act Office	Central Utah Water Conservancy District	Conventional	12,214.00	Nov-14				
PILOT PROJECTS												
CO	Contract	South Canal (Drop 2)		Western Colorado	Percheron Power, LLC, Uncompahgre Valley Water Users Association	Hydrodynamic Screw	987.00	5/27/2014	7/29/2014	9/17/2014	12/17/2014	

Turbine replacements (efficiency gains) and rewinds (capacity gains) completed at Reclamation reserved facilities 1999 - present

Competed 12/2/2014 Revised 3/21/2016

NOTE: Data is considered provisional and is subject to revision.

Region	Facility	Unit	Year turbine replacement completed	Estimated PEAK efficiency gain*	Year rewind completed	Rewind capacity gain (kW)	Unit capacity (includes rewind, if completed) (kW)	Efficiency gain kW equivalent	Historical annual generation (before upgrade, 10 year average) (kWh)	Expected increase in annual kWh due to efficiency gain, given historical annual generation
PN	Grand Coulee	3	2001	3.72%			125,000.00	4,650.00	564,255,400.00	20,990,300.88
GP	Yellowtail	3	2001	3.16%	Feb-16	9,375.00	62,500.00	1,975.00	251,091,100.00	7,934,478.76
GP	Yellowtail	4	2001	3.16%	Rewind Scheduled	9,375.00	62,500.00	1,975.00	229,411,600.00	7,249,406.56
PN	Grand Coulee	12	2003	4.50%			125,000.00	5,625.00	522,280,700.00	23,502,631.50
MP	Shasta	4	2003	3.90%	2003	17,000.00	142,000.00	5,538.00	353,250,620.00	13,776,774.18
PN	Grand Coulee	1	2004	3.72%			125,000.00	4,650.00	576,537,200.00	21,447,183.84
PN	Grand Coulee	7	2004	3.35%			125,000.00	4,187.50	382,608,900.00	12,817,398.15
PN	Grand Coulee	11	2004	4.50%			125,000.00	5,625.00	543,513,900.00	24,458,125.50
MP	Shasta	5	2004	3.90%	2000, 2005	41,000.00 (2000), 17,000.00 (2005)	142,000.00	5,538.00	420,613,500.00	16,403,926.50
PN	Grand Coulee	17	2005	4.50%			125,000.00	5,625.00	622,675,050.00	28,020,377.25
LC	Parker	3	2005	4.86%			30,000.00	1,458.00	145,895,997.00	7,090,545.45
MP	Shasta	3	2005	3.90%	2000, 2005	41,000.00 (2000), 17,000.00 (2005)	142,000.00	5,538.00	421,834,500.00	16,451,545.50
UC	Flaming Gorge	3	2006	5.92%			50,500.00	2,989.60	165,872,422.00	9,819,647.38
PN	Grand Coulee	2	2006	3.72%			125,000.00	4,650.00	594,458,400.00	22,113,852.48
PN	Grand Coulee	16	2006	4.50%			125,000.00	5,625.00	563,154,200.00	25,341,939.00
MP	Shasta	S2	2006	3.90%			2,000.00	78.00	1,992,520.00	77,708.28
UC	Flaming Gorge	2	2007	5.92%			50,500.00	2,989.60	159,148,122.00	9,421,568.82
UC	Glen Canyon	8	2007	3.37%			165,000.00	5,560.50	392,393,800.00	13,223,671.06
PN	Grand Coulee	6	2007	3.72%			125,000.00	4,650.00	487,485,600.00	18,134,464.32
MP	Shasta	1	2007	3.90%	2007	17,000.00	142,000.00	5,538.00	387,992,100.00	15,131,691.90
UC	Flaming Gorge	1	2008	5.92%			50,500.00	2,989.60	131,960,556.00	7,812,064.92
PN	Grand Coulee	9	2008	3.35%			125,000.00	4,187.50	402,066,900.00	13,469,241.15
PN	Grand Coulee	14	2008	4.50%			125,000.00	5,625.00	599,680,900.00	26,985,640.50
PN	Grand Coulee	15	2008	4.50%			125,000.00	5,625.00	595,591,200.00	26,801,604.00
LC	Parker	1	2008	4.86%			30,000.00	1,458.00	107,171,649.00	5,208,542.14
MP	Shasta	2	2008	3.90%	2008	17,000.00	142,000.00	5,538.00	468,679,500.00	18,278,500.50
PN	Grand Coulee	4	2009	3.72%			125,000.00	4,650.00	294,230,700.00	10,945,382.04
PN	Grand Coulee	5	2009	3.72%			125,000.00	4,650.00	396,670,800.00	14,756,153.76
PN	Grand Coulee	10	2009	4.50%			125,000.00	5,625.00	519,804,500.00	23,391,202.50
LC	Hoover	N4	2009	2.00%			130,000.00	2,600.00	305,551,900.00	6,111,038.00
LC	Parker	2	2009	4.86%			30,000.00	1,458.00	139,367,070.00	6,773,239.60
UC	Glen Canyon	6	2010	3.37%			125,000.00	4,212.50	658,459,100.00	22,190,071.67
PN	Grand Coulee	8	2010	3.35%			125,000.00	4,187.50	416,142,100.00	13,940,760.35
PN	Grand Coulee	13	2010	4.50%			125,000.00	5,625.00	536,669,900.00	24,150,145.50
LC	Hoover	A6	2010	2.00%			130,000.00	2,600.00	444,892,200.00	8,897,844.00
LC	Parker	4	2010	4.86%			30,000.00	1,458.00	101,716,858.10	4,943,439.30
MP	Folsom	2	2011	2.37%			69,000.00	1,635.30	189,827,300.00	4,498,907.01
UC	Glen Canyon	7	2011	3.37%			165,000.00	5,560.50	359,775,506.00	12,124,434.55
PN	Grand Coulee	18	2011	4.50%			125,000.00	5,625.00	605,374,330.00	27,241,844.85
LC	Hoover	N3	2011	2.00%			130,000.00	2,600.00	363,158,000.00	7,263,160.00
MP	Judge Francis Carr	1	2011	3.94%			77,200.00	3,041.68	200,695,000.00	7,907,383.00
GP	Fremont Canyon	1	2012	1.07%			33,400.00	357.38	99,616,400.00	1,065,895.48
GP	Fremont Canyon	2	2012	1.07%			33,400.00	357.38	101,404,300.00	1,085,026.01
UC	Glen Canyon	1	2012	3.37%			165,000.00	5,560.50	342,364,017.00	11,537,667.37
UC	Glen Canyon	5	2012	3.37%			165,000.00	5,560.50	553,688,300.00	18,659,295.71
LC	Hoover	N8	2012	2.75%			130,000.00	3,575.00	114,143,500.00	3,138,946.25
MP	Judge Francis Carr	2	2012	3.94%			77,200.00	3,041.68	192,687,400.00	7,591,883.56
MP	Folsom	1	2013	2.37%			69,000.00	1,635.30	173,095,830.00	4,102,371.17
UC	Glen Canyon	4	2013	3.37%			165,000.00	5,560.50	676,186,298.00	22,787,478.24

Generation Gains 1999-Present revised 3-21-2016

Region	Facility	Unit	Year turbine replacement completed	Estimated PEAK efficiency gain*	Year rewind completed	Rewind capacity gain (kW)	Unit capacity (includes rewind, if completed) (kW)	Efficiency gain kW equivalent	Historical annual generation (before upgrade, 10 year average) (kWh)	Expected increase in annual kWh due to efficiency gain, given historical annual generation
PN	Palisades	1	2013	3.00%			44,141.00	1,324.23	119,482,100.00	3,584,463.00
UC	Glen Canyon	3	2014	3.37%			165,000.00	5,560.50	593,352,199.00	19,995,969.11
LC	Hoover	A1	2014	3.00%			130,000.00	3,900.00	73,344,600.00	2,200,338.00
LC	Hoover	A8	2014	3.00%			61,500.00	1,845.00	47,508,900.00	1,425,267.00
PN	Palisades	4	2014	4.00%			44,141.00	1,765.64	171,152,800.00	6,846,112.00
LC	Hoover	N6	2015	3.00%			130,000.00	3,900.00	417,877,800.00	12,536,334.00
PN	Palisades	3	2015	4.86%			44,141.00	2,145.25	152,887,500.00	7,430,332.50
UC	Glen Canyon	2	Nov-15	3.37%			165,000.00	5,560.50	505,575,202.00	17,037,884.31
MP	Folsom	3	Ongoing Turbine Replacement	2.37%			69,000.00	1,635.30	213,883,600.00	5,069,041.32
PN	Minidoka	9	Ongoing Turbine Replacement	TBD						
PN	Palisades	2	Ongoing Turbine Replacement	4.00%			44,141.00	1,765.64	152,954,500.00	6,118,180.00
MP	Trinity	1	Ongoing Turbine Replacement	TBD			70,000.00		228,127,460.00	
LC	Hoover	A0	Scheduled Turbine Replacement	3.00%			2,400.00	72.00	8,147,731.00	244,431.93
LC	Hoover	N0	Scheduled Turbine Replacement	3.00%			2,400.00	72.00	8,944,610.00	268,338.30
LC	Hoover	N5	Scheduled Turbine Replacement	3.00%			130,000.00	3,900.00	181,392,200.00	5,441,766.00
MP	Trinity	2	Scheduled Turbine Replacement	TBD			70,000.00		176,475,850.00	
GP	Alcova	1			2002	2,700.00	20,700.00	-	60,365,400.00	-
GP	Alcova	2			2001	2,700.00	20,700.00	-	55,632,300.00	-
PN	Boise River Diversion	1			2004	650.00	1,150.00	-	0.00	-
PN	Boise River Diversion	2			2004	650.00	1,150.00	-	0.00	-
PN	Boise River Diversion	3			2004	650.00	1,150.00	-	0.00	-
UC	Crystal	1			2004	3,500.00	31,500.00	-	179,659,000.00	-
UC	Lower Molina	1			2013	730.00	5,589.00	-	15,589,677.00	-
UC	Upper Molina	1			2013	1,300.00	9,936.00	-	26,470,249.00	-
GP	Yellowtail	1			Rewind Scheduled	9,375.00	62,500.00	-	193,621,800.00	-
GP	Yellowtail	2			Rewind Scheduled	9,375.00	62,500.00	-	161,230,100.00	-
***Note: Performance testing has a 0.75-1.0 percent uncertainty**										